



## HDS 6/12 C

Compact hot water high pressure cleaner with ecoefficiency mode and steam function



### 1 Efficiency

- ecoefficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO<sub>2</sub> emissions by 20%.

### 2 Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.



### 3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.



### 4 Mobility

- Jogger principle with large wheels and steering roller.
- Large integrated handles in the chassis.



HDS 6/12 C

■ Economical ecoefficiency mode

Technical data		
Order Number		1.169-904.0
EAN code		4054278167206
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	240-560
Pressure	bar / MPa	30-120 / 3-12
Max. temperature	°C	80 / 155
Power rating	kW	3
Consumption fuel oil	kg/h	3,5
Fuel tank	l	15
Weight	kg	93
Dimensions (L x W x H)	mm	1060 × 650 × 920

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / ID 6, 250 bar
Spray lance	mm	1050
Power nozzle		■
SDS system		■
Anti-twist system (AVS)		-
Pressure switch control		■
Integral fuel and detergent tank		■
Servo Control		■

■ Included in delivery.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	ID	Max. working pressure	Length	Price	Description	
<b>Standard with unions on both sides</b>								
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5 with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	▲
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	▲
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			▲
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			▲
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l/h. With union on both sides. 2x M 22 x 1.5 with anti-kink protection.	▲
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m			▲
High-pressure hose, 10 m DN 6, AVS trigger gun connector	11	6.110-035.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	■
	12	6.110-034.0	ID 6	250 bar	10 m			□
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connection	13	6.110-056.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
<b>Longlife 400 with unions on both sides</b>								
High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling	14	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 20 m, DN 8, extension	15	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling	16	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose 1.5 m, DN 8, including connectors	17	6.110-024.0	ID 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
	18	6.110-069.0	ID 8	400 bar	1.5 m			□
High-pressure hose packaged	19	6.110-038.0	ID 8	400 bar	10 m			□
<b>Food industry version with unions on both sides</b>								
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	20	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	21	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0


**KÄRCHER**



		Order Number	ID	Max. working pressure	Length	Price	Description	
<b>Longlife food industry version with unions on both sides</b>								
High pressure hose food DN 8 / 10 m	22	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	▲
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	23	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	□
<b>Food industry version</b>								
High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	24	6.110-063.0	ID 6	250 bar	15 m		15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C  
1.169-904.0



		Order Number	Flow rate					Price	Description
Trigger guns									
Extended easy press trigger gun	1	4.118-005.0							Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector. ■
Servo Control									
Servo control	2	4.118-007.0	0-750 l/h						Servo control for water flow and pressure control (< 750 l/h) on trigger gun. □
Quick connect									
Quick-fitting pipe union coupler trapezo	3	2.115-000.0							□
Quick-fitting pipe union plug nipple tra	4	2.115-001.0							

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Nozzle size				Price	Description	
<b>Power nozzle spray angle 25°</b>									
Power nozzle, spray angle 25°	1	2.113-007.0	42						■
<b>HP nozzle spray angle 0°</b>									
High-pressure nozzle spray angle 0°	2	2.113-033.0	45					High-pressure nozzle with powerful jet for extremely stubborn dirt.	□
<b>Power nozzle spray angle 15°</b>									
Power nozzle spray angle 15°	3	2.113-046.0	45					Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	□
<b>Power nozzle spray angle 40°</b>									
Power nozzle spray angle 40°	4	2.113-053.0	45					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.



# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Max. working pressure	Length		Price	Description	
<b>Rotating spray lances</b>								
1050 mm lance, rotatable, ergonomic	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm				□
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm				□
Rotatable lance, 600 mm, ergonomic	4	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 1550 mm, rotatable, ergonomic	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 2050 mm, rotatable, ergonomic	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Jet pipe extension TR 1000 mm	8	4.112-048.0	300 bar	1000 mm				□
<b>Double lance</b>								
Double lance 960 mm	9	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
<b>Angular spray lance</b>								
WC and gutter lance	10	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
<b>Flexible spray lance</b>								
Flexible lance 1050 mm	11	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
<b>Telescopic spray lance</b>								
Telescopic jet pipe	12	4.112-037.0	225 bar	5400 mm				□
Restraint belt for telescopic jet pipe	13	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	□
<b>Gutter cleaner</b>								
Gutter cleaning lance	14	2.112-015.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□
<b>Undercarriage spray lance</b>								
Underbody lance	15	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	□
<b>Additional handle</b>								
	16	4.321-380.0						□
<b>Weed control</b>								
WR 50 trapezoidal thread	17	2.114-013.0						□
WR 20 trapezoidal thread	18	2.114-014.0						□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C  
1.169-904.0



		Order Number						Price	Description	
Crane lifting kit										
Add-on kit suspension crane HDS C	1	2.642-638.0								<input type="checkbox"/>
Flame monitoring attachment kit										
ABS flame monitor for HDS C	2	2.642-711.0								<input type="checkbox"/>
Y distributor										
Y distributor	3	4.111-024.0								<input type="checkbox"/>


■ Included in delivery.    □ Available accessories.    ▲ Extension hose.



# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Flow rate	Nozzle size		Price	Description	
<b>Hard Surface Cleaner FRV 30</b>								
Add-on kit hose attachment	1	2.642-528.0						<input type="checkbox"/>
Add-on kit dirt trap	2	2.642-532.0						<input type="checkbox"/>
<b>Hard surface cleaner FR 30 ME</b>								
FR 30 ME surface cleaner	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
<b>Machine-specific nozzle kit for FR</b>								
Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h	4	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	<input type="checkbox"/>
<b>Machine-specific nozzle kits for FRV</b>								
Nozzle kit 045 for FRV 30	5	2.642-432.0		45				<input type="checkbox"/>
<b>Hard surface cleaner FRV 30 Me</b>								
Suction hose FRV 30 me	6	4.441-040.0						<input type="checkbox"/>
FRV 30 ME	7	2.111-012.0						<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number						Price	Description	
<b>Nozzle union</b>										
Protection part TR only for replacement	1	4.112-011.0								<input type="checkbox"/>
<b>Spacer (including nozzle union)</b>										
Spacer (incl.nozzle union)	2	5.394-294.0							Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	<input type="checkbox"/>
<b>Coupling parts</b>										
	3	6.987-705.0								<input type="checkbox"/>
<b>Rotary coupling</b>										
Rotary coupling	4	4.111-021.0							Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	<input type="checkbox"/>
<b>Coupling</b>										
Coupler -2xM22x1,5	5	4.111-037.0							Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	<input type="checkbox"/>
<b>Connector</b>										
Nozzle connector/screw connector	6	4.111-022.0							Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	<input type="checkbox"/>
	7	4.111-038.0								<input type="checkbox"/>
<b>Adapter EASY!Lock</b>										
Adapter 1 M22AG-TR22AG	8	4.111-029.0								<input type="checkbox"/>
Adapter 2 M22IG-TR22AG	9	4.111-030.0								<input type="checkbox"/>
Adapter 3 M22IG-TR22AG	10	4.111-031.0								<input type="checkbox"/>
Adapter M22 - Swivel	11	4.111-032.0							M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	<input type="checkbox"/>
Adapter 5 TR22IG-M22AG	12	4.111-033.0								<input type="checkbox"/>
Adapter 6 TR22IG-M22AG	13	4.111-034.0								<input type="checkbox"/>
Adapter 7 M18IG-TR20AG	14	4.111-035.0								<input type="checkbox"/>
Adapter 8 TR20IG-M18AG	15	4.111-036.0								<input type="checkbox"/>
<b>Flue pipe</b>										
Flue gas adapter	16	4.656-149.0							Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	<input type="checkbox"/>
	17	4.656-080.0								<input type="checkbox"/>
<b>HP detergent injector</b>										
Detergent injector for high and low pressure (without nozzles)	18	4.637-032.0							Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	<input type="checkbox"/>
Detergent injector for high pressure	19	4.637-033.0							Cleaning agent dosage at high pressure 3 - 5 %	<input type="checkbox"/>
<b>Machine-specific nozzle kit with order no. 3.637-170</b>										
Machine-specific nozzle kit with order no. 3.637-170.0 HD 500-700 l/h	20	4.769-046.0							For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C  
1.169-904.0




		Order Number					Price	Description	
Nozzle insert with order no. 3.637-001									
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	21	4.769-003.0						Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	<input type="checkbox"/>
Low pressure for units rated up to 1100 l/h	22	4.769-001.0						For low pressure with machines up to 1.100 l/h	<input type="checkbox"/>

■ Included in delivery.    □ Available accessories.    ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0


**KÄRCHER**



		Order Number	Max. working pressure	Nozzle size		Price	Description	
<b>Barrel and tank cleaning</b>								
	1	2.112-020.0						<input type="checkbox"/>
<b>Pipe cleaning hose, ID 6</b>								
Hose assembly TR pipe cleaning DN6 max.2	2	6.110-046.0	250 bar					<input type="checkbox"/>
Pipe cleaning hose, DN 6, 20 m, 220 bar	3	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 max.2	4	6.110-047.0	250 bar					<input type="checkbox"/>
<b>Pipe cleaning nozzle</b>								
Drain cleaning dirt blaster D 25/040	5	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	<input type="checkbox"/>
Drain cleaning dirt blaster D 30/040	6	6.415-946.0		40	30 mm			<input type="checkbox"/>
Drain cleaning dirt blaster D 35/040	7	6.415-948.0		40	35 mm			<input type="checkbox"/>
Nozzle pipe cleaning size 120	8	5.763-089.0		120	16 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	<input type="checkbox"/>
Pipe cleaning nozzle	9	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
	10	5.763-016.0		60	16 mm			<input type="checkbox"/>
	11	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
Rotating pipe cleaning nozzle	12	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C  
1.169-904.0



		Order Number	Max. working pressure	Nozzle size			Price	Description	
<b>Angle vario nozzle 0°-90°</b>									
Variable angle nozzle 0-90°	1	4.113-006.0		80				Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.	<input type="checkbox"/>
<b>Dirt blaster, large</b>									
Dirt blaster - without changeover function	2	4.114-027.0	300 bar	50				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	<input type="checkbox"/>

■ Included in delivery.    □ Available accessories.    ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Nozzle size				Price	Description	
<b>Wet blasting attachment (without nozzle)</b>									
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	<input type="checkbox"/>
<b>Nozzle pack for wet blasting attachment</b>									
Nozzle pack TR wet jet set 0045	3	2.112-022.0	45						<input type="checkbox"/>
<b>Boron carbide nozzle</b>									
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Flow rate				Price	Description	
<b>Cup foam lance</b>									
Packing complete for 6.394-969.0	1	2.112-018.0							<input type="checkbox"/>
Tank 1L	2	6.414-954.0							<input type="checkbox"/>
<b>Inno Foam Set</b>									
Inno foam kit with detergent injector	3	2.112-000.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	<input type="checkbox"/>
Inno foam kit	4	2.112-008.0							<input type="checkbox"/>
<b>Easy Foam Set</b>									
Easy Foam Set with RM injector	5	2.112-010.0						HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	<input type="checkbox"/>
Easy foam set	6	2.112-011.0							<input type="checkbox"/>
<b>Nozzle kits for Inno/Easy Foam Set</b>									
Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h	7	2.111-018.0	600-700 l/h					Optimal adaptation to different machine outputs for economic use.	<input type="checkbox"/>
<b>Foam nozzle mounting kit</b>									
Foam nozzle kit	8	2.112-013.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	<input type="checkbox"/>


■ Included in delivery. □ Available accessories. ▲ Extension hose.



# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Length					Price	Description	
<b>Hose reel add-on kit</b>										
Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C	1	2.110-010.0	20 m							<input type="checkbox"/>
<b>Automatic, self-winding hose reels</b>										
Add-on kit automatic hose reel HDS-C	2	2.110-012.0	20 m							<input type="checkbox"/>
Add-on kit hose reel	3	2.110-013.0								<input type="checkbox"/>
Add-on kit hose reel plastics	4	6.392-074.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Add-on kit hose reel	5	6.392-083.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>
Hose reel, automatic, 20 m, painted	6	6.392-106.0	20 m						Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
	7	6.392-105.0	20 m							<input type="checkbox"/>
Hose reel, automatic, 20 m, stainless steel	8	6.392-076.0	20 m						Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
ABS hose reel stainless steel	9	6.392-122.0	20 m						High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled spring drive. Connection for HP hoses with nipple.	<input type="checkbox"/>
Swivel holder	10	2.639-931.0							Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
ABS wall fastening stainless steel	11	2.641-867.0							Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C  
1.169-904.0



		Order Number	Flow rate				Price	Description	
Push-on washing brush									
Push-on wash brush, M 18 x 1.5	1	4.113-001.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	<input type="checkbox"/>
Rotating washing brush									
	2	4.113-004.0	500-800 l/h						<input type="checkbox"/>
	3	4.113-003.0	500-800 l/h						<input type="checkbox"/>

■ Included in delivery.    □ Available accessories.    ▲ Extension hose.

# ACCESSORIES FOR HDS 6/12 C

## 1.169-904.0

**KÄRCHER**



		Order Number	Length	Diameter			Price	Description	
<b>Geka coupling</b>									
With hose nozzle, R 1/2"	1	6.388-461.0						with hose liner	<input type="checkbox"/>
With hose nozzle, R 3/4"	2	6.388-455.0							<input type="checkbox"/>
With hose nozzle, R 1"	3	6.388-465.0							<input type="checkbox"/>
Hose coupling	4	6.388-458.0						with female thread	<input type="checkbox"/>
<b>Suction filter</b>									
Water filter	5	6.414-956.0							<input type="checkbox"/>
Suction filter with check valve	6	4.730-012.0						Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>
<b>Fine-mesh water filter</b>									
Fine-mesh water filter with adapter	7	4.730-102.0						Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
Fine-mesh water filter, 100 µm, R 1"	8	2.638-270.0						Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	<input type="checkbox"/>
<b>Water supply hose</b>									
Water supply hose	9	4.440-038.0	7,5 m					NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
	10	4.440-207.0	7,5 m					NW 19 R1" / R 3/4", up to 85 °C, for pick-up	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.