### KARCHER



### HDS 12/18-4 S

Super class hot water high-pressure cleaner with a two lance operation option.



#### 1 Water treatment unit

- In the Eco setting the unit operates in the most economical temperature range (60°C) with full water flow.
- Burner cycles are optimised to reduce fuel consumption by up to 20% compared to full-load operation.

#### 2 Maximum efficiency

- Highly efficient burner technology.
- 4-pole electric motor with 3 piston axial pump.



- Roomy storage compartment for cleaning agents, gloves and tools.
- Within easy reach for left-handed or right-handed users and ideal for two-lance operation.

#### 4 Detergent regulation

- Precise metering valve ensures low consumption.
- Easy changeover between cleaning agent tanks 1 and 2.

### **TECHNICAL DATA AND EQUIPMENT.**

### KARCHER



#### HDS 12/18-4 S

- 2-lance operation possibleTwo detergent tanksEconomical ecolefficiency mode

Technical data				
Order Number		1.071-917.0		
EAN code		4054278140391		
Current type	Ph / V / Hz	3 / 420 / 50		
Flow rate	l/h	600-1200		
Pressure	bar / MPa	30-180 / 3-18		
Max. temperature	°C	80 / 155		
Power rating	kW	8,4		
Consumption fuel oil	kg/h	7,7		
Fuel tank	I	25		
Weight	kg	178		
Dimensions (L x W x H)	mm	1330 × 750 × 1060		
Equipment				
Trigger gun		EASY!Force Advanced	Two detergent tanks	•
High-pressure hose	m	10 / Longlife / DN 8,400 bar	Dry running protection	•
Spray lance	mm	1050		
Power nozzle		•		
Servo Control		•		
Anti-twist system (AVS)		-		
Three piston axial pump		with ceramic piston		
Pressure switch control		•		
Optional two-lance operation		•		
SDS system		•		
Electronic service control with LED display		•		
Included in delivery.				



		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides	;							
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l , h. With union on both sides. 2x M 22 x 1.5 with anti-kink	1
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m		protection.	
Longlife 400 with unions on both si	ides							
High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling	11	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 20 m, DN 8, extension	12	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling	13	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose packaged	14	6.110-038.0	ID 8	400 bar	10 m			
High-pressure hose 1.5 m, DN 8, including connectors	15	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
Food industry version with unions	on bot	1		1				
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	16	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	17	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	
Longlife food industry version with	n unior	ns on both sides						
High pressure hose food DN 8 / 10 m	18	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	5

■ Included in delivery. 
□ Available accessories. ▲ Extension hose.

HDS 12/18-4 S, 1.071-917.0, 2017-07-19

KARCHER



	Order Number	Flow rate				Price	Description
1	4.118-005.0						Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.
2	4.118-009.0	1100 l/h					
3	2.115-000.0						c
4	2.115-001.0						
	2	1     4.118-005.0       2     4.118-009.0       3     2.115-000.0	2 4.118-009.0 1100 l/h 3 2.115-000.0	1     4.118-005.0       2     4.118-009.0       3     2.115-000.0	1     4.118-005.0       2     4.118-009.0       3     2.115-000.0	1     4.118-005.0       2     4.118-009.0       3     2.115-000.0	1     4.118-005.0       2     4.118-009.0       3     2.115-000.0

HDS 12/18-4 S, 1.071-917.0, 2017-07-19



		Order Number	Nozzle size			Price	Description
Power nozzle spray angle 25°					1		
Power nozzle spray angle 25°	1	2.113-027.0	68				Fan jet nozzle for large-area coverage and stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	2	2.113-037.0	75				High-pressure nozzle with powerful jet for extremely stubborn dirt.
Power nozzle spray angle 15°							
Power nozzle spray angle $15^\circ$	3	2.113-049.0	70				Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
Power nozzle spray angle 40°							
Power nozzle spray angle $40^{\circ}$	4	2.113-056.0	75				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.			



		Order Number	Max. working pressure	Length		Price	Description	
Rotating spray lances								
1050 mm lance, rotatable, ergonomic	1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm				
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm				
Rotatable lance, 600 mm, ergonomic	4	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 1550 mm, rotatable, ergonomic	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 2050 mm, rotatable, ergonomic	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Jet pipe extension TR 1000 mm	8	4.112-048.0	300 bar	1000 mm				
Double lance								
Double lance 960 mm	9	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use ( e.g. stable cleaning).	
Angular spray lance								
WC and gutter lance	10	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance								
Flexible lance 1050 mm	11	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance		L		1			1	
Telescopic jet pipe	12	4.112-037.0	225 bar	5400 mm				
Restraint belt for telescopic jet pipe	13	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	
Gutter cleaner		L		1			,	
Gutter cleaning lance	14	2.112-015.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance								
Underbody lance	15	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle				1				
	16	4.321-380.0						
Weed control					1	1		1
WR 50 trapezoidal thread	17						-	
WR 20 trapezoidal thread	18	2.114-014.0	▲ Extension h					



								Τ
		Order Number				Price	Description	
Crane lifting kit								
Crane loading kit for HDS middle	1	2.642-424.0					Effortless loading by crane.	
and super class								
Grey wheel kit								
Grey wheel kit HDS M/S	2	2.641-975.0						
Flame monitoring attachment kit								
ABS flame monitor for HDS M/S	3	2.641-796.0					More safety thanks to ABS HDS M/S flame monitoring	
							system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes.	
Y distributor					I	 	supply cuts our automatically in the name extinguishes.	-
Y distributor	4	4.111-024.0						
Accumulator kits								
Add-on accumulator for HDS M/S	5	2.641-803.0					The accumulator can be mounted on the HDS machine in	
							order to dampen pressure surges, which conserves the	
							machine's line system.	
Remote control set								
Remote control set	6	2.642-157.0						
Coin-op remote control								
Coin-op remote control	7	2.642-158.0						
■ Included in delivery. □ Av	ailable	e accessories.	Extension ho	ose.				

### KARCHER

				4	3	5	0	
		Order Number	Flow rate	Nozzle size			Price	Description
Hard Surface Cleaner FRV 30		1						
Add-on kit hose attachment		2.642-528.0						
Add-on kit dirt trap	2	2.642-532.0						
Hard surface cleaner FR 30 ME FR 30 ME surface cleaner	3	2.111-013.0			300 mm			Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50		1						noose y.
FR 50 surface cleaner	4	2.111-023.0			500 mm			Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kit for FF Nozzle kit for surface cleaners (type-specific) 1100 - 1300 l/h		2.639-188.0	1100-1300 l/h					Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h).
Machine-specific nozzle kits for F	RV	1			<u> </u>			sorrace creations (1100 to 1500 i/ii).
Nozzle pack 080		2.642-982.0		80				
Hard surface cleaner FRV 30 Me								
Suction hose FRV 30 me		4.441-040.0						
FRV 30 ME	8	2.111-012.0						
Surface Cleaner FR 50 Me	0	2.111-024.0						
■ Included in delivery. □ A		e accessories.	Extension ho	DSE.				

				5		6		$\left  \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$
		Order Number					Price	Description
Nozzle union Protection part TR only for	1	4.112-011.0						
replacement								
Spacer (including nozzle union) Spacer (incl.nozzle union)	2	5.394-294.0						Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.
Coupling parts	З	6.987-705.0	1					
Rotary coupling		0.387-705.0			<u> </u>			
Rotary coupling	4	4.111-021.0						Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.
Coupling	_						1	
Coupler -2xM22x1,5	5	4.111-037.0						Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.
Connector								
Nozzle connector/screw connector	6	4.111-022.0						Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.
	7	4.111-038.0						
Adapter EASY!Lock								
Adapter 1 M22AG-TR22AG	8	4.111-029.0						
Adapter 2 M22IG-TR22AG	9	4.111-030.0						_
Adapter 3 M22IG-TR22AG Adapter M22 - Swivel	10 11	4.111-031.0 4.111-032.0						M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS
Adapter 5 TR22IG-M22AG	12	4.111-033.0						connection.
Adapter 6 TR22IG-M22AG	12	4.111-033.0						-
Adapter 7 M18IG-TR20AG	14	4.111-035.0			+ +			
Adapter 8 TR20IG-M18AG	15	4.111-036.0						
Flue pipe								
Flue gas adapter	16	4.656-079.0						Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).
HP detergent injector								
	17	6.645-763.0			+			-
Detergent injector for high and low pressure (without nozzles) Detergent injector for high	18 19 20	6.500-000.0 4.637-032.0 4.637-033.0						Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. Cleaning agent dosage at high pressure 3 - 5 %
pressure								
Machine-specific nozzle kit with or		1	1		1 1		1	
Machine-specific nozzle kit with order no. 3.637-170.0 1000-1200 I/h I/h	21	4.769-048.0						For HD/HDS 1000 - 1200 I/h. Consists of nozzle insert + HP power nozzle + union

HDS 12/18-4 S, 1.071-917.0, 2017-07-19



		Order Number					Price	Description	
Nozzle insert with order no. 3.637-	001				I	<u> </u>	<u> </u>		1
High pressure for units rated 1100	22	4.769-002.0						For high pressure with machines above 1.100 l/h	
l/h or more									
Low pressure for units rated 1100	23	4.769-006.0						For low pressure with machines above 1.100 l/h	
I/h or more									
■ Included in delivery □ Av	ailahle	e accessories	Extension h	nse					

### KARCHER













		Order Number	Max. working pressure	Nozzle size		Price	Description	
Barrel and tank cleaning							L L L	
	1	2.112-020.0						
HKF 50 spray head, brass								
HKF 50 spray head , brass	2	3.631-039.0					Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally	
	3	3.631-058.0						
Nozzle kit for HKF 50 spray head (3	8.631-0	009.0 / 3.631-039	9.0)					
Nozzle 090 for single nozzle operation HKF 50	4	6.415-447.0		90			Nozzle for single-nozzle operation	
Cone for plugging into bungholes	5	4.132-002.0					Cone for plugging into bungholes	
Double handle for exact control of the spray head	6	2.863-036.0					Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	7	5.411-061.0					Screw plug for using a spray head with one nozzle	
Pipe cleaning nozzle								
Nozzle pipe cleaning size 100	8	5.763-088.0		100	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	9	5.763-019.0		65	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	٦
	10	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	٦
	11	5.763-021.0		70	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	



		Order Number	Max. working	Nozzle size		Price	Description
Angle vario nozzle 0°-90°							
Variable angle nozzle 0-90°	1	4.113-008.0		55			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
Dirt blaster, large			·				
Dirt blaster - without changeover function	2	4.114-030.0	300 bar	70			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.



		Order Number	Nozzle size			Price	Description	
Wet blasting attachment (without r	nozzle)	)						
Wet blasting attachment with flow control (without nozzles)		4.115-000.0					Paint, rust and scale removal made easy: Karcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attach	ment					·		
Nozzle pack TR wet jet set 0070	3	2.112-027.0	70					
Boron carbide nozzle								
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-083.0	8 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	٦
■ Included in delivery. □ Av	ailabl	e accessories.	▲ Extension ho	ose.				

### KARCHER



		Order Number	Flow rate		Price	Description
Cup foam lance					 	
Packing complete for 6.394-969.0	1	2.112-018.0				
Tank 1L	2	6.414-954.0				
Inno Foam Set						·
Inno foam kit with detergent injector	3	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and
Inno foam kit	4	2.112-008.0				stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	5	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and
Easy foam set	6	2.112-011.0				disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 110 Inno/Easy set 1000 - 1300 I/h	7	2.111-020.0	1000-1300 l/h			Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.
Foam nozzle mounting kit						
Foam nozzle kit	8	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

#### KARCHER







3










		Order Number	Length		Price	Description	
Automatic, self-winding hose reels							
Add-on kit hose reel HDS M/S	1	2.110-011.0	20 m			Automatic hose reel as a complete attachment kit that's east to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose.	y []
Add-on kit holder for automatic hose reel HDS-M	2	2.643-040.0					
Add-on kit hose reel plastics	3	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	4	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Hose reel, automatic, 20 m, painted	5	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracke Suitable for 20 m high-pressure hose.	t. 🗆
	6	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stainless steel	7	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	8	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable fo use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Swivel holder	9	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	e. 🗆
ABS wall fastening stainless steel	10	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641 866). This makes maximum flexibility and convenience possible when working with the HP hose.	-

### KARCHER

# ACCESSORIES FOR HDS 12/18-4 S 1.071-917.0



		Order Number	Flow rate	Water feed temperature	Length	Length	Price	Description	
Solar cleaning - telescopic lances									
Telescopic rod complete 14m	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick- release couplings for easy extension and retraction.	
Telescopic rod complete 10m CFK	2	4.110-007.0		max. 60 °C					
Telescopic rod complete 10m	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.	
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.	
Hose solar	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	



		Order Number	Flow rate			Price	Description	
Push-on washing brush								
Push-on wash brush, M 18 x 1.5	1	4.113-001.0					Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush								
	2	4.113-002.0	800-1300 l/h					
	3	4.113-005.0	800-1300 l/h					
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension h	ose.				



		Order Number	Length	Diameter		Price	Description	
Geka coupling								_
With hose nozzle, R 3/4"	1	6.388-455.0					with hose liner	
With hose nozzle, R 1"	2	6.388-465.0						
Hose coupling	3	6.388-458.0					with female thread	
Suction filter								
Water filter	4	6.414-956.0						
Suction filter with check valve	5	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter								
Fine-mesh water filter with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4°, with adapter, 1°.	
Fine-mesh water filter, 100 µm, R 1"	7	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high- pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 I/h. Connector 1".	
Water supply hose								
Water supply hose	8	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	E
	9	4.440-270.0	7,5 m				NW 19 R1" / R1", up to 85 °C	