



HD 10/25-4 S Plus

Super class 3-phase cold water high-pressure cleaner for continuous operation in tough operating conditions.



















- 1 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.
- At last work without getting tired: the EASY!Force high-pressure
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.
- 2 Proven Kärcher quality
- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic pistons.

3 For increased safety

- Integrated electronics for unit monitoring.
- Automatic switch-off in case of undervoltage or overvoltage.

4 Outstanding mobility

- Large rubber tyres for negotiating uneven surfaces, stairs and lan-
- Proven sack trolley principle for easy, ergonomic transport.

TECHNICAL DATA AND EQUIPMENT.





HD 10/25-4 S Plus

- Save energy and time: EASY!Force high-pressure guns and
- EASY!Lock quick-release locks.

 Water-cooled three-phase motor

 Maximum impact pressure for stubborn dirt

Technical data		
Order Number		1.286-913.0
EAN code		4054278159058
Current type	Ph / V / Hz	3 / 400 / 50
Flow rate	l/h	500-1000
Operating pressure	bar / MPa	30-250 / 3-25
Max. pressure	bar / MPa	275 / 27,5
Max. water feed temperature	°C	bis zu 60
Power rating	kW	9,2
Weight	kg	62
Dimensions (L x W x H)	mm	560 × 500 × 1090

Equipment				
Trigger gun		EASY!Force Advanced	Oil sight glass	
Trigger gun with soft grip			Servo Control	-
High-pressure hose	m	10	Brass water inlet fitting	
Spray lance	mm	1050		
Power nozzle				
Dirt Blaster spray lance				
Anti-twist system (AVS)		T.		
4-pole three-phase motor with air and water cooling		•		
Pressure switch control				
Large fine mesh water filter				
Electronic motor protection system with LED display		•		

■ Included in delivery.































		Order Number	ID	Max. working pressure	Length	Price	Description
Standard with unions on both side	5			1			
High-pressure hose, 15 m DN 8, AVS trigger gun connector	1	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 20 m DN 8, AVS trigger gun connector	2	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 30 m DN 8, including rotary coupling	3	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose, 15 m DN 10, 220 bar, extension	4	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.
High-pressure hose, 20 m DN 10, 220 bar, extension	5	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar
High-pressure hose, 25 m DN 10, extension, not rotatable	6	6.110-044.0	ID 10	220 bar	25 m		
Hose assembly premium DN10 22MPa 40m	7	6.110-045.0	ID 10	220 bar	40 m		
Hose assembly premium DN12 21MPa 15m	8	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 I / h. With union on both sides. 2x M 22 x 1.5 with anti-kink
Hose assembly premium DN12 21MPa 40m	9	6.110-060.0	ID 12	210 bar	40 m		protection.
High-pressure hose, 10 m DN 8, AVS trigger gun connector	10	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
Longlife 400 with unions on both s	ides					· · · · · · · · · · · · · · · · · · ·	
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	11	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 20 m, DN 8, extension	12	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	13	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose 1.5 m, DN 8, including connectors	14	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).
	15	6.110-069.0	ID 8	400 bar	1,5 m		
High-pressure hose packaged		6.110-038.0	ID 8	400 bar	10 m		
Food industry version with unions	1		15.0	10501	140		las in a superior in the super
High-pressure hose, 10 m ID 8, suitable for food industry, extensi- on piece	17	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.
High-pressure hose, 20 m ID 8, suitable for food industry, extensi- on piece	18	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.
Longlife food industry version with	1	s on both sides					
High pressure hose food DN 8 / 10 m	19	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5

[■] Included in delivery.

Available accessories.

Extension hose.





		Order Number	ID	Max. working pressure	Length	Price	Description	
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	20	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun- ted)	

[■] Included in delivery.

Available accessories.

Extension hose.











		1		I			
		Order Number	Flow rate			Price	Description
Trigger guns							
Extended easy press trigger gun	1	4.118-005.0					Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.
Servo Control							
Servo control	2	4.118-008.0	750-1100 l/h				•
Quick connect							
Quick-fitting pipe union coupler	3	2.115-000.0					In
trapezo							
Quick-fitting pipe union plug nipp- le tra	4	2.115-001.0					

[■] Included in delivery.

Available accessories.

Extension hose.





		Order Number	Nozzle size			Price	Description
Power nozzle spray angle 25°				'			
Power nozzle spray angle 25°	1	2.113-009.0	47				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	2	2.113-034.0	50				High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$
Power nozzle spray angle 15°							
Power nozzle spray angle 15°	3	2.113-047.0	55				Fan jet nozzle with 15° spray angle suitable for stubborn dirt.
Power nozzle spray angle 40°							
Power nozzle spray angle 40°	4	2.113-054.0	50				Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.









		Order Number	Max. working pressure	Nozzle size		Price	Description
Dirt blaster, large				ı			
Dirt blaster - without changeover function	1	4.114-027.0	300 bar	50			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.
Triple nozzles							
Triple nozzle 050	2	4.117-037.0	300 bar	50			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.
Angle vario nozzle 0°-90°							
Spezial nozzle 0005	3	4.113-007.0		50			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.

[■] Included in delivery.

Available accessories.

Extension hose.





							Т
			May wayling				
		Order Number	Max. working pressure	Length	Price	Description	
Rotating spray lances							_
1050 mm lance, rotatable, ergono- mic	1	4.112-000.0	300 bar	1050 mm		1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm			
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm			
Rotatable lance, 600 mm, ergonomic	4	4.112-007.0	300 bar	600 mm		600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	. [
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm		850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	. [
Lance 1550 mm, rotatable, ergo- nomic	6	4.112-018.0	300 bar	1550 mm		1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	Г
Lance 2050 mm, rotatable, ergo- nomic	7	4.112-021.0	300 bar	2050 mm		2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° under pressure.	
Double lance							
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm		960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance							
WC and gutter lance	9	4.112-029.0				Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance							
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm		1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance		ı			,		
Telescopic jet pipe		4.112-037.0	225 bar	5400 mm			
Restraint belt for telescopic jet pipe	12	6.373-987.0				Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner							
Gutter cleaning lance	13	2.112-015.0				The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance							
Underbody lance	14	4.112-032.0		700 mm		Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle							
	15	4.321-380.0					l





	1						
		Order Number			Price	Description	
Crane lifting kit							
Crane loading kit for HD super class	1	2.640-438.0				Effortless loading by crane.	
Y distributor							
		4.111-024.0					

[■] Included in delivery.

Available accessories.

Extension hose.























		Order Number	Flow rate	Nozzle size	Diame- ter	Price	Description	
Hard Surface Cleaner FRV 30								
Add-on kit rubber lip	1	2.642-910.0					For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	2	4.440-939.0					5m extension hose for FRV 30. Connection sleeve included.	
Add-on kit hose attachment	3	2.642-528.0						
Add-on kit dirt trap	4	2.642-532.0						
FRV 30	5	2.111-010.0						
Hard surface cleaner FR 30 ME								
FR 30 ME surface cleaner	6	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Hard Surface Cleaner FR 50								
FR 50 surface cleaner	7	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 850 - 1100 l/h	8	2.640-442.0	850-1100 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).	
Machine-specific nozzle kits for FF	RV							
Nozzle kit 050 for FRV 30	9	2.642-433.0		50				
Hard surface cleaner FRV 30 Me								
Suction hose FRV 30 me	10	4.441-040.0						
FRV 30 ME	11	2.111-012.0						
Surface Cleaner FR 50 Me								
	12	2.111-024.0						

[■] Included in delivery.

Available accessories.

Extension hose.































		Order Number		Price	Description
Nozzle union					
Protection part TR only for replacement	1	4.112-011.0			
Coupling parts				 ,	
	2	6.987-705.0			
Rotary coupling					
Rotary coupling	3	4.111-021.0			Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.
Coupling					
Coupler -2xM22x1,5	4	4.111-037.0			Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \ x \ 1.5 \ m.$
Connector					
Nozzle connector/screw connector	5	4.111-022.0			Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M 22 \times 1.5$ and $1 \times M 18 \times 1.5$.
	6	4.111-038.0			
Adapter EASY!Lock			,	 	
Adapter 1 M22AG-TR22AG	7	4.111-029.0			
Adapter 2 M22IG-TR22AG	8	4.111-030.0			
Adapter 3 M22IG-TR22AG	9	4.111-031.0			
Adapter M22 - Swivel	10	4.111-032.0			M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.
Adapter 5 TR22IG-M22AG	11	4.111-033.0			
Adapter 6 TR22IG-M22AG	12	4.111-034.0			
Adapter 7 M18IG-TR20AG	13	4.111-035.0			
Adapter 8 TR20IG-M18AG	14	4.111-036.0			
HP detergent injector					
,	15	6.645-761.0			
	16	6.500-000.0			
Detergent injector for high and low pressure (without nozzles)	17	4.637-032.0			Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.
Detergent injector for high pressu- re	18	4.637-033.0			Cleaning agent dosage at high pressure 3 - 5 %
Machine-specific nozzle kit with or	der no	. 3.637-170			
Machine-specific nozzle kit with order no. 3.637-170.0 750-1000 l/h	19	4.769-047.0			For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union
Nozzle insert with order no. 3.637-	001		,		
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	20	4.769-003.0			Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.
Low pressure for units rated up to 1100 I/h	21	4.769-001.0			For low pressure with machines up to 1.100 l/h



























						1		
		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Barrel and tank cleaning		'	'					
	1	2.112-020.0						
HKF 50 spray head, brass								
HKF 50 spray head , brass	2	3.631-039.0					Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally	
	_	3.631-058.0						
Nozzle kit for HKF 50 spray head (3		1	9.0)	1		1	la contra de la	
Nozzle 045 for dual nozzle opera- tion HKF 50	4	6.415-446.0		45			Nozzle for dual-nozzle operation	
Nozzle 090 for single nozzle operation HKF 50	5	6.415-447.0		90			Nozzle for single-nozzle operation	
Cone for plugging into bungholes	6	4.132-002.0					Cone for plugging into bungholes	
Double handle for exact control of the spray head	7	2.863-036.0					Double handle. Precise control of the spray head	
Screw plug for using a spray head with one nozzle	8	5.411-061.0					Screw plug for using a spray head with one nozzle	
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning DN6 max.2	9	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	10	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	11	6.110-047.0	250 bar					
Pipe cleaning nozzle								
Drain cleaning dirt blaster D 25/060	12	6.415-945.0		60	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the	
Drain cleaning dirt blaster D 30/060	13	6.415-947.0		60	30 mm		necessary forward movement, as well as convenient hand- ling.	
Drain cleaning dirt blaster D 35/060	14	6.415-949.0		60	35 mm			
Nozzle pipe cleaning size 80	15	5.763-087.0		80	25 mm		Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	16	5.763-019.0		65	16 mm		16 mm pipe cleaning nozzle with internal thread. Various je	et 🗆
	17	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	18	5.763-021.0		70	30 mm		30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	19	6.415-440.0		65	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	

[■] Included in delivery.

Available accessories.

Extension hose.







		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without i	nozzle)				
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kārcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack TR wet jet set 0050	3	2.112-023.0	50			
Boron carbide nozzle						
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-083.0	8 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

[■] Included in delivery.

Available accessories.

Extension hose.













		Order Number	Flow rate			Price	Description
Cup foam lance		Order Nomber	1 low rate			Titee	pescription .
Packing complete for 6.394-968.0	1 1	2.112-017.0					
Tank 1L	_	6.414-954.0					
Inno Foam Set			·	'			
Inno foam kit with detergent injector	3	2.112-000.0					High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set							
Easy Foam Set with RM injector	4	2.112-010.0					HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Se							
Nozzle kit 090 Inno/Easy kit 700 - 1000 I/h	5	2.111-019.0	700-1000 l/h				Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.
Foam nozzle mounting kit							
Foam nozzle kit	6	2.112-013.0					Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[■] Included in delivery.

Available accessories.

Extension hose.



















				1		1	
		Order Number	Lameth			Price	Description
		Order Normber	Lengui			Price	Description
Hose reel add-on kit							
Hose reel kit for HD super class	1	2.110-008.0	20 m				ABS hose reel for mounting on the machine. For safe and
							tidy stowage of high-pressure hoses (with connecting hose
							to machine's HP outlet) Can be rotated under pressure, with
							M 22 x 1.5 connection.
Automatic, self-winding hose reels				ı		1	1
Add-on kit hose reel plastics	2	6.392-074.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con-
							sole is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	3	6.392-083.0	20 m				Automatic hose reel for 20 m high-pressure hose. The con-
Add-off Kit flose reel	ر	0.532-005.0	20111				sole consists of stainless steel, the drum is made from plas-
							tic.
Hose reel, automatic, 20 m, pain-	4	6.392-106.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket.
ted							Suitable for 20 m high-pressure hose.
	5	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stain-	6	6.392-076.0	20 m				Automatic stainless steel hose reel. With swivel holder.
less steel							Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	7	6.392-122.0	20 m				High-grade, automatic steel hose reel. Especially suitable for
							use in the food industry. The material and finish provide for \square
							a corrossion-resistant, watertight capsuled sprong drive.
Swivel holder	0	2.620.024.0					Connection for HP hoses with nipple.
Swiver holder	8	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose.
							Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel	9	2.641-867.0					Swivelling wall bracket made of high-grade steel (for 2.641-
riss train rasterning starriess steer		2.5 11 507.0					866). This makes maximum flexibility and convenience
							possible when working with the HP hose.

[■] Included in delivery.

Available accessories.

Extension hose.











				Water feed		ļ		
		Order Number	Flow rate	temperature	Length	Length	Price	Description
Solar cleaning - telescopic lances								
Telescopic rod complete 14m	1	4.110-002.0		max. 60 °C				Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction.
Telescopic rod complete 10m CFK	2	4.110-007.0		max. 60 °C				
Telescopic rod complete 10m	3	4.110-003.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.
iSolar TL 7 H (without hose)	4	4.110-004.0		max. 60 °C				Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.
Hose solar	5	6.392-978.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
	6	6.392-977.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.
	7	6.392-976.0		max. 155 °C				High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

[■] Included in delivery.

Available accessories.

Extension hose.









		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on wash brush, M 18 x 1.5	1	4.113-001.0				Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush							
	2	4.113-002.0	800-1300 l/h				
	3	4.113-005.0	800-1300 l/h				

[■] Included in delivery.

Available accessories.

Extension hose.

















		Order Number	Length	Diameter		Price	Description	
Geka coupling								
With hose nozzle, R 1"	1	6.388-465.0						
Hose coupling	2	6.388-458.0					with female thread	
Suction filter								
Water filter	3	6.414-956.0						
Suction filter with check valve	4	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter								
Fine-mesh water filter with adapter	5	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Fine-mesh water filter, 100 μm, R 1"	6	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1°.	-
Water supply hose								
Water supply hose	7	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	8	4.440-270.0	7,5 m				NW 19 R1" / R1", up to 85 °C	
Backflow check valve								
Backflow preventer	9	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	l

[■] Included in delivery.

Available accessories.

Extension hose.