



HD 10/25-4 SX Plus

Super class 3-phase cold water high-pressure cleaner for continuous operation in tough operating conditions. With built-in high-pressure hose reel.



1 Proven Kärcher quality

- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic pistons.

3 For increased safety

- Integrated electronics for unit monitoring.
- Automatic switch-off in case of undervoltage or overvoltage.

2 Hose storage

- Supported on both sides; for 20 m high-pressure hose.
- Hose guide passes under the unit; high stability.

4 Outstanding mobility

- Large rubber tyres for negotiating uneven surfaces, stairs and landings.
- Proven sack trolley principle for easy, ergonomic transport.



HD 10/25-4 SX Plus

- Water-cooled three-phase motor
- Easy Press trigger gun with soft grip and servo control
- Maximum impact pressure for stubborn dirt

Technical data

| | | |
|-----------------------------|---------------|------------------|
| Order No. | 1.286-500.0 | |
| EAN code | 4039784732780 | |
| Current type | Ph / V / Hz | 3 / 400 / 50 |
| Flow rate | l/h | 500-1000 |
| Operating pressure | bar / MPa | 30-250 / 3-25 |
| Max. pressure | bar / MPa | 275 / 27,5 |
| Max. water feed temperature | °C | 60 |
| Power rating | kW | 9,2 |
| Weight | kg | 64 |
| Dimensions (L x W x H) | mm | 560 x 500 x 1090 |
| Detergent tank | l | 6 |

Equipment

| | | | |
|---|------------------------|---|---|
| Trigger gun | Easy-press trigger gun | Electronic motor protection system with LED display | ■ |
| Trigger gun with soft grip | ■ | Oil sight glass | ■ |
| High-pressure hose | m | Servo Control | ■ |
| Spray lance | mm | Brass water inlet fitting | ■ |
| Triple nozzle (0°/25°/40°) | Touchless | | |
| Dirt Blaster spray lance | ■ | | |
| Integral high-pressure hose reel | ■ | | |
| Anti-twist system (AVS) | ■ | | |
| 4-pole three-phase motor with air and water cooling | ■ | | |
| Pressure switch control | ■ | | |
| Large fine mesh water filter | ■ | | |

■ Included in delivery.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER


| | | Order No. | ID | Max. working pressure | Length | | Price | Description | |
|---|----|-------------|-------|-----------------------|--------|--|-------|--|---|
| Standard with unions on both sides | | | | | | | | | |
| High-pressure hose packaged | 1 | 6.391-342.0 | ID 8 | 315 bar | 10 m | | | | ▲ |
| High-pressure hose, 15 m DN 8, 315 bar, including rotary coupling | 2 | 6.390-010.0 | ID 8 | 315 bar | 15 m | | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose, 20 m DN 8, 315 bar, extension | 3 | 6.390-031.0 | ID 8 | 315 bar | 20 m | | | With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar | ▲ |
| High-pressure hose, 30 m DN 8, including rotary coupling | 4 | 6.390-293.0 | ID 8 | 315 bar | 30 m | | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose, 15 m DN 10, 220 bar, extension | 5 | 6.390-023.0 | ID 10 | 220 bar | 15 m | | | 15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar. | ▲ |
| Longlife 400 with unions on both sides | | | | | | | | | |
| High-pressure hose Longlife 400, 10 m, DN 8, including rotary coupling | 6 | 6.388-083.0 | ID 8 | 400 bar | 10 m | | | 10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection. | ▲ |
| High-pressure hose packaged | 7 | 6.391-354.0 | ID 8 | 400 bar | 10 m | | | | ▲ |
| High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling | 8 | 6.389-709.0 | ID 8 | 400 bar | 15 m | | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose Longlife 400, 20 m, DN 8, extension | 9 | 6.390-027.0 | ID 8 | 400 bar | 20 m | | | with rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling | 10 | 6.390-294.0 | ID 8 | 400 bar | 30 m | | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose 1.5 m, DN 8, including connectors | 11 | 6.390-178.0 | ID 8 | 400 bar | 1.5 m | | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). | □ |
| Food industry version with unions on both sides | | | | | | | | | |
| High-pressure hose, 10 m ID 8, suitable for food industry, extension piece | 12 | 6.389-479.0 | ID 8 | 250 bar | 10 m | | | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve. | ▲ |
| High-pressure hose, 20 m ID 8, suitable for food industry, extension piece | 13 | 6.389-581.0 | ID 8 | 250 bar | 20 m | | | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar. | ▲ |
| Longlife food industry version with unions on both sides | | | | | | | | | |
| High pressure hose food DN 8 / 10 m | 14 | 6.391-864.0 | ID 8 | 400 bar | 10 m | | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose food industry 400 bar, 20 m, DN 8, including rotary coupling | 15 | 6.391-887.0 | ID 8 | 400 bar | 20 m | | | | ▲ |
| Standard | | | | | | | | | |
| High-pressure hose, 20 m DN 8, AVS trigger gun connector | 16 | 6.390-171.0 | ID 8 | 315 bar | 20 m | | | 20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. | ■ |
| High-pressure hose, 15 m DN 8, AVS trigger gun connector | 17 | 6.390-185.0 | ID 8 | 315 bar | 15 m | | | 15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar. | □ |
| Longlife 400 | | | | | | | | | |
| High-pressure hose packaged | 18 | 6.391-351.0 | ID 8 | 400 bar | 10 m | | | | □ |
| High-pressure hose Longlife 400, 20 m DN 8, AVS trigger gun connector | 19 | 6.390-208.0 | ID 8 | 400 bar | 20 m | | | 20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced. | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | ID | Max. working pressure | Length | Price | Description | |
|--|----|-------------|------|-----------------------|--------|-------|---|--------------------------|
| Food industry version | | | | | | | | |
| High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food industry, grey | 20 | 6.390-704.0 | ID 8 | 250 bar | 10 m | | Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar | <input type="checkbox"/> |
| High-pressure hose, 20 m ID 8, AVS trigger gun connector, suitable for food industry, grey | 21 | 6.390-705.0 | ID 8 | 250 bar | 20 m | | 20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar. | <input type="checkbox"/> |
| Longlife food industry version | | | | | | | | |
| High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection | 22 | 6.391-885.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted) | <input type="checkbox"/> |
| High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection | 23 | 6.391-886.0 | ID 8 | 400 bar | 20 m | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Flow rate | | | | Price | Description | |
|---|---|-------------|--------------|--|--|--|-------|--|---|
| Easy Press high-pressure gun with holding power reduction (Kärcher patent) | | | | | | | | | |
| Easy press high-pressure trigger gun with softgrip | 1 | 4.775-466.0 | | | | | | Easy press high-pressure trigger gun with integrated adapter for connecting to high-pressure hoses M 22 x 1.5. | ■ |
| Servo Control | | | | | | | | | |
| Servo control | 2 | 4.775-470.0 | 750-1100 l/h | | | | | | ■ |
| Trigger guns | | | | | | | | | |
| High end high-pressure trigger gun | 3 | 4.775-823.0 | | | | | | | □ |
| Quick connect | | | | | | | | | |
| Quick coupling | 4 | 6.401-458.0 | | | | | | For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1.5 female. | □ |
| Plug nipple | 5 | 6.401-459.0 | | | | | | Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1.5 male. | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Max. working pressure | Nozzle size | | | Price | Description | |
|--|---|-------------|-----------------------|-------------|--|--|-------|---|---|
| Triple nozzle, touchless changeover | | | | | | | | | |
| Triple nozzle, touchless changeover | 1 | 4.767-065.0 | | 50 | | | | Triple nozzle with high-pressure pencil jet (25°) and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle. | ■ |
| Dirt blaster, large | | | | | | | | | |
| Dirt blaster - without changeover function | 2 | 4.763-253.0 | 300 bar | 50 | | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | ■ |
| Triple nozzles | | | | | | | | | |
| Triple nozzle 050 | 3 | 4.767-154.0 | 300 bar | 50 | | | | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5. | □ |
| Angle vario nozzle 0°-90° | | | | | | | | | |
| Spezial nozzle 0005 | 4 | 4.763-039.0 | | 50 | | | | Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces. | □ |
| Inaktiv | | | | | | | | | |
| Dirt blaster - with changeover to low pressure cleaning agent intake | 5 | 4.763-949.0 | 300 bar | 55 | | | | | □ |
| Inaktiv | | | | | | | | | |
| Dirt blaster with changeover to fan jet | 6 | 4.763-957.0 | 300 bar | 50 | | | | | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Max. working pressure | Length | | | Price | Description | |
|--|----|-------------|-----------------------|---------|--|--|-------|---|---|
| Rotating spray lances | | | | | | | | | |
| 1050 mm lance, rotatable, ergonomic | 1 | 4.760-660.0 | 300 bar | 1050 mm | | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ■ |
| Rotatable lance, 600 mm, ergonomic | 2 | 4.760-664.0 | 300 bar | 600 mm | | | | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 850 mm, rotatable, ergonomic | 3 | 4.760-663.0 | 300 bar | 840 mm | | | | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 1550 mm, rotatable, ergonomic | 4 | 4.760-661.0 | 300 bar | 1550 mm | | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 2050 mm, rotatable, ergonomic | 5 | 4.760-662.0 | 300 bar | 2050 mm | | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Spray lances | | | | | | | | | |
| Anti-vibration lance | 6 | 6.415-951.0 | 250 bar | 950 mm | | | | The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster. | □ |
| Spray lance | | | | | | | | | |
| Lance 250 mm, non-rotatable | 7 | 4.760-667.0 | | 250 mm | | | | 250 mm stainless steel lance. With manual coupling. Non-rotatable. | □ |
| Double lance | | | | | | | | | |
| Double lance 960 mm | 8 | 6.394-665.0 | 310 bar | 960 mm | | | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | □ |
| Variable pressure spray lance | | | | | | | | | |
| Variable pressure spray lance | 9 | 4.760-362.0 | | 670 mm | | | | 670 mm variable pressure lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application. | □ |
| Variable pressure lance | 10 | 4.760-230.0 | | 1040 mm | | | | 1040 mm pressure adjustable lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application. | □ |
| Adapter for variable pressure spray lance | | | | | | | | | |
| Adapter for variable pressure lance | 11 | 4.762-075.0 | | | | | | For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5 | □ |
| Angular spray lance | | | | | | | | | |
| WC and gutter lance | 12 | 4.760-073.0 | | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | □ |
| Flexible spray lance | | | | | | | | | |
| Flexible lance 1050 mm | 13 | 6.394-654.0 | 210 bar | 1050 mm | | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | □ |
| Telescopic spray lance | | | | | | | | | |
| Telescopic jet pipe | 14 | 6.394-690.0 | 225 bar | | | | | | □ |
| Restraint belt for telescopic jet pipe | 15 | 6.373-987.0 | | | | | | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Max. working pressure | Length | | | Price | Description | |
|----------------------------------|----|-------------|-----------------------|--------|--|--|-------|---|--------------------------|
| Gutter cleaner | | | | | | | | | |
| Gutter cleaning lance | 16 | 2.642-305.0 | | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | <input type="checkbox"/> |
| Undercarriage spray lance | | | | | | | | | |
| Underbody lance | 17 | 4.760-245.0 | | 700 mm | | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0




| | | Order No. | | | | | Price | Description | |
|----------------------|---|-------------|--|--|--|--|-------|---|--------------------------|
| Miscellaneous | | | | | | | | | |
| Backflow check valve | 1 | 6.412-578.0 | | | | | | To prevent cleaning agent from entering the drinking water system at low supply pressure. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0



| | | Order No. | | | | | | Price | Description | |
|--------------------------------------|---|-------------|--|--|--|--|--|-------|--|--------------------------|
| Crane lifting kit | | | | | | | | | | |
| Crane loading kit for HD super class | 1 | 2.640-438.0 | | | | | | | Effortless loading by crane. | <input type="checkbox"/> |
| Grey wheel kit | | | | | | | | | | |
| Mounting kit for non-marking wheels | 2 | 2.641-493.0 | | | | | | | Grey wheels that do not leave streaks for cleaning in the sanitary or food industries or swimming pools. | <input type="checkbox"/> |
| Y distributor | | | | | | | | | | |
| Y distributor | 3 | 4.405-048.0 | | | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Flow rate | Nozzle size | Diameter | Price | Description | |
|--|----|-------------|--------------|-------------|----------|-------|--|--------------------------|
| Hard surface cleaner FRV 30 | | | | | | | | |
| FRV 30 | 1 | 2.642-999.0 | | | | | | <input type="checkbox"/> |
| Add-on kit rubber lip | 2 | 2.642-910.0 | | | | | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | <input type="checkbox"/> |
| Extension hose 5 m | 3 | 4.440-939.0 | | | | | 5m extension hose for FRV 30. Connection sleeve included. | <input type="checkbox"/> |
| Add-on kit hose attachment | 4 | 2.642-528.0 | | | | | | <input type="checkbox"/> |
| Add-on kit dirt trap | 5 | 2.642-532.0 | | | | | | <input type="checkbox"/> |
| Hard surface cleaner FR 30 ME | | | | | | | | |
| FR 30 ME surface cleaner | 6 | 2.640-355.0 | | | 300 mm | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | <input type="checkbox"/> |
| Hard surface cleaner FR 50 | | | | | | | | |
| FR 50 surface cleaner | 7 | 2.640-679.0 | | | 500 mm | | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. | <input type="checkbox"/> |
| Machine-specific nozzle kit for FR | | | | | | | | |
| Nozzle kit for surface cleaners (type-specific) 850 - 1100 l/h | 8 | 2.640-442.0 | 850-1100 l/h | | | | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h). | <input type="checkbox"/> |
| Machine-specific nozzle kits for FRV | | | | | | | | |
| Nozzle kit 050 for FRV 30 | 9 | 2.642-433.0 | | 50 | | | | <input type="checkbox"/> |
| Hard surface cleaner FRV 30 Me | | | | | | | | |
| FRV 30 ME | 10 | 2.642-911.0 | | | | | | <input type="checkbox"/> |
| Suction hose FRV 30 me | 11 | 4.441-040.0 | | | | | | <input type="checkbox"/> |
| Flächenreiniger FR 50 Me | | | | | | | | |
| | 12 | 2.643-598.0 | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | | | | | | Price | Description | |
|---|----|-------------|--|--|--|--|--|-------|--|--------------------------|
| Nozzle union | | | | | | | | | | |
| Nozzle connector | 1 | 5.401-210.0 | | | | | | | For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG). | <input type="checkbox"/> |
| Spacer (including nozzle union) | | | | | | | | | | |
| Spacer (incl. nozzle union) | 2 | 5.394-294.0 | | | | | | | Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance. | <input type="checkbox"/> |
| Coupling parts | | | | | | | | | | |
| | 3 | 6.987-705.0 | | | | | | | | <input type="checkbox"/> |
| Rotary coupling | | | | | | | | | | |
| Rotary coupling | 4 | 4.401-091.0 | | | | | | | Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection. | <input type="checkbox"/> |
| Coupling | | | | | | | | | | |
| Coupler -2xM22x1,5 | 5 | 4.403-002.0 | | | | | | | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m. | <input type="checkbox"/> |
| Connector | | | | | | | | | | |
| Nozzle connector/screw connector | 6 | 4.402-022.0 | | | | | | | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. | <input type="checkbox"/> |
| HP detergent injector | | | | | | | | | | |
| Detergent injector for high and low pressure (without nozzles) | 7 | 3.637-001.0 | | | | | | | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. | <input type="checkbox"/> |
| Machine-specific nozzle kit with order no. 3.637-170 | | | | | | | | | | |
| Machine-specific nozzle kit with order no. 3.637-170.0 1000-1200 l/h l/h | 8 | 4.769-048.0 | | | | | | | For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HP power nozzle + union | <input type="checkbox"/> |
| Nozzle insert with order no. 3.637-001 | | | | | | | | | | |
| Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h. | 9 | 4.769-003.0 | | | | | | | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h. | <input type="checkbox"/> |
| Low pressure for units rated up to 1100 l/h | 10 | 4.769-001.0 | | | | | | | For low pressure with machines up to 1.100 l/h | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Max. working pressure | Nozzle size | Diameter | Price | Description | |
|---|----|-------------|-----------------------|-------------|----------|-------|---|--------------------------|
| HKF 50 spray head, brass | | | | | | | | |
| HKF 50 spray head, brass | 1 | 3.631-039.0 | | | | | Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally | <input type="checkbox"/> |
| Nozzle kit for HKF 50 spray head (3.631-009.0 / 3.631-039.0) | | | | | | | | |
| Nozzle 045 for dual nozzle operation HKF 50 | 2 | 6.415-446.0 | | 45 | | | Nozzle for dual-nozzle operation | <input type="checkbox"/> |
| Nozzle 090 for single nozzle operation HKF 50 | 3 | 6.415-447.0 | | 90 | | | Nozzle for single-nozzle operation | <input type="checkbox"/> |
| Cone for plugging into bungholes | 4 | 4.132-002.0 | | | | | Cone for plugging into bungholes | <input type="checkbox"/> |
| Double handle for exact control of the spray head | 5 | 2.863-036.0 | | | | | Double handle. Precise control of the spray head | <input type="checkbox"/> |
| Screw plug for using a spray head with one nozzle | 6 | 5.411-061.0 | | | | | Screw plug for using a spray head with one nozzle | <input type="checkbox"/> |
| Pipe cleaning hose, ID 6 | | | | | | | | |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 7 | 6.390-030.0 | 250 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). | <input type="checkbox"/> |
| Pipe cleaning nozzle | | | | | | | | |
| Drain cleaning dirt blaster D 25/060 | 8 | 6.415-945.0 | | 60 | 25 mm | | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | <input type="checkbox"/> |
| Drain cleaning dirt blaster D 30/060 | 9 | 6.415-947.0 | | 60 | 30 mm | | | <input type="checkbox"/> |
| Drain cleaning dirt blaster D 35/060 | 10 | 6.415-949.0 | | 60 | 35 mm | | | <input type="checkbox"/> |
| Nozzle pipe cleaning size 100 | 11 | 5.763-088.0 | | 100 | 24 mm | | Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle. | <input type="checkbox"/> |
| Nozzle pipe cleaning size 120 | 12 | 5.763-089.0 | | 120 | 16 mm | | Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle. | <input type="checkbox"/> |
| Pipe cleaning nozzle | 13 | 5.763-019.0 | | 65 | 16 mm | | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| | 14 | 5.763-020.0 | | 65 | 16 mm | | | <input type="checkbox"/> |
| | 15 | 5.763-021.0 | | 70 | 30 mm | | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| Rotating pipe cleaning nozzle | 16 | 6.415-440.0 | | 65 | 16 mm | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0



| | | Order No. | Nozzle size | | | | Price | Description | |
|-------------------------------------|---|-------------|-------------|--|--|--|-------|--|--------------------------|
| HP nozzle spray angle 0° | | | | | | | | | |
| High-pressure nozzle spray angle 0° | 1 | 2.884-535.0 | 50 | | | | | High-pressure nozzle with powerful jet for extremely stubborn dirt. | <input type="checkbox"/> |
| Power nozzle spray angle 15° | | | | | | | | | |
| Power nozzle spray angle 15° | 2 | 2.883-390.0 | 55 | | | | | Fan jet nozzle with 15° spray angle suitable for stubborn dirt. | <input type="checkbox"/> |
| Power nozzle spray angle 25° | | | | | | | | | |
| Power nozzle spray angle 25° | 3 | 2.883-399.0 | 50 | | | | | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. | <input type="checkbox"/> |
| | 4 | 2.884-521.0 | 250 | | | | | | <input type="checkbox"/> |
| Power nozzle spray angle 40° | | | | | | | | | |
| Power nozzle spray angle 40° | 5 | 2.884-524.0 | 50 | | | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Nozzle size | | | | Price | Description | |
|---|---|-------------|-------------|--|--|--|-------|--|--------------------------|
| Wet blasting attachment (without nozzle) | | | | | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.762-010.0 | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. | <input type="checkbox"/> |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.762-022.0 | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. | <input type="checkbox"/> |
| Nozzle pack for wet blasting attachment | | | | | | | | | |
| Nozzle kit for wet blasting attachment 050 | 3 | 2.637-902.0 | 50 | | | | | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022. | <input type="checkbox"/> |
| Boron carbide nozzle | | | | | | | | | |
| Boron carbide nozzle, for machines as of 1000 l/h | 4 | 6.415-084.0 | 6 mm | | | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Flow rate | | | | Price | Description | |
|--|---|-------------|-----------|--|--|--|-------|--|--------------------------|
| Cup foam lance | | | | | | | | | |
| Tank 1L | 1 | 6.414-954.0 | | | | | | | <input type="checkbox"/> |
| Cup foam lance | 2 | 6.394-668.0 | 1200 l/h | | | | | Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design. | <input type="checkbox"/> |
| Foam lance nozzle Ø1,25 | 3 | 6.394-968.0 | | | | | | | <input type="checkbox"/> |
| Inno Foam Set | | | | | | | | | |
| Inno foam kit | 4 | 2.640-692.0 | | | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | <input type="checkbox"/> |
| Easy Foam Set | | | | | | | | | |
| Easy foam set | 5 | 2.640-693.0 | | | | | | HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | <input type="checkbox"/> |
| Nozzle kits for Inno/Easy Foam Set | | | | | | | | | |
| Nozzle kit 090 z. Inno/Easy set for HD 10/25 | 6 | 2.640-694.0 | 1000 l/h | | | | | Optimal adaptation to different machine outputs for economic use. | <input type="checkbox"/> |
| Foam nozzle mounting kit | | | | | | | | | |
| Foam nozzle kit | 7 | 2.637-926.0 | | | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER




| | | Order No. | Length | | | | | Price | Description | |
|---|---|-------------|--------|--|--|--|--|-------|--|--------------------------|
| Hose reel add-on kit | | | | | | | | | | |
| Hose reel kit for HD super class | 1 | 2.640-439.0 | 20 m | | | | | | ABS hose reel for mounting on the machine. For safe and tidy stowage of high-pressure hoses (with connecting hose to machine's HP outlet) Can be rotated under pressure, with M 22 x 1.5 connection. | <input type="checkbox"/> |
| Automatic, self-winding hose reels | | | | | | | | | | |
| Swivel holder | 2 | 2.639-931.0 | | | | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. | <input type="checkbox"/> |
| ABS wall fastening stainless steel | 3 | 2.641-867.0 | | | | | | | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. | <input type="checkbox"/> |
| Add-on kit hose reel plastics | 4 | 6.392-975.0 | 20 m | | | | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | <input type="checkbox"/> |
| Add-on kit hose reel | 5 | 6.392-965.0 | 20 m | | | | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, painted | 6 | 2.639-919.0 | 20 m | | | | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, stainless steel | 7 | 6.391-421.0 | 20 m | | | | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| ABS hose reel stainless steel | 8 | 2.641-866.0 | 20 m | | | | | | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Flow rate | Water feed temperature | Length | Length | Price | Description | |
|---|---|-------------|-----------|------------------------|--------|--------|-------|---|--------------------------|
| Solar cleaning - telescopic lances | | | | | | | | | |
| iSolar TL 7 H (without hose) | 1 | 4.107-054.0 | | 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction. | <input type="checkbox"/> |
| Telescopic rod complete 10m | 2 | 4.107-053.0 | | 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction. | <input type="checkbox"/> |
| Telescopic rod complete 10m CFK | 3 | 4.107-055.0 | | 60 °C | | | | | <input type="checkbox"/> |
| Telescopic rod complete 14m | 4 | 4.107-052.0 | | 60 °C | | | | Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction. | <input type="checkbox"/> |
| Hose solar | 5 | 6.392-978.0 | | 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | <input type="checkbox"/> |
| | 6 | 6.392-977.0 | | 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | <input type="checkbox"/> |
| | 7 | 6.392-976.0 | | 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0



| | | Order No. | Flow rate | | | | Price | Description | |
|--------------------------------|---|-------------|--------------|--|--|--|-------|---|--------------------------|
| Push-on washing brush | | | | | | | | | |
| Push-on wash brush, M 18 x 1.5 | 1 | 4.762-016.0 | | | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6. | <input type="checkbox"/> |
| Rotating washing brush | | | | | | | | | |
| | 2 | 4.762-559.0 | 900-1300 l/h | | | | | | <input type="checkbox"/> |
| | 3 | 4.762-562.0 | 900-1300 l/h | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 10/25-4 SX PLUS

1.286-500.0

KÄRCHER



| | | Order No. | Length | Diameter | | Price | Description | |
|--------------------------------------|---|-------------|--------|----------|--|-------|--|--------------------------|
| Geka coupling | | | | | | | | |
| With hose nozzle, R 3/4" | 1 | 6.388-455.0 | | | | | with hose liner | <input type="checkbox"/> |
| Hose coupling | 2 | 6.388-458.0 | | | | | with female thread | <input type="checkbox"/> |
| Suction filter | | | | | | | | |
| Water filter | 3 | 6.414-956.0 | | | | | | <input type="checkbox"/> |
| Suction filter with check valve | 4 | 4.730-012.0 | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | <input type="checkbox"/> |
| Fine-mesh water filter | | | | | | | | |
| Fine-mesh water filter with adapter | 5 | 4.730-102.0 | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1" | <input type="checkbox"/> |
| Fine-mesh water filter, 100 µm, R 1" | 6 | 2.638-270.0 | | | | | Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1". | <input type="checkbox"/> |
| Water supply hose | | | | | | | | |
| Water supply hose | 7 | 4.440-207.0 | 7,5 m | | | | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | <input type="checkbox"/> |
| | 8 | 4.440-270.0 | 7,5 m | | | | NW 19 R1" / R1", up to 85 °C | <input type="checkbox"/> |
| Backflow check valve | | | | | | | | |
| Backflow preventer | 9 | 2.641-374.0 | | | | | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.