



HD 7/10 CXF

Cold-water high-pressure cleaner for daily commercial use in the food industry.



1 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last – work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.

2 Hygiene requirements

- Water inlet temperature up to 80°C.
- Abrasion-resistant grey wheels.

3 Booster pump

- Cleaning agent intake system for removing stubborn dirt.
- Booster pump with pressure tank

4 Servo Control

- Pressure washer



HD 7/10 CXF

- For sensitive sanitary, hygiene and food areas
- Grey, non-marking wheels

| Technical data | | |
|-----------------------------|-------------|-----------------|
| Order Number | | 1.151-906.0 |
| EAN code | | 4054278164823 |
| Current type | Ph / V / Hz | 3 / 400 / 50 |
| Flow rate | l/h | 250-700 |
| Operating pressure | bar / MPa | 10-100 / 1-10 |
| Max. pressure | bar / MPa | 120 / 12 |
| Max. water feed temperature | °C | 80 |
| Power rating | kW | 4,5 |
| Weight | kg | 31,3 |
| Dimensions (L x W x H) | mm | 360 × 375 × 925 |

| Equipment | | |
|---|----|----------------------------|
| High-pressure hose | m | 15 / Food industry version |
| Spray lance | mm | 840 |
| Triple nozzle (0°/25°/40°) | | Manual |
| High-pressure hose drum | | ■ |
| Anti-twist system (AVS) | | - |
| Pressure switch control | | ■ |
| Infinitely variable pressure and water flow control on the unit | | ■ |
| Servo Control | | ■ |
| ■ Included in delivery. | | |

ACCESSORIES FOR HD 7/10 CXF 1.151-906.0

KÄRCHER



| | | Order Number | ID | Max. working pressure | Length | Price | Description | |
|--|---|--------------|------|-----------------------|--------|-------|--|---|
| Food industry version with unions on both sides | | | | | | | | |
| High-pressure hose, 10 m ID 8, suitable for food industry, extension piece | 1 | 6.110-051.0 | ID 8 | 250 bar | 10 m | | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve. | ▲ |
| High-pressure hose, 20 m ID 8, suitable for food industry, extension piece | 2 | 6.110-052.0 | ID 8 | 250 bar | 20 m | | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar. | ▲ |
| Longlife food industry version with unions on both sides | | | | | | | | |
| High pressure hose food DN 8 / 10 m | 3 | 6.110-053.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5 | ▲ |
| Food industry version | | | | | | | | |
| Hose assembly trapezoidal thread hygiene | 4 | 6.110-074.0 | ID 6 | 250 bar | 15 m | | | ■ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0




| | | Order Number | Flow rate | | | | | Price | Description | |
|--|---|--------------|--------------|--|--|--|--|-------|---|---|
| Trigger guns | | | | | | | | | | |
| Hand trigger gun only for replacement | 1 | 4.118-015.0 | | | | | | | | ■ |
| Servo Control | | | | | | | | | | |
| Servo control | 2 | 4.118-007.0 | 0-750 l/h | | | | | | Servo control for water flow and pressure control (< 750 l/h) on trigger gun. | ■ |
| Servo Control - high-grade steel version | 3 | 4.118-016.0 | 750-1100 l/h | | | | | | | □ |
| Quick connect | | | | | | | | | | |
| Quick-fitting pipe union coupler trapezo | 4 | 2.115-000.0 | | | | | | | | □ |
| Quick-fitting pipe union plug nipple tra | 5 | 2.115-001.0 | | | | | | | | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0



| | | Order Number | Max. working pressure | Nozzle size | | | Price | Description | |
|--|---|--------------|-----------------------|-------------|--|--|-------|---|---|
| Triple nozzles | | | | | | | | | |
| Triple jet nozzle 060 | 1 | 4.117-040.0 | 300 bar | 60 | | | | | ■ |
| Dirt blaster, large | | | | | | | | | |
| Dirt blaster - without changeover function | 2 | 4.114-036.0 | 300 bar | 55 | | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | □ |

■ Included in delivery.
 □ Available accessories.
 ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Max. working pressure | Length | | | Price | Description | |
|--|----|--------------|-----------------------|---------|--|--|-------|---|---|
| Rotating spray lances | | | | | | | | | |
| Lance 850 mm, rotatable, ergonomic | 1 | 4.112-006.0 | 300 bar | 840 mm | | | | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | ■ |
| Lance 250 mm, non-rotatable | 2 | 4.112-027.0 | 300 bar | 250 mm | | | | | □ |
| 550 mm lance, non-rotatable | 3 | 4.112-024.0 | 300 bar | 400 mm | | | | | □ |
| Rotatable lance, 600 mm, ergonomic | 4 | 4.112-007.0 | 300 bar | 600 mm | | | | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| 1050 mm lance, rotatable, ergonomic | 5 | 4.112-000.0 | 300 bar | 1050 mm | | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 1550 mm, rotatable, ergonomic | 6 | 4.112-018.0 | 300 bar | 1550 mm | | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Lance 2050 mm, rotatable, ergonomic | 7 | 4.112-021.0 | 300 bar | 2050 mm | | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Double lance | | | | | | | | | |
| Double lance 960 mm | 8 | 6.394-665.0 | 310 bar | 960 mm | | | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | □ |
| Angular spray lance | | | | | | | | | |
| WC and gutter lance | 9 | 4.112-029.0 | | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | □ |
| Flexible spray lance | | | | | | | | | |
| Flexible lance 1050 mm | 10 | 4.112-035.0 | 210 bar | 1050 mm | | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | □ |
| Telescopic spray lance | | | | | | | | | |
| Telescopic jet pipe | 11 | 4.112-037.0 | 225 bar | 5400 mm | | | | | □ |
| Restraint belt for telescopic jet pipe | 12 | 6.373-987.0 | | | | | | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. | □ |
| Gutter cleaner | | | | | | | | | |
| Gutter cleaning lance | 13 | 2.112-015.0 | | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | □ |
| Undercarriage spray lance | | | | | | | | | |
| Underbody lance | 14 | 4.112-032.0 | | 700 mm | | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | □ |
| Additional handle | | | | | | | | | |
| | 15 | 4.321-380.0 | | | | | | | □ |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Flow rate | Nozzle size | Diameter | Price | Description | |
|---|----|--------------|-----------|-------------|----------|-------|--|--------------------------|
| Hard Surface Cleaner FRV 30 | | | | | | | | |
| Add-on kit rubber lip | 1 | 2.642-910.0 | | | | | For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes. | <input type="checkbox"/> |
| Extension hose 5 m | 2 | 4.440-939.0 | | | | | 5m extension hose for FRV 30. Connection sleeve included. | <input type="checkbox"/> |
| Add-on kit hose attachment | 3 | 2.642-528.0 | | | | | | <input type="checkbox"/> |
| Add-on kit dirt trap | 4 | 2.642-532.0 | | | | | | <input type="checkbox"/> |
| FRV 30 | 5 | 2.111-010.0 | | | | | | <input type="checkbox"/> |
| Hard surface cleaner FR 30 | | | | | | | | |
| FR 30 | 6 | 2.111-011.0 | | | 300 mm | | | <input type="checkbox"/> |
| Hard surface cleaner FR 30 ME | | | | | | | | |
| FR 30 ME surface cleaner | 7 | 2.111-013.0 | | | 300 mm | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | <input type="checkbox"/> |
| Hard Surface Cleaner FR 50 | | | | | | | | |
| FR 50 surface cleaner | 8 | 2.111-023.0 | | | 500 mm | | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. | <input type="checkbox"/> |
| Machine-specific nozzle kits for FRV | | | | | | | | |
| Nozzle kit 050 for FRV 30 | 9 | 2.642-433.0 | | 50 | | | | <input type="checkbox"/> |
| Hard surface cleaner FRV 30 Me | | | | | | | | |
| Suction hose FRV 30 me | 10 | 4.441-040.0 | | | | | | <input type="checkbox"/> |
| FRV 30 ME | 11 | 2.111-012.0 | | | | | | <input type="checkbox"/> |
| Surface Cleaner FR 50 Me | | | | | | | | |
| | 12 | 2.111-024.0 | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | | | | | | Price | Description | |
|---|----|--------------|--|--|--|--|--|-------|--|--------------------------|
| Nozzle union | | | | | | | | | | |
| Protection part TR only for replacement | 1 | 4.112-011.0 | | | | | | | | <input type="checkbox"/> |
| Coupling parts | | | | | | | | | | |
| | 2 | 6.987-705.0 | | | | | | | | <input type="checkbox"/> |
| Rotary coupling | | | | | | | | | | |
| Rotary coupling | 3 | 4.111-021.0 | | | | | | | Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection. | <input type="checkbox"/> |
| Coupling | | | | | | | | | | |
| Coupler - 2xM22x1,5 | 4 | 4.111-037.0 | | | | | | | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m. | <input type="checkbox"/> |
| Connector | | | | | | | | | | |
| Nozzle connector/screw connector | 5 | 4.111-022.0 | | | | | | | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. | <input type="checkbox"/> |
| | 6 | 4.111-038.0 | | | | | | | | <input type="checkbox"/> |
| Adapter EASY!Lock | | | | | | | | | | |
| Adapter 1 M22AG-TR22AG | 7 | 4.111-029.0 | | | | | | | | <input type="checkbox"/> |
| Adapter 2 M22IG-TR22AG | 8 | 4.111-030.0 | | | | | | | | <input type="checkbox"/> |
| Adapter 3 M22IG-TR22AG | 9 | 4.111-031.0 | | | | | | | | <input type="checkbox"/> |
| Adapter M22 - Swivel | 10 | 4.111-032.0 | | | | | | | M22 x 1.5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection. | <input type="checkbox"/> |
| Adapter 5 TR22IG-M22AG | 11 | 4.111-033.0 | | | | | | | | <input type="checkbox"/> |
| Adapter 6 TR22IG-M22AG | 12 | 4.111-034.0 | | | | | | | | <input type="checkbox"/> |
| Adapter 7 M18IG-TR20AG | 13 | 4.111-035.0 | | | | | | | | <input type="checkbox"/> |
| Adapter 8 TR20IG-M18AG | 14 | 4.111-036.0 | | | | | | | | <input type="checkbox"/> |
| HP detergent injector | | | | | | | | | | |
| Detergent injector for high pressure | 15 | 3.637-170.0 | | | | | | | Cleaning agent dosage at high pressure 3 - 5 % | <input type="checkbox"/> |
| Machine-specific nozzle kit with order no. 3.637-170 | | | | | | | | | | |
| Machine-specific nozzle kit with order no. 3.637-170.0 HD 500-700 l/h | 16 | 4.769-045.0 | | | | | | | For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0



| | | Order Number | Nozzle size | | | | Price | Description | |
|-------------------------------------|---|--------------|-------------|--|--|--|-------|--|--------------------------|
| HP nozzle spray angle 0° | | | | | | | | | |
| High-pressure nozzle spray angle °0 | 1 | 2.113-036.0 | 60 | | | | | Solid jet for very stubborn dirt and stains. | <input type="checkbox"/> |
| Power nozzle spray angle 15° | | | | | | | | | |
| Power nozzle spray angle 15° | 2 | 2.113-048.0 | 60 | | | | | Fan jet nozzle for stubborn dirt and stains. | <input type="checkbox"/> |
| Power nozzle spray angle 25° | | | | | | | | | |
| Power nozzle 25° spray angle | 3 | 2.113-026.0 | 60 | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Nozzle size | | | | Price | Description | |
|---|---|--------------|-------------|--|--|--|-------|---|--------------------------|
| Wet blasting attachment (without nozzle) | | | | | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.115-000.0 | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. | <input type="checkbox"/> |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.115-006.0 | | | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. | <input type="checkbox"/> |
| Nozzle pack for wet blasting attachment | | | | | | | | | |
| Nozzle pack TR wet jet set 0060 | 3 | 2.112-025.0 | 60 | | | | | | <input type="checkbox"/> |
| Boron carbide nozzle | | | | | | | | | |
| Boron carbide nozzle, for machines as of 1000 l/h | 4 | 6.415-084.0 | 6 mm | | | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Max. working pressure | Nozzle size | Diameter | | Price | Description | |
|--|----|--------------|-----------------------|-------------|----------|--|-------|---|--------------------------|
| Pipe cleaning hose, ID 6 | | | | | | | | | |
| Hose assembly TR pipe cleaning DN6 max.2 | 1 | 6.110-046.0 | 250 bar | | | | | | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 2 | 6.110-008.0 | 250 bar | | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). | <input type="checkbox"/> |
| Hose assembly TR pipe cleaning DN6 max.2 | 3 | 6.110-047.0 | 250 bar | | | | | | <input type="checkbox"/> |
| Hose assembly TR pipe cleaning DN6 14MPa | 4 | 6.110-048.0 | 140 bar | | | | | | <input type="checkbox"/> |
| Pipe cleaning hose | 5 | 6.110-049.0 | 140 bar | | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | <input type="checkbox"/> |
| Pipe cleaning hose, DN 6, 30 m | 6 | 6.110-050.0 | 140 bar | | | | | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | <input type="checkbox"/> |
| Pipe cleaning nozzle | | | | | | | | | |
| Drain cleaning dirt blaster D 25/060 | 7 | 6.415-945.0 | | 60 | 25 mm | | | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | <input type="checkbox"/> |
| Drain cleaning dirt blaster D 30/060 | 8 | 6.415-947.0 | | 60 | 30 mm | | | | <input type="checkbox"/> |
| Drain cleaning dirt blaster D 35/060 | 9 | 6.415-949.0 | | 60 | 35 mm | | | | <input type="checkbox"/> |
| Pipe cleaning nozzle | 10 | 5.763-019.0 | | 65 | 16 mm | | | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| | 11 | 5.763-021.0 | | 70 | 30 mm | | | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |
| Rotating pipe cleaning nozzle | 12 | 6.415-440.0 | | 65 | 16 mm | | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Flow rate | | | | Price | Description | |
|--|---|--------------|-------------|--|--|--|-------|---|--------------------------|
| Cup foam lance | | | | | | | | | |
| Packing complete for 6.394-968.0 | 1 | 2.112-017.0 | | | | | | | <input type="checkbox"/> |
| Tank 1L | 2 | 6.414-954.0 | | | | | | | <input type="checkbox"/> |
| Inno Foam Set | | | | | | | | | |
| Inno foam kit with detergent injector | 3 | 2.640-151.0 | | | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | <input type="checkbox"/> |
| Inno foam set HD 7/10 CXF | 4 | 2.112-009.0 | | | | | | Complete ready-to-use high-pressure foam system for use in the food and sanitary industries with HD 7/10 CXF for cleaning and disinfection. Double spray lance with foam nozzle and switch to high-pressure jet for rinsing, etc., CA-HP injector with precise 0 - 5 % metering valve. Nozzle kit included in delivery. | <input type="checkbox"/> |
| Easy Foam Set | | | | | | | | | |
| Easy-Foam-Set HD 7/10 CXF | 5 | 2.112-012.0 | | | | | | Complete ready-to-use high-pressure foam system for use in the food and sanitary industries with HD 7/10 CXF for cleaning and disinfection. Foam nozzle for connection to HP spray lance and high-pressure detergent injector with pressure 0-5 % metering valve. Nozzle kit included in delivery. | <input type="checkbox"/> |
| Nozzle kits for Inno/Easy Foam Set | | | | | | | | | |
| Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h | 6 | 2.640-687.0 | 600-700 l/h | | | | | Optimal adaptation to different machine outputs for economic use. | <input type="checkbox"/> |
| Foam nozzle mounting kit | | | | | | | | | |
| Foam nozzle kit | 7 | 2.637-926.0 | | | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | <input type="checkbox"/> |
| | 8 | 2.112-013.0 | | | | | | | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Length | | | | | Price | Description | |
|---|---|--------------|--------|--|--|--|--|-------|--|--------------------------|
| Automatic, self-winding hose reels | | | | | | | | | | |
| Add-on kit hose reel plastics | 1 | 6.392-074.0 | 20 m | | | | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | <input type="checkbox"/> |
| Add-on kit hose reel | 2 | 6.392-083.0 | 20 m | | | | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, painted | 3 | 6.392-106.0 | 20 m | | | | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| | 4 | 6.392-105.0 | 20 m | | | | | | | <input type="checkbox"/> |
| Hose reel, automatic, 20 m, stainless steel | 5 | 6.392-076.0 | 20 m | | | | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | <input type="checkbox"/> |
| ABS hose reel stainless steel | 6 | 6.392-122.0 | 20 m | | | | | | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled spring drive. Connection for HP hoses with nipple. | <input type="checkbox"/> |
| Swivel holder | 7 | 2.639-931.0 | | | | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. | <input type="checkbox"/> |
| ABS wall fastening stainless steel | 8 | 2.641-867.0 | | | | | | | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0




| | | Order Number | Flow rate | | | | | Price | Description | |
|--------------------------------|---|--------------|-------------|--|--|--|--|-------|--|--------------------------|
| Push-on washing brush | | | | | | | | | | |
| Push-on washing brush | 1 | 4.762-497.0 | | | | | | | With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles. | <input type="checkbox"/> |
| Push-on wash brush, M 18 x 1.5 | 2 | 4.113-001.0 | | | | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6. | <input type="checkbox"/> |
| Rotating washing brush | | | | | | | | | | |
| | 3 | 4.113-004.0 | 500-800 l/h | | | | | | | <input type="checkbox"/> |
| | 4 | 4.113-003.0 | 500-800 l/h | | | | | | | <input type="checkbox"/> |

■ Included in delivery.
 ☐ Available accessories.
 ▲ Extension hose.

ACCESSORIES FOR HD 7/10 CXF

1.151-906.0

KÄRCHER



| | | Order Number | Length | Diameter | | | Price | Description | |
|-------------------------------------|---|--------------|--------|----------|--|--|-------|--|--------------------------|
| Geka coupling | | | | | | | | | |
| With hose nozzle, R 1/2" | 1 | 6.388-461.0 | | | | | | with hose liner | <input type="checkbox"/> |
| With hose nozzle, R 3/4" | 2 | 6.388-455.0 | | | | | | | <input type="checkbox"/> |
| With female thread, R 3/4" | 3 | 6.388-473.0 | | | | | | with female thread | <input type="checkbox"/> |
| Suction filter | | | | | | | | | |
| Water filter | 4 | 6.414-956.0 | | | | | | | <input type="checkbox"/> |
| Suction filter with check valve | 5 | 4.730-012.0 | | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | <input type="checkbox"/> |
| Fine-mesh water filter | | | | | | | | | |
| Fine-mesh water filter with adapter | 6 | 4.730-102.0 | | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | <input type="checkbox"/> |
| Water supply hose | | | | | | | | | |
| Water supply hose | 7 | 4.440-038.0 | 7,5 m | | | | | NW 13 R1" / R 3/4", up to 30 °C | <input type="checkbox"/> |
| Backflow check valve | | | | | | | | | |
| Backflow preventer | 8 | 2.641-374.0 | | | | | | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection | <input type="checkbox"/> |

■ Included in delivery. □ Available accessories. ▲ Extension hose.