KARCHER




HDS 2000 Super

Twin-pump hot water high-pressure cleaner for two person operation.







1 Duo drive concept

- Two fatigue tested, water-cooled three-phase motors.
- Delayed start prevents mains overload.

2 Service control

- Electronic machine monitoring to protect against disturbances.
- Service interval display via LED.





3 Burner technology (oil-heated)

- Highly efficient burner technology.
- Spiral heating coil for a compact design.

4 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.

TECHNICAL DATA AND EQUIPMENT.

KARCHER



HDS 2000 Super

- Two powerful pump units
 Electronic service control with flame monitor
 cleaning agent dosing can be controlled from the trigger gun

Technical data				
Order Number		1.071-934.0		
EAN code		4054278172392		
Current type	Ph / V / Hz	3 / 400 / 50		
Flow rate	l/h	800-1850		
Pressure	bar / MPa	30-180 / 3-18		
Max. temperature	°C	80 / 98		
Power rating	kW	2 x 6,7		
Consumption fuel oil	kg/h	12,3		
Fuel tank	1	25		
Weight	kg	280		
Dimensions (L x W x H)	mm	1500 × 834 × 1015		
Equipment				
Trigger gun		EASY!Force Advanced	SDS system	•
High-pressure hose	m	15 / Longlife	Electronic service control with LED display	•
Spray lance	mm	1050	2 pump units with ceramic sleeves	
Power nozzle			Two detergent tanks	
Servo Control			Dry running protection	
Anti-twist system (AVS)		-		
Galvanized and powder coated chassis	;			
Three piston axial pump		with ceramic piston		
Pressure switch control				
Optional two-lance operation		•		
Pole reversing plug (three-phase)				
Included in delivery.				



		Order Number	ID	Max. working pressure	Length	Price	Description
Standard with unions on both sides				1			
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.
Food industry version with unions	on bot	h sides					
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	4	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	5	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.
Longlife food industry version with	union	s on both sides					
High pressure hose food DN 8 / 10 m	6	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5
Longlife 400 with unions on both si	des						
High-pressure hose 1.5 m, DN 8, including connectors	7	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).





		Order Number	Flow rate		Price	Description
Trigger guns			·			· · · · · · · · · · · · · · · · · · ·
Extended easy press trigger gun	1	4.118-005.0				Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.
Servo Control						
Servo control	2	4.118-009.0	1100 l/h			
Quick connect						
Quick-fitting pipe union coupler trapezo	3	2.115-000.0				c
Quick-fitting pipe union plug nipple tra	4	2.115-001.0				Γ




		Order Number	Nozzle size			Price	Description
Power nozzle spray angle 25°							II
Power nozzle spray angle 25°	1	2.113-018.0	110				Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°							
High-pressure nozzle spray angle °0	2	2.113-039.0	110				Solid jet for very stubborn dirt and stains.
Power nozzle spray angle 15°							
Power nozzle spray angle 15°	3	2.113-052.0	100				Fan jet nozzle for stubborn dirt and stains.
Power nozzle spray angle 40°					 		
Nozzle chemical trapezoidal thread for r	4	2.113-067.0	130				
■ Included in delivery. □ Av	ailable	e accessories.	Extension ho)SP			



		Order Number	Max. working pressure	Length			Price	Description	
Rotating spray lances									
1050 mm lance, rotatable, ergonomic	1	4.112-000.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm					
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm					
Rotatable lance, 600 mm, ergonomic	4	4.112-007.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 1550 mm, rotatable, ergonomic	6	4.112-018.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Lance 2050 mm, rotatable, ergonomic	7	4.112-021.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Double lance									
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	
Angular spray lance									
WC and gutter lance	9	4.112-029.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance								,	
Flexible lance 1050 mm	10	4.112-035.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance		1		1	1			1	
Telescopic jet pipe	11		225 bar	5400 mm					
Restraint belt for telescopic jet pipe	12	6.373-987.0						Convenient strap for relief when working with the telescopi spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	
Gutter cleaner						· · · ·			
Gutter cleaning lance	13	2.112-015.0						The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance									
Underbody lance	14	4.112-032.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle									
	15	4.321-380.0							
Included in delivery.	vailable	e accessories.	▲ Extension h	ose.					







		Order Number	Flow rate	Nozzle size		Price	Description
Machine-specific nozzle kits for FR	v						
Nozzle pack 080	1	2.642-982.0		80			

				D	6		$\left \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
		Order Number				Price	Description	
Nozzle union Protection part TR only for	1	4.112-011.0		1 1				
replacement	1	4.112-011.0						
Spacer (including nozzle union) Spacer (incl.nozzle union)	2	5.394-294.0					Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	
Coupling parts		C 007 705 0		1 1		1	1	
Rotary coupling	3	6.987-705.0	I			I		
Rotary coupling	4	4.111-021.0					Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling								
Coupler -2xM22x1,5	5	4.111-037.0					Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \ x \ 1.5 \ m.$	
Connector						1	1	
Nozzle connector/screw connector	6	4.111-022.0					Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
	7	4.111-038.0						
Adapter EASY!Lock		4 4 4 4 0 20 0	1	1 1		1		
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	8	4.111-029.0 4.111-030.0					-	
Adapter 3 M22IG-TR22AG	10	4.111-031.0					-	H
Adapter M22 - Swivel	11	4.111-032.0					M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	12	4.111-033.0						
Adapter 6 TR22IG-M22AG	13	4.111-034.0					4	
Adapter 7 M18IG-TR20AG	14						-	
Adapter 8 TR20IG-M18AG	15	4.111-036.0				l		
Flue pipe Flue gas adapter	16	4.656-079.0					Flue gas adapter with draught damper for flue pipe	
	10	4.030-073.0					connection (adapter for HDS burners for connection to a stack system).	
HP detergent injector	1		1	1				
Detergent injector for high and low pressure (without nozzles)	17	4.637-032.0					Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	18	4.637-033.0					Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with or	der no	. 3.637-170						
Machine-specific nozzle kit with order no. 3.637-170.0 1000-1200 I/h I/h	19	4.769-048.0					For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637- High pressure for units rated 1100 I/h or more	1	4.769-002.0					For high pressure with machines above 1.100 l/h	
Included in delivery		·	Extension hose	I				

■ Included in delivery.
□ Available accessories.
▲ Extension hose.

HDS 2000 Super, 1.071-934.0, 2017-07-19



		Order Number			Price	Description	
Low pressure for units rated 1100	21	4.769-006.0				For low pressure with machines above 1.100 l/h	П
I/h or more							



		Order Number	Max. working pressure	Nozzle size		Price	Description	
Barrel and tank cleaning								
	1	2.112-020.0						
■ Included in delivery. □ Av	/ailable	e accessories.	▲ Extension ho	ose.				



		Order Number	Max. working	Nozzle size		Price	Description
Angle vario nozzle 0°-90°							
Variable angle nozzle 0-90°	1	4.113-008.0		55			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
Dirt blaster, large			·				
Dirt blaster - without changeover function	2	4.114-044.0	300 bar	120			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.



		Order Number	Nozzle size			Price	Description
Wet blasting attachment (without r	ozzle))					· · · · · · · · · · · · · · · · · · ·
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.
Boron carbide nozzle							
Boron carbide nozzle, for machines as of 1000 l/h	3	6.415-083.0	8 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension ho	ose.			

HDS 2000 Super, 1.071-934.0, 2017-07-19



		Order Number	Flow rate		Price	Description
Cup foam lance						· · · · ·
Packing complete for 6.394-968.0	1	2.112-017.0				
Tank 1L	2	6.414-954.0				
Inno Foam Set						
Inno foam kit with detergent injector	3	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and
Inno foam kit	4	2.112-008.0				stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	5	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and
Easy foam set	6	2.112-011.0				disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 110 Inno/Easy set 1000 - 1300 I/h	7	2.111-020.0	1000-1300 l/h			Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.
Foam nozzle mounting kit						
Foam nozzle kit	8	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.













		Order Number	Length		Price	Description
Automatic, self-winding hose reels						· · · · · · · · · · · · · · · · · · ·
Add-on kit hose reel plastics	1	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.
Add-on kit hose reel	2	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.
Hose reel, automatic, 20 m, painted	3	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.
	4	6.392-105.0	20 m			
Hose reel, automatic, 20 m, _stainless steel	5	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.
ABS hose reel stainless steel	6	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.
Swivel holder	7	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
ABS wall fastening stainless steel	8	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.



		Order Number	Flow rate			Price	Description	
Push-on washing brush								
Push-on wash brush, M 18 x 1.5	1	4.113-001.0					Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	
Rotating washing brush								
	2	4.113-002.0	800-1300 l/h					
	3	4.113-005.0	800-1300 l/h					
■ Included in delivery. □ Av	ailable	e accessories.	▲ Extension h	ose.				

KARCHER

ACCESSORIES FOR HDS 2000 SUPER 1.071-934.0



		Order Number	Length	Diameter		Price	Description	
Geka coupling								
With hose nozzle, R 3/4"	1	6.388-455.0					with hose liner	0
With hose nozzle, R 1"	2	6.388-465.0						
Hose coupling	3	6.388-458.0					with female thread	Γ
Suction filter								
Water filter	4	6.414-956.0						
Suction filter with check valve	5	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter								
Fine-mesh water filter with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	
Fine-mesh water filter, 100 µm, R 1"	7	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high- pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	
Water supply hose		•		•			· · · · ·	
Water supply hose	8	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	9	4.440-270.0	7,5 m				NW 19 R1" / R1", up to 85 °C	