



#### HDS 9/16-4 ST Gas

Stationary gas-fired hot water high-pressure cleaner



1 Water-cooled 4-pole electric motor (oil-heated)

Long service life.

Improved efficiency.

#### 2 Burner technology (oil-heated)

High heat output.

Spiral heating coil for a compact design.

HDS 9/16-4 ST Gas, 1.251-900.0, 2017-07-31

#### **TECHNICAL DATA AND EQUIPMENT.**

#### KARCHER



#### HDS 9/16-4 ST Gas

Dry running protection

- Surface-type burner technology
   Water-cooled stainless steel boiler with built-in stainless steel

_	vvulci	coolcu	Stunness	Sic
	heater	coil		

Technical data		
Order Number		1.251-900.0
EAN code		4054278169354
Current type	Ph / V / Hz	3 / 400 / 50
Fuse protection	Α	min. 16
Flow rate	l/h	500-960
Pressure	bar / MPa	30-160 / 3-16
Max. temperature	°C	98
Power rating	kW	6,4
Consumption, heating oil/gas	m³/h	7,2
Weight	kg	160
Dimensions (L x W x H)	mm	1110 × 565 × 970

Equipment	
SDS system	1
System pressure relief	I contraction of the second seco
Flame monitor	I Contraction of the second seco
Ready for Servo Control	I Contraction of the second seco
Ready for remote control	I Contraction of the second seco
Included in delivery.	



		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides	5	1		1				
High-pressure hose, 30 m DN 8, including rotary coupling	1	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose, 15 m DN 10, 220 bar, extension	2	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	
High-pressure hose, 20 m DN 10, 220 bar, extension	3	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protec- tion. NW 10/155°C/220 bar	
High-pressure hose, 25 m DN 10, extension, not rotatable	4	6.110-044.0	ID 10	220 bar	25 m			
Hose assembly premium DN12 21MPa 15m	5	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than $1,800$ l h. With union on both sides. $2 \times M 22 \times 1.5$ with anti-kink	/
Hose assembly premium DN12 21MPa 40m	6	6.110-060.0	ID 12	210 bar	40 m		protection.	
Longlife 400 with unions on both s	ides							
High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling	7	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 20 m, DN 8, extension	8	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling	9	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	
High-pressure hose 1.5 m, DN 8, including connectors	10	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	
	11	6.110-069.0	ID 8	400 bar	1,5 m			
High-pressure hose packaged	12	6.110-038.0	ID 8	400 bar	10 m			
Food industry version with unions	on bot	h sides						
High-pressure hose, 10 m ID 8, suitable for food industry, extensi- on piece	13	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	
High-pressure hose, 20 m ID 8, suitable for food industry, extensi- on piece	14	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Con- nectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	
Longlife food industry version with	h unior	is on both sides						
High pressure hose food DN 8 / 10 m	15	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With rotary coupling, 2 x M 22 x 1,5	
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun con- nection	16	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Au&ende- cke## animal-grease-resistant, non-colour-bleeding materi- al. With patented AVS connection in the pistol (pivot moun- ted)	

□ Available accessories. ▲ Extension hose.

#### KARCHER



					Diame-		
		Order Number	Flow rate	Nozzle size	ter	Price	Description
Hard surface cleaner FR 30 ME				1		 	
FR 30 ME surface cleaner	1	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50							
FR 50 surface cleaner	2	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kit for FR							
Nozzle kit for surface cleaners (type-specific) 850 - 1100 l/h	3	2.640-442.0	850-1100 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).
Machine-specific nozzle kits for FF	٧V						
Nozzle pack 080	4	2.642-982.0		80			
Hard surface cleaner FRV 30 Me							
Suction hose FRV 30 me	5	4.441-040.0					
FRV 30 ME	6	2.111-012.0					
Surface Cleaner FR 50 Me							
	7	2.111-024.0					
□ Available accessories. ▲ E	Extensi	on hose.					

2 2 3 3				6		$ \left  \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	
		Order Number			Price	Description	
Nozzle union Protection part TR only for repla-	1	4.112-011.0					
cement Coupling parts							
	2	6.987-705.0					
Rotary coupling Rotary coupling	3	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling		<u> </u>				n. with grip protection.	
Coupler -2xM22x1,5	4	4.111-037.0				Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \text{ M } 22 x 1.5 \text{ m}$ .	
Connector Nozzle connector/screw connector	5	4.111-022.0				Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
	6	4.111-038.0					
Adapter EASY!Lock	7	4.111-029.0					
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	8	4.111-029.0				-	
Adapter 3 M22IG-TR22AG	9	4.111-031.0				-	
Adapter M22 - Swivel	10	4.111-032.0				M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connec- tion.	
Adapter 5 TR22IG-M22AG	11	4.111-033.0					
Adapter 6 TR22IG-M22AG		4.111-034.0				_	
Adapter 7 M18IG-TR20AG Adapter 8 TR20IG-M18AG	13		 _			-	
Adapter 8 TR20IG-M18AG ADAPTER for replacement TR22IG-	14 15	4.111-036.0 4.111-046.0				-	
M22AG Er	15						
HP detergent injector		4 627 022 0					
Detergent injector for high and low pressure (without nozzles)	16	4.637-032.0				Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressu- re	17	4.637-033.0				Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with or	der no	. 3.637-170					
Machine-specific nozzle kit with order no. 3.637-170.0 750-1000 I/h	18	4.769-047.0				For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-			1 1				1
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.	19	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	20	4.769-001.0				For low pressure with machines up to 1.100 l/h	

HDS 9/16-4 ST Gas, 1.251-900.0, 2017-07-31



		Order Number	Nozzle size		Price	Description
HP nozzle spray angle 0°						
High-pressure nozzle spray angle °0	1	2.113-036.0	60			Solid jet for very stubborn dirt and stains.
Power nozzle spray angle 15°						
Power nozzle spray angle $15^{\circ}$	2	2.113-048.0	60			Fan jet nozzle for stubborn dirt and stains.
Power nozzle spray angle 25°						
Power nozzle 25° spray angle	3	2.113-026.0	60			
□ Available accessories. ▲ E	xtens	ion hose.				



		Order Number	Flow rate		Price	Description	
Trigger guns							╘
Extended easy press trigger gun	1	4.118-005.0				Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.	
Servo Control							
Servo control	2	4.118-008.0	750-1100 l/h				
Quick connect							
Quick-fitting pipe union coupler trapezo	3	2.115-000.0					
Quick-fitting pipe union plug nipp- le tra	4	2.115-001.0					
□ Available accessories. ▲ E	ktensi	on hose.	-		 ·		

HDS 9/16-4 ST Gas, 1.251-900.0, 2017-07-31



		Order Number	Nozzle size		Price	Description
Wet blasting attachment (without n	ozzle)					· ·
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control.
Nozzle pack for wet blasting attach	ment					
Nozzle pack TR wet jet set 0060	3	2.112-025.0	60			
Boron carbide nozzle						
Boron carbide nozzle, for machi- nes as of 1000 l/h	4	6.415-084.0	6 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Available accessories. 🔺 Ext



		Order Number	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6 Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar					
Pipe cleaning hose, DN 6, 20 m, 220 bar	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar					

 $\hfill\square$  Available accessories.  $\hfill A$  Extension hose.



			Max. working					
		Order Number	pressure	Nozzle size		Price	Description	
Dirt blaster, large								
Dirt blaster - without changeover function	1	4.114-036.0	300 bar	55			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

□ Available accessories. ▲ Extension hose.



Order Number           2.112-017.0           6.414-954.0           2.112-000.0	Flow rate				Price	Description
2.112-017.0 6.414-954.0	· Flow rate				Price	Description
2 6.414-954.0						
2 6.414-954.0						
2 112-000 0						]
2 2 1 1 2 000 0						
2.112.000.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
	· · ·					
2.112-010.0						HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
5 2.111-019.0	700-1000 l/h					Nozzle kit contains Kärcher power nozzles and nozzle in- serts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.
5 2.112-013.0						Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary.
5	2.111-019.0	2.111-019.0 700-1000 l/h 2.112-013.0	2.111-019.0     700-1000 l/h       2.112-013.0			

□ Available accessories. ▲ Extension hose

#### KARCHER

















		Order Number	Length		Price	Description	
Automatic, self-winding hose reels							_
Add-on kit hose reel plastics	1	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	2	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic.	
Hose reel, automatic, 20 m, pain- ted	3	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose.	
	4	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stain- less steel	5	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	6	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Swivel holder	7	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	
ABS wall fastening stainless steel	8	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.	
Add-on kit hose reel TR 40m	9	6.392-442.0	40 m				

□ Available accessories. ▲ Extension hose.

1	2	3	4-5	6	7	9
10	11	12	13	14	15	16

		Order Number	Max. working pressure	Length		Price	Description	
Rotating spray lances	1			I	1 1			-
Lance 250 mm, non-rotatable	1	4.112-027.0	300 bar	250 mm				
550 mm lance, non-rotatable	2	4.112-024.0	300 bar	400 mm				
Rotatable lance, 600 mm, ergono- mic	3	4.112-007.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergono mic handle for ease of use and protection. Rotatable 360° under pressure.	-
Lance 850 mm, rotatable, ergono- mic	4	4.112-006.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergono mic handle for ease of use and protection. Rotatable 360° under pressure.	-
1050 mm lance, rotatable, ergono- mic	5	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 1550 mm, rotatable, ergo- nomic	6	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Lance 2050 mm, rotatable, ergo- nomic	7	4.112-021.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360 under pressure.	
Jet pipe extension TR 1000 mm	8	4.112-048.0	300 bar	1000 mm				
Double lance								
Double lance 960 mm	9	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use ( e.g. stable cleaning).	
Angular spray lance								
WC and gutter lance	10	4.112-029.0					Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance								
Flexible lance 1050 mm	11	4.112-035.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
Telescopic spray lance				1			,	
Telescopic jet pipe	12	4.112-037.0	225 bar	5400 mm		_		
Restraint belt for telescopic jet pipe	13	6.373-987.0					Convenient strap for relief when working with the telesco- pic spray lance (6.394-690). The burden is optimally distri- buted on the body and longer periods of use are possible.	
Gutter cleaner				1	1			
Gutter cleaning lance	14	2.112-015.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				1				
Underbody lance	15	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle								
	16	4.321-380.0						
□ Available accessories. ▲ E		on hose.		<u> </u>	I		1	-



							$\square$
		Order Number	Flow rate		Price	Description	
Push-on washing brush							
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	
Rotating washing brush							
	2	4.113-002.0	800-1300 l/h				
	3	4.113-005.0	800-1300 l/h				
□ Available accessories. ▲ E	ktensi	on hose.					



								$\square$
		Order Number	Length	Diameter		Price	Description	
Geka coupling								
Hose coupling	1	6.388-458.0					with female thread	
Water supply hose								
Water supply hose	2	4.440-038.0	7,5 m				NW 13 R1" / R 3/4", up to 30 °C	
□ Available accessories. ▲ E	vtonci	ion hoso						