



HDS 12/14-4 ST Gas

Stationary gas-fired hot water high-pressure cleaner









- 1 Water-cooled 4-pole electric motor (oil-heated)
- Long service life.
- Improved efficiency.
- 2 Burner technology (oil-heated)
- High heat output.
- Spiral heating coil for a compact design.

TECHNICAL DATA AND EQUIPMENT.





HDS 12/14-4 ST Gas

- Dry running protection
 Surface-type burner technology
 Water-cooled stainless steel boiler with built-in stainless steel heater coil

Technical data		
Order Number		1.251-901.0
EAN code		4054278169361
Current type	Ph / V / Hz	3 / 400 / 50
Fuse protection	Α	16
Flow rate	I/h	600-1200
Pressure	bar / MPa	30-140 / 3-14
Max. temperature	°C	98
Power rating	kW	7,5
Consumption, heating oil/gas	kg/h	8,9
Weight	kg	170
Dimensions (L x W x H)	mm	1110 × 565 × 1080

Equipment			
SDS system			
System pressure relief			
Flame monitor	•		
Ready for Servo Control			
Ready for remote control			

■ Included in delivery.





























				Max. working			
		Order Number	ID	pressure	Length	Price	Description
Standard with unions on both sides							
High-pressure hose, 15 m DN 10, 220 bar, extension	1	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.
High-pressure hose, 20 m DN 10, 220 bar, extension	2	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar
High-pressure hose, 25 m DN 10, extension, not rotatable	3	6.110-044.0	ID 10	220 bar	25 m		
Hose assembly premium DN12 21MPa 15m	4	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 x 1.5 with anti-kink
Hose assembly premium DN12 21MPa 40m	5	6.110-060.0	ID 12	210 bar	40 m		protection.
Longlife 400 with unions on both si			1				
High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling	6	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 20 m, DN 8, extension	7	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling	8	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5
High-pressure hose 1.5 m, DN 8, including connectors	9	6.110-024.0	ID 8	400 bar	1,5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).
	10	6.110-069.0	ID 8	400 bar	1,5 m		
High-pressure hose packaged	11	6.110-038.0	ID 8	400 bar	10 m		
Food industry version with unions		1					,
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	12	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	13	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non- discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.
Longlife food industry version with	union	s on both sides					
High pressure hose food DN 8 / 10 m	14	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	15	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

[☐] Available accessories. ▲ Extension hose

















						1		
		Order Number	Flow rate	Nozzle size			Price	Description
Hard surface cleaner FR 30 ME			'					
FR 30 ME surface cleaner	1	2.111-013.0			300 mm			Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50								
FR 50 surface cleaner	2	2.111-023.0			500 mm			Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 1100 - 1300 l/h	3	2.639-188.0	1100-1300 l/h					Nozzle kit includes power nozzles and unions. For Kārcher surface cleaners (1100 to 1300 l/h).
Machine-specific nozzle kits for FR	V							
Nozzle pack 080	4	2.642-982.0		80				
Hard surface cleaner FRV 30 Me								
Suction hose FRV 30 me	5	4.441-040.0						
FRV 30 ME	6	2.111-012.0						
Surface Cleaner FR 50 Me								
	7	2.111-024.0						

[☐] Available accessories. ▲ Extension hose.































							_
		Order Number			Price	Description	
Nozzle union			'				
Protection part TR only for replacement	1	4.112-011.0					
Coupling parts							
	2	6.987-705.0					
Rotary coupling							
Rotary coupling	3	4.111-021.0				Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	
Coupling						,	
Coupler -2xM22x1,5	4	4.111-037.0				Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	
Connector						,	
Nozzle connector/screw connector	5	4.111-022.0				Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	
	6	4.111-038.0					
Adapter EASY!Lock							
Adapter 1 M22AG-TR22AG	7	4.111-029.0					
Adapter 2 M22IG-TR22AG	8	4.111-030.0					
Adapter 3 M22IG-TR22AG	9	4.111-031.0					
Adapter M22 - Swivel	10	4.111-032.0				M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	11	4.111-033.0					
Adapter 6 TR22IG-M22AG	12	4.111-034.0					
Adapter 7 M18IG-TR20AG	13	4.111-035.0					
Adapter 8 TR20IG-M18AG	14	4.111-036.0					
HP detergent injector							
Detergent injector for high and low pressure (without nozzles)	15	4.637-032.0				Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	16	4.637-033.0				Cleaning agent dosage at high pressure 3 - 5 %	
Machine-specific nozzle kit with or	der no	. 3.637-170					
Machine-specific nozzle kit with order no. 3.637-170.0 1000-1200 l/h l/h	17	4.769-048.0				For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-	001		1	 			
Nozzle insert for Order No. 3.637- 001, high-pressure for machines up to 1100 l/h.	18	4.769-003.0				Nozzle insert for detergent injector 3.637-001 for high- pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h Available accessories.	19	4.769-001.0				For low pressure with machines up to 1.100 l/h	





		Order Number	Nozzle size		Price	Description
HP nozzle spray angle 0°						
High-pressure nozzle spray angle °0	1	2.113-038.0	80			High-pressure nozzle with powerful jet for extremely stubborn dirt. $\hfill\Box$
Power nozzle spray angle 15°						
Power nozzle spray angle 15°	2	2.113-051.0	80			Fan jet nozzle with 15 $^{\circ}$ spray angle suitable for stubborn dirt.
Power nozzle spray angle 25°						
Triple nozzle, touchless changeover	3	2.113-015.0	80			
Power nozzle spray angle 40°						
Power nozzle spray angle 40°	4	2.113-057.0	80			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

[☐] Available accessories. ▲ Extension hose.











		Order Number	Flow rate		Price	Description
Trigger guns						
Extended easy press trigger gun	1	4.118-005.0				Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector.
Servo Control						
Servo control	2	4.118-009.0	1100 l/h			
Quick connect						
Quick-fitting pipe union coupler	3	2.115-000.0				
trapezo						
Quick-fitting pipe union plug nipple tra	4	2.115-001.0				

[☐] Available accessories. ▲ Extension hose.







		Order Number	Max. working pressure	Nozzle size		Price	Description
Angle vario nozzle 0°-90°							
Variable angle nozzle 0-90°	1	4.113-006.0		80			Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.
Dirt blaster, large							
Dirt blaster - without changeover function	2	4.114-030.0	300 bar	70			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa. 85°C.

[☐] Available accessories. ▲ Extension hose.







		Order Number	Nozzle size		Price	Description	
Wet blasting attachment (without i	nozzle)					
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0				Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attach	ment						
Nozzle pack TR wet jet set 0080	3	2.112-029.0	80				
Boron carbide nozzle							
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-083.0	8 mm			In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	

[□] Available accessories. ▲ Extension hose.





		Order Number	Max. working	Nozzle size		Price	Description	
		Order Norriber	pressure	NUZZIE SIZE		PIICE	Description	
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning	1	6.110-046.0	250 bar					
DN6 max.2								
Pipe cleaning hose, DN 6, 20 m,	2	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes	
220 bar							up to 220 bar (threaded connection for R 1/8 nozzle).	┸╜
Hose assembly TR pipe cleaning	3	6.110-047.0	250 bar					
DN6 max.2								

[☐] Available accessories. ▲ Extension hose.













		Order Number	Flow rate		Price	Description
Cup foam lance						
Packing complete for 6.394-968.0	1	2.112-017.0				
Tank 1L	2	6.414-954.0				
Inno Foam Set						
Inno foam kit with detergent injector	3	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	4	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Nozzle kits for Inno/Easy Foam Set						
Nozzle kit 110 Inno/Easy set 1000 - 1300 I/h	5	2.111-020.0	1000-1300 l/h			Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance.
Foam nozzle mounting kit						
Foam nozzle kit	6	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[☐] Available accessories. ▲ Extension hose.

















							Г
		Order Number	Length		Price	Description	
Automatic, self-winding hose reels							
Add-on kit hose reel plastics	1	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Add-on kit hose reel	2	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Hose reel, automatic, 20 m, painted	3	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose.	-
	4	6.392-105.0	20 m				
Hose reel, automatic, 20 m, stainless steel	5	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
ABS hose reel stainless steel	6	6.392-122.0	20 m			High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	
Swivel holder	7	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	
ABS wall fastening stainless steel	8	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[☐] Available accessories. ▲ Extension hose.





14 2.112-015.0

15 4.112-032.0

16 4.321-380.0

700 mm

pipe

Gutter cleaner

Gutter cleaning lance

Additional handle

Undercarriage spray lance
Underbody lance

spray lance (6.394-690). The burden is optimally distributed \Box

The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.

Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.

on the body and longer periods of use are possible.

[☐] Available accessories. ▲ Extension hose.









		Order Number	Flow rate		Price	Description
Push-on washing brush						
Push-on washing brush	1	4.762-497.0				With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.
Rotating washing brush						
	2	4.113-002.0	800-1300 l/h			
	3	4.113-005.0	800-1300 l/h			

[☐] Available accessories. ▲ Extension hose.





	Order Number	Length	Diameter		Price	Description	
Geka coupling							
Hose coupling	 6.388-458.0					with female thread	

[☐] Available accessories. ▲ Extension hose.