



#### **HDC Advanced**

Stationary high-pressure cleaner for the simultaneous use of 2 to 12 take-off points

#### 1 Modular design

■ The HDC systems can be equipped with up to 4 pumps depending on the requirements. This provides the highest possible level of flexibility for all uses.

#### 2 Intelligent pump control

No matter how much water is needed: the control switches additional pumps on and off as required.

### **TECHNICAL DATA AND EQUIPMENT.**





#### **HDC Advanced**

| Technical data              |           |                   |
|-----------------------------|-----------|-------------------|
| Order No.                   |           | 1.509-502.2       |
| EAN code                    |           | 4039784405578     |
| Pressure                    | bar / MPa | 100 / 10 / /      |
| Flow rate                   | I/h       | 700-12000         |
| Max. water feed temperature | °C        | 85                |
| Motor starting              |           | softstart         |
| Current type                | Ph/V/Hz   | 3 / 400 / 50      |
| Dimensions (L x W x H)      | mm        | 1150 × 750 × 1840 |









|   |   | Order No.   | Flow rate     | Nozzle size | Diame-<br>ter | Price | Description   |  |
|---|---|-------------|---------------|-------------|---------------|-------|---|--|
| Hard surface cleaner FR 30 ME   |   |             |               |             |               |       |   |  |
| FR 30 ME surface cleaner  | 1 | 2.640-355.0 |               |             | 300 mm        |       | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.                |  |
| Hard surface cleaner FR 50  |   |             |               |             |               |       |   |  |
| FR 50 surface cleaner   | 2 | 2.640-679.0 |               |             | 500 mm        |       | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. |  |
| Machine-specific nozzle kit for FR  |   |             |               |             |               |       |   |  |
| Nozzle kit for surface cleaners<br>(type-specific) 850 - 1100 l/h               | 3 | 2.640-442.0 | 850-1100 l/h  |             |               |       | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).   |  |
| Nozzle kit for surface cleaners<br>(type-specific) 1100 - 1300 l/h              | 4 | 2.639-188.0 | 1100-1300 l/h |             |               |       | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (1100 to 1300 l/h).  |  |
| Nozzle pack for hard surface<br>cleaners (machine-specific) 1300<br>- 1,800 l/h | 5 | 2.640-781.0 | 1300-1800 l/h |             |               |       | Machine-specific nozzle kit Kärcher power nozzle for hard surface cleaners  |  |

<sup>☐</sup> Available accessories.































|  |        |             | T |   |   |   |       |   | _  |
|--|--------|-------------|---|---|---|---|-------|---|----|
|  |        |             |   |   |   |   |       |   |    |
|  |        |             |   |   |   |   |       |   |    |
|  |        |             |   |   |   |   |       |   |    |
|  |        | Order No.   |   |   |   |   | Price | Description   |    |
| High-pressure pipework                   |        |             |   |   |   |   |       |   | _  |
| Quick-release coupling, fixed part       | 1      | 6.463-025.0 |   |   |   |   |       | fixed part  | [  |
| Quick-release coupling, moveable         | 2      | 6.463-023.0 |   |   |   |   |       | loose part  | [  |
| part                                     |        |             |   |   |   |   |       |   |    |
| Coupling                                 |        | 1           | ı | 1 | 1 | ı |       | 1   |    |
| Coupler -2xM22x1,5                       | 3      | 4.403-002.0 |   |   |   |   |       | Brass double connector for connecting and extending high-<br>pressure hoses. With rubber protection. Connector: 2x M 2:<br>x 1.5 m.   |    |
| Connector                                |        | l           |   |   |   | l |       | A 1.3 III.  | t  |
| Nozzle connector/screw connector         | 4      | 4.402-022.0 |   |   |   |   |       | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1x \ M \ 22 \ x \ 1.5$ and $1x \ M \ 18 \ x \ 1.5$ . |    |
| Stationary high-pressure cleaning s      | ystem  | ns          |   | - |   |   |       |   |    |
| Trigger gun                              | -      | 4.775-018.0 |   |   |   |   |       |   | [  |
| Double connecting                        | 6      | 5.402-001.0 |   |   |   |   |       |   | [  |
| High-pressure ball valve                 | 7      | 6.412-066.0 |   |   |   |   |       |   | [  |
|  | 8      | 6.412-386.0 |   |   |   |   |       |   | [  |
|  | 9      | 6.412-491.0 |   |   |   |   |       |   | [  |
| Quick release coupling                   | 10     | 6.463-022.0 |   |   |   |   |       |   | [  |
| Stationary high-pressure cleaners        |        |             |   |   |   |   |       |   |    |
|  | 11     | 6.413-500.0 |   |   |   |   |       |   | [  |
| Jet pipe 600 mm                          | 12     | 4.760-625.0 |   |   |   |   |       |   | [  |
| Jet pipe 1050 mm                         | 13     | 4.760-626.0 |   |   |   |   |       |   | _[ |
| NOT YET ATTENDED TO                      | 14     | 4.760-627.0 |   |   |   |   |       |   | [  |
| ><br>Jet pipe 2050 mm                    | 15     | 4.760-628.0 |   |   |   |   |       |   | Г  |
| Take-off point equipment                 | 15     | 4.700-028.0 |   |   |   |   |       |   |    |
| Hose and spray lance holder VA           | 16     | 2.042-003.0 |   |   |   |   |       | Hose and spray lance wall holder for practical and safe storage of high-pressure hoses or spray lances. Stainless   |    |
| Hose track system high-pressure cl       | eaners |             |   |   |   |   |       | steel wall holder.  | +  |
| Hose drum, automatic, 10 m               | 17     | 2.637-750.0 |   |   |   |   |       | 20m   |    |
| Hose reel, manual, 20 m, stainless steel | 18     | 2.637-566.0 |   |   |   |   |       |   |    |
| Take-off point equipment                 |        |             |   |   |   |   |       |   | Ė  |
| Hand trigger gun 30 Mpa 2500 l/h         | 19     | 4.775-799.0 |   |   |   |   |       |   | [  |
| Hand trigger gun 30 Mpa 3000 l/h         | 20     | 4.775-798.0 |   |   |   |   |       |   | [  |
| Hand trigger gun                         | 21     | 4.775-784.0 |   |   |   |   |       |   | [  |
| Applying cleaning agents                 |        |             |   |   |   |   |       |   | ı, |
| Central detergent supply                 | 22     | 3.910-005.0 |   |   |   |   |       |   | [  |
| Foam injector                            | 23     | 3.637-054.0 |   |   |   |   |       |   | [  |
| ABS metering unit double HDC             | 24     | 2.641-702.0 |   |   |   |   |       |   | _[ |
| ABS cleaning agents wall bracket HDC     | 25     | 2.641-703.0 |   |   |   |   |       |   | [  |
| ABS cleaning carriage mobile HDC         | 26     | 2.641-704.0 |   |   |   |   |       |   |    |
| Nozzle for single foam, 900 l/h          | 27     | 4.763-207.0 |   |   |   |   |       | 1   | [  |
| Foam nozzle                              | 28     | 4.767-072.0 |   |   |   |   |       |   | [  |







|                               | 1 |             |             |   |       | T  | $\top$ |
|-------------------------------|---|-------------|-------------|---|-------|--|--------|
|                               |   |             |             |   |       |  |        |
|                               |   |             |             |   |       |  |        |
|                               |   |             |             |   |       |  |        |
|                               |   | Order No.   | Nozzle size |   | Price | Description  |        |
| Power nozzle spray angle 15°  |   |             |             |   |       |  |        |
| Power nozzle spray angle 15°  | 1 | 2.883-392.0 | 70          |   |       | Fan jet nozzle with 15° spray angle suitable for stubborn  |        |
|                               | 2 | 2.883-390.0 | 55          |   |       | dirt.  |        |
|                               | 3 | 2.883-391.0 | 60          |   |       | Fan jet nozzle for stubborn dirt and stains.   |        |
|                               | 4 | 2.883-394.0 | 80          |   |       | Fan jet nozzle with 15° spray angle suitable for stubborn dirt.                                      |        |
| Power nozzle spray angle 25°  | • |             |             | • |       |  |        |
| Power nozzle spray angle 25°  | 5 | 2.883-404.0 | 70          |   |       | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. |        |
| Power nozzle, spray angle 25° | 6 | 2.883-401.0 | 55          |   |       |  |        |
| Power nozzle 25° spray angle  | 7 | 2.883-402.0 | 60          |   |       |  |        |
|                               | 8 | 2.883-406.0 | 80          |   |       |  |        |
| Power nozzle spray angle 40°  |   |             |             |   |       |  |        |
| Power nozzle spray angle 40°  | 9 | 2.884-526.0 | 75          |   |       | Power nozzle with a 40° spray angle and fan jet, suitable for  | r 🖂    |

<sup>☐</sup> Available accessories.



|                          |   | Order No.   |  |  | Price | Description |  |
|--------------------------|---|-------------|--|--|-------|-------------|--|
| Take off point equipment |   |             |  |  |       |             |  |
|                          | 1 | 4.763-927.0 |  |  |       |             |  |
|                          | 2 | 4.775-012.0 |  |  |       |             |  |

<sup>☐</sup> Available accessories.





|               |   | Order No.   | Flow rate |  | Price | Description |
|---------------|---|-------------|-----------|--|-------|-------------|
| Servo Control |   |             |           |  |       |             |
| Servo control | 1 | 4.775-471.0 | 1100 l/h  |  |       |             |
|               | 1 | 4.775-471.0 | 1100 l/h  |  |       |             |

<sup>☐</sup> Available accessories.















|  |        | Order No.   | ID    | Max. working pressure | Length | Price | Description  |  |
|--|--------|-------------|-------|-----------------------|--------|-------|--|--|
| Standard with unions on both sides   |        | <u>'</u>    |       |                       |        |       |  |  |
| High-pressure hose packaged  | 1      | 6.391-342.0 | ID 8  | 315 bar               | 10 m   |       |  |  |
| High-pressure hose, 15 m DN 8, 315 bar, including rotary coupling                  | 2      | 6.390-010.0 | ID 8  | 315 bar               | 15 m   |       | With rotary coupling, 2 x M 22 x 1.5   |  |
| High-pressure hose, 20 m DN 8,<br>315 bar, extension                               | 3      | 6.390-031.0 | ID 8  | 315 bar               | 20 m   |       | With M 22x1.5 union at both ends and anti-kink protection ID 8/155°C/315 bar   |  |
| High-pressure hose, 15 m DN 10, 220 bar, extension                                 | 4      | 6.390-023.0 | ID 10 | 220 bar               | 15 m   |       | 15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.   |  |
| Longlife 400 with unions on both si  | ides   |             |       |                       |        |       |  |  |
| High-pressure hose packaged  | 5      | 6.391-354.0 | ID 8  | 400 bar               | 10 m   |       |  |  |
| High-pressure hose Longlife 400,<br>20 m, DN 8, extension                          | 6      | 6.390-027.0 | ID 8  | 400 bar               | 20 m   |       | with rotary coupling, 2 x M 22 x 1.5   |  |
| Food industry version with unions  | on bot | h sides     |       |                       |        |       |  |  |
| High-pressure hose, 10 m ID 8,<br>suitable for food industry, extensi-<br>on piece | 7      | 6.389-479.0 | ID 8  | 250 bar               | 10 m   |       | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.                            |  |
| High-pressure hose, 20 m ID 8, suitable for food industry, extension piece         | 8      | 6.389-581.0 | ID 8  | 250 bar               | 20 m   |       | 20 m high-pressure hose (DN 8) with swivel coupling. Non-<br>discolouring outer layer for use in the food industry. Con-<br>nectors at both ends, M 22 x 1.5, with kink protection. NW<br>8/155°C/250 bar. |  |

<sup>☐</sup> Available accessories.







|  |   | Order No.   | Length |  | Price | Description   |  |
|--|---|-------------|--------|--|-------|---|--|
| Automatic, self-winding hose reels               |   |             |        |  |       |   |  |
| Hose reel, automatic, 20 m, stain-<br>less steel | 1 | 6.391-421.0 | 20 m   |  |       | Automatic stainless steel hose reel. With swivel holder.<br>Suitable for 20 m high-pressure hose. |  |
| Strahlrohe                                       |   |             |        |  |       |   |  |
| Spray lance, industrial type, black, 1050 mm     | 2 | 4.760-653.0 |        |  |       |   |  |

<sup>☐</sup> Available accessories.













|  |   |             | 1                     |         |  |       |   |
|--|---|-------------|-----------------------|---------|--|-------|---|
|  |   | Order No.   | Max. working pressure | Length  |  | Price | Description   |
| Rotating spray lances                    |   |             |                       |         |  |       |   |
| Rotatable lance, 600 mm, ergonomic       | 1 | 4.760-664.0 | 300 bar               | 600 mm  |  |       | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |
| 1050 mm lance, rotatable, ergonomic      | 2 | 4.760-660.0 | 300 bar               | 1050 mm |  |       | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |
| Lance 1550 mm, rotatable, ergo-<br>nomic | 3 | 4.760-661.0 | 300 bar               | 1550 mm |  |       | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |
| Lance 2050 mm, rotatable, ergo-<br>nomic | 4 | 4.760-662.0 | 300 bar               | 2050 mm |  |       | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |
| Lance for industrial use, grey           | 5 | 4.760-655.0 | 300 bar               | 1050 mm |  |       | 1050 mm grey, rotatable food-grade lance for use in the food industry. All parts coming into contact with water are food safe.  |
| Variable pressure spray lance            |   |             |                       |         |  |       |   |
| Variable pressure spray lance            | 6 | 4.760-362.0 |                       | 670 mm  |  |       | 670 mm variable pressure lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.    |
| Variable pressure lance                  | 7 | 4.760-230.0 |                       | 1040 mm |  |       | 1040 mm pressure adjustable lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application. |

<sup>☐</sup> Available accessories.