KARCHER



3 Service-friendly

HDS 13/20 De Tr1

The HDS 13/20 trailer operates at pressures of 200 bar and is the perfect solution for mobile, self-sufficient hot water cleaning at high pressure. Ideal not only for everyday cleaning in the municipal sector, but also for industry and construction.





1 Maximum efficiency

Highly efficient burner technology.

2 Simple operation

Safe and ample storage for protective gear, accessories and cleaning agents.

TECHNICAL DATA AND EQUIPMENT.

KARCHER



HDS 13/20 De Tr1

| Technical data | | |
|------------------------|-----------|---------------------|
| Order Number | | 1.524-952.2 |
| Engine manufacturer | | Yanmar |
| Fuel | | Diesel |
| Power rating | kW / hp | 19 / 26 / 19 / 26 |
| Flow rate | l/h | 900-1300 |
| Pressure | bar / MPa | 60-200 / 6-20 |
| | kg/h | 11,3 |
| Weight | kg | 950 |
| Dimensions (L x W x H) | mm | 3646 × 1747 × 1735 |
| | | |
| Equipment | | |
| Trigger gun | | EASY!Force Advanced |
| High-pressure hose | m | 30 |
| Spray lance | mm | 1050 |
| Power nozzle | | 1 |
| Servo Control | | |
| | | |

Included in delivery.


KARCHER





| | | Order Number | Order Number ID | Max. working | | | | | |
|--|-------|------------------|-----------------|--------------|--------|-------|---|--|--|
| | | Order Number | ID | pressure | Length | Price | Description | | |
| Standard with unions on both sides | | | | | | | | | |
| High-pressure hose, 15 m DN 10, 220 bar, extension | 1 | 6.110-042.0 | ID 10 | 220 bar | 15 m | | 15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar. | | |
| High-pressure hose, 20 m DN 10, 220 bar, extension | 2 | 6.110-043.0 | ID 10 | 220 bar | 20 m | | with union on both sides, M 22 x 1.5 with anti-kink protection. NW $10/155^{\circ}C/220$ bar | | |
| High-pressure hose, 25 m DN 10, extension, not rotatable | 3 | 6.110-044.0 | ID 10 | 220 bar | 25 m | | | | |
| Hose assembly premium DN12 21MPa 15m | 4 | 6.110-059.0 | ID 12 | 210 bar | 15 m | | High-pressure hose for water volumes greater than $1,800 \text{ J}$, h. With union on both sides. $2 \times M 22 \times 1.5$ with anti-kink | | |
| Hose assembly premium DN12 21MPa 40m | 5 | 6.110-060.0 | ID 12 | 210 bar | 40 m | | protection. | | |
| Longlife 400 with unions on both si | des | | | | | | | | |
| High-pressure hose Longlife 400, 20 m, DN 8, extension | 6 | 6.110-027.0 | ID 8 | 400 bar | 20 m | | with rotary coupling, 2 x M 22 x 1.5 | | |
| High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling | 7 | 6.110-029.0 | ID 8 | 400 bar | 15 m | | With rotary coupling, 2 x M 22 x 1.5 | | |
| High-pressure hose packaged | 8 | 6.110-038.0 | ID 8 | 400 bar | 10 m | | | | |
| High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling | 9 | 6.110-023.0 | ID 8 | 400 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 | | |
| Longlife food industry version with | unior | ns on both sides | | | | | | | |
| High pressure hose food DN 8 / 10 m | 10 | 6.110-053.0 | ID 8 | 400 bar | 10 m | | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5 | | |





KARCHER

ACCESSORIES FOR HDS 13/20 DE TR1 1.524-952.2

| | | | | 4 | 3 | 5 | 0 | |
|---|---|--------------|---------------|-------------|--------|---|-------|---|
| | | Order Number | Flow rate | Nozzle size | | | Price | Description |
| Hard Surface Cleaner FRV 30 | | 1 | | | | | | |
| Add-on kit hose attachment | 1 | 2.642-528.0 | | | | | | |
| Add-on kit dirt trap | 2 | 2.642-532.0 | | | | | | |
| Hard surface cleaner FR 30 ME | | | | 1 | | | 1 | |
| FR 30 ME surface cleaner | 3 | 2.111-013.0 | | | 300 mm | | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. |
| Hard Surface Cleaner FR 50 | | 1 | 1 | | | | | indostry. |
| FR 50 surface cleaner | 4 | 2.111-023.0 | | | 500 mm | | | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system. |
| Machine-specific nozzle kit for FR | | | | | | | | |
| Nozzle pack for hard surface cleaners (machine-specific) 1300 - 1,800 l/h | 5 | 2.640-781.0 | 1300-1800 l/h | | | | | Machine-specific nozzle kit Kärcher power nozzle for hard surface cleaners |
| Machine-specific nozzle kits for FR | v | | | | | | | |
| Nozzle pack 080 | 6 | 2.642-982.0 | | 80 | | | | |
| Hard surface cleaner FRV 30 Me | | | | | | | | |
| Suction hose FRV 30 me | 7 | | | | | | | |
| FRV 30 ME | 8 | 2.111-012.0 | | | | | | |
| Surface Cleaner FR 50 Me | 9 | 2.111-024.0 | | | | | | |
| □ Available accessories. ▲ E | | | 1 | I | 1 | | I | |

| 2 |) | | Ð | •:1==================================== | | 6 | | |
|--|----|----------------------------|---|---|---|-----------------|----------|--|
| 9 10 |) | | D | 12 | | () 13 | | |
| | | | | | | | | |
| | | Order Number | | | | | Price | Description |
| Nozzle union | | | | | | | | |
| Protection part TR only for replacement | 1 | 4.112-011.0 | | | | | | |
| Coupling parts | | <u> </u> | | | | | <u> </u> | |
| | 2 | 6.987-705.0 | | | | | | |
| Rotary coupling | | | | | | | 1 | |
| Rotary coupling | 3 | 4.111-021.0 | | | | | | Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection. |
| Coupling | | | | | | | | |
| Coupler -2xM22x1,5 | 4 | 4.111-037.0 | | | | | | Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m. |
| Connector | | | | | | | | |
| Nozzle connector/screw connector | 5 | 4.111-022.0 | | | | | | Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. |
| | 6 | 4.111-038.0 | | | | | | |
| Adapter EASY!Lock | - | 4 1 1 1 0 20 0 | 1 | | 1 | | 1 | |
| Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG | 7 | 4.111-029.0 4.111-030.0 | | | + | | | - |
| Adapter 3 M22IG-TR22AG | 8 | 4.111-030.0 | | | | | | - |
| Adapter M22 - Swivel | 10 | 4.111-032.0 | | | | | | M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection. |
| Adapter 5 TR22IG-M22AG | 11 | 4.111-033.0 | | | | | | _ |
| Adapter 6 TR22IG-M22AG | 12 | 4.111-034.0 | | | | | | |
| Adapter 7 M18IG-TR20AG | 13 | 4.111-035.0 | | | | | | |
| Adapter 8 TR20IG-M18AG | 14 | 4.111-036.0 | | | | | | |



| | | Order Number | Nozzle size | | Price | Description |
|---------------------------------------|---|--------------|-------------|--|-------|--|
| HP nozzle spray angle 0° | | | | | | · · · · · · |
| High-pressure nozzle spray angle °0 | 1 | 2.113-037.0 | 75 | | | High-pressure nozzle with powerful jet for extremely stubborn dirt. |
| Power nozzle spray angle 15° | | | | | | |
| Power nozzle spray angle 15° | 2 | 2.113-049.0 | 70 | | | Fan jet nozzle with 15° spray angle suitable for stubborn dirt. |
| Power nozzle spray angle 25° | | | | | | · · · · |
| Power nozzle TR for replacement 25070 | 3 | 2.113-028.0 | 70 | | | |
| Power nozzle spray angle 40° | | | | | | · |
| Power nozzle spray angle 40° | 4 | 2.113-056.0 | 75 | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. |



| | | Order Number | Flow rate | | Price | Description | |
|---|--------|--------------|-----------|---|-------|--|--|
| Trigger guns | | | | 1 | I | | |
| Extended easy press trigger gun | 1 | 4.118-005.0 | | | | Extended easy press high-pressure trigger gun for high- pressure hoses with rotating connector. | |
| Servo Control | | | | | | | |
| Servo control | 2 | 4.118-009.0 | 1100 l/h | | | | |
| Quick connect | | | | | | | |
| Quick-fitting pipe union coupler trapezo | 3 | 2.115-000.0 | | | | | |
| Quick-fitting pipe union plug nipple tra | 4 | 2.115-001.0 | | | | | |
| | xtensi | on hose. | - | | · | · | |



| | | Order Number | Nozzle size | | Price | Description |
|---|--------|--------------|-------------|--|-------|---|
| Wet blasting attachment (without r | ozzle) | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.115-000.0 | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.115-006.0 | | | | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. |
| Nozzle pack for wet blasting attach | ment | | | | · | |
| Nozzle pack TR wet jet set 0070 | 3 | 2.112-027.0 | 70 | | | |
| Boron carbide nozzle | | | | | | |
| Boron carbide nozzle, for machines as of 1000 l/h | 4 | 6.415-083.0 | 8 mm | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. |



| | | Order Number | Max. working pressure | Nozzle size | | Price | Description | |
|---|--------|--------------|-----------------------|-------------|-------|-------|--|---|
| Pipe cleaning hose, ID 6 | | | | L | | | | _ |
| Hose assembly TR pipe cleaning DN6 max.2 | 1 | 6.110-046.0 | 250 bar | | | | | |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 2 | 6.110-008.0 | 250 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). | |
| Hose assembly TR pipe cleaning DN6 max.2 | 3 | 6.110-047.0 | 250 bar | | | | | |
| Pipe cleaning nozzle | | | | | | · | | |
| Nozzle pipe cleaning size 80 | 4 | 5.763-087.0 | | 80 | 25 mm | | Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle. | |
| □ Available accessories. ▲ E | xtensi | ion hose. | | | | | | |



| | | | Max. working | | | | | |
|--|---|--------------|--------------|-------------|--|-------|--|--|
| | | Order Number | pressure | Nozzle size | | Price | Description | |
| Dirt blaster, large | | | | | | | | |
| Dirt blaster - without changeover function | 1 | 4.114-030.0 | 300 bar | 70 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | |



| | | Order Number | Flow rate | | Price | Description |
|---|---|--------------|---------------|--|-------|--|
| Cup foam lance | | | L | | | |
| Packing complete for 6.394-968.0 | 1 | 2.112-017.0 | | | | |
| Tank 1L | 2 | 6.414-954.0 | | | | |
| Inno Foam Set | | | | | | |
| Inno foam kit | 3 | 2.112-008.0 | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. |
| Easy Foam Set | | | | | | |
| Easy foam set | 4 | 2.112-011.0 | | | | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. |
| Nozzle kits for Inno/Easy Foam Set | | | | | | |
| Nozzle kit 110 Inno/Easy set 1000 - 1300 I/h | 5 | 2.111-020.0 | 1000-1300 l/h | | | Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance. |
| Foam nozzle mounting kit | | | | | | |
| Foam nozzle kit | 6 | 2.112-013.0 | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. |

KARCHER
















| | | Order Number | Length | | Price | Description | |
|--|---|--------------|--------|--|-------|--|--|
| Automatic, self-winding hose reels | | | | | | | |
| Add-on kit hose reel plastics | 1 | 6.392-074.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | |
| Add-on kit hose reel | 2 | 6.392-083.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | |
| Hose reel, automatic, 20 m, painted | 3 | 6.392-106.0 | 20 m | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | |
| | 4 | 6.392-105.0 | 20 m | | | | |
| Hose reel, automatic, 20 m, stainless steel | 5 | 6.392-076.0 | 20 m | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | |
| ABS hose reel stainless steel | 6 | 6.392-122.0 | 20 m | | | High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple. | |
| Swivel holder | 7 | 2.639-931.0 | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel. | |
| ABS wall fastening stainless steel | 8 | 2.641-867.0 | | | | Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose. | |



| | | Order Number | Flow rate | Water feed temperature | Length | Length | Price | Description | |
|------------------------------------|---|--------------|-----------|---------------------------|--------|--------|-------|--|--|
| Solar cleaning - telescopic lances | | | | | | | | | |
| Telescopic rod complete 14m | 1 | 4.110-002.0 | | max. 60 °C | | | | Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick- release couplings for easy extension and retraction. | |
| Telescopic rod complete 10m CFK | 2 | 4.110-007.0 | | max. 60 °C | | | | | |
| Telescopic rod complete 10m | 3 | 4.110-003.0 | | max. 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction. | |
| iSolar TL 7 H (without hose) | 4 | 4.110-004.0 | | max. 60 °C | | | | Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction. | |
| Hose solar | 5 | 6.392-978.0 | | max. 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |
| | 6 | 6.392-977.0 | | max. 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |
| | 7 | 6.392-976.0 | | max. 155 °C | | | | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod | |



| | | Order Number | Max. working pressure | Length | Р | Price | Description | |
|---|---------|--------------|-----------------------|---------|-------|-------|--|----|
| Rotating spray lances | | | | | | | | |
| Lance 250 mm, non-rotatable | 1 | 4.112-027.0 | 300 bar | 250 mm | | | | |
| 550 mm lance, non-rotatable | 2 | 4.112-024.0 | 300 bar | 400 mm | | | | |
| Rotatable lance, 600 mm, ergonomic | 3 | 4.112-007.0 | 300 bar | 600 mm | | | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Lance 850 mm, rotatable, ergonomic | 4 | 4.112-006.0 | 300 bar | 840 mm | | | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| 1050 mm lance, rotatable, ergonomic | 5 | 4.112-000.0 | 300 bar | 1050 mm | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Lance 1550 mm, rotatable, ergonomic | 6 | 4.112-018.0 | 300 bar | 1550 mm | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Lance 2050 mm, rotatable, ergonomic | 7 | 4.112-021.0 | 300 bar | 2050 mm | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Double lance | | | | | | | | |
| Double lance 960 mm | 8 | 6.394-665.0 | 310 bar | 960 mm | | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | |
| Angular spray lance | | | | | | | | |
| WC and gutter lance | 9 | 4.112-029.0 | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | |
| Flexible spray lance | | | | | | | | |
| Flexible lance 1050 mm | 10 | 4.112-035.0 | 210 bar | 1050 mm | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | |
| Telescopic spray lance | 1 | | | 1 | 1 | | | 1- |
| Telescopic jet pipe | 11 | | 225 bar | 5400 mm | | | | |
| Restraint belt for telescopic jet pipe | 12 | 6.373-987.0 | | | | | Convenient strap for relief when working with the telescopi spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. | |
| Gutter cleaner | | | | | | | | |
| Gutter cleaning lance | 13 | 2.112-015.0 | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | |
| Undercarriage spray lance | | | | | | | | |
| Underbody lance | 14 | 4.112-032.0 | | 700 mm | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | |
| Additional handle | | | | 1 | | | | |
| | | 4.321-380.0 | | | | | | |
| □ Available accessories. ▲ | Extensi | on hose. | | | | | | |

 $\hfill\square$ Available accessories. $\hfill A$ Extension hose.



| | | Order Number | Flow rate | | Price | Description | |
|-----------------------------------|--------|--------------|--------------|--|-------|---|--|
| Push-on washing brush | | | | | | | |
| Push-on wash brush, M 18 x 1.5 $$ | 1 | 4.113-001.0 | | | | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6. | |
| Rotating washing brush | | | | | | | |
| | 2 | 4.113-002.0 | 800-1300 l/h | | | | |
| | 3 | 4.113-005.0 | 800-1300 l/h | | | | |
| □ Available accessories. ▲ E | xtensi | ion hose. | | | | | |



| | | Order Number | Length | Diameter | | Price | Description | |
|-------------------------------------|---|--------------|--------|-----------|--|-------|---|---|
| Suction filter | | order Homber | Lengen | Braineter | | Thee | | 1 |
| Water filter | 1 | 6.414-956.0 | | | | | | |
| Suction filter with check valve | 2 | 4.730-012.0 | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | |
| Fine-mesh water filter | | | | | | | | |
| Fine-mesh water filter with adapter | 3 | 4.730-102.0 | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | |