

ILF – Series Inline Filter Cartridges

AXEON ILF – Series Inline Filter Cartridges utilize a sleek encapsulated design that fits most standard water lines that feature coconut shell carbon and sediment filtration. The carbon used in these cartridges has been specifically developed to reduce sediments, color, soluble organic compounds (SOC) and volatile organic compounds (VOC).

AXEON ILF – Series Inline Filter Cartridges provide solutions for a variety of applications that need the removal of bad taste and odor. These cartridges act as an excellent post-treatment for reverse osmosis as well as being effective for applications in ice, coffee making and refrigeration.

Benefits

- Chlorine, Bad Taste and Odor Reduction
- Design Eliminates Channeling, By-Pass and Reduces Release of Carbon Fines
- Tested and Verified Performance by Independent Laboratory

Operating Limits

- Service Life (gal / l): 2,500 / 9,500 or est. 6 months
- Maximum Flow Rate (gpm / lpm): 0.50 / 1.9
- Maximum Operating Pressure (psi / bar): 100 / 6.89
- Minimum Operating Temperature (°F / °C): 35 / 2
- Maximum Operating Temperature (°F / °C): 100 / 38

Applications

- Icemakers
- Reverse Osmosis Systems
- Coffee Makers
- Refrigerators



Tested and Certified by NSF International against ANSI/NSF Standard 42 for material requirements only.



Product Specifications

Part Number	Model Number	Diameter (in / mm)	Length (in / mm)	Ports FNPT (in)	Case Quantity	Box Dimensions (in / mm)	Approximate Weight by Case (lbs.)
200654	ILF – 2010 – 14 – GAC	2.00 / 50.80	10.00 / 254.0	1/4	25	10.75 X 10.75 X 10.75 / 273.0 X 273.0 X 273.0	15
200618	ILF – 2010 – 14 – SED	2.00 / 50.80	10.00 / 254.0	1/4	25	10.75 X 10.75 X 10.75 / 273.0 X 273.0 X 273.0	12

Know Higher Standards™

