## **G95 - SHORE LED BULB**

## tala


## 6W | 600 lm | 2000-3000K

G95-6W-2000-3000K-E26-MW-120V

Shore WoD 2000K to 3000K E27 Matte Porcelain US LED Bulb


Tala's G95 for Shore offers highly impressive technical qualities alongside a refined visual aesthetic. A design feature to be celebrated, the bulb is characterised by its Dim to Warm and flicker free behaviour, offering warm and ambient light when dimmed down from 100-0%. Fitted with a standard E26 base cap.





C1/C180 C90/C270

IES/LDT photometry files and product photography available on request



## PHYSICAL

TM30 - Rf

Bulb diameter:	3 3/4in
Bulb length:	5 4/8in
Glass shape:	G95
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	70g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54
ELECTRICAL	
Power:	6W
Current:	0.06A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	100 lm/W
Lifetime:	15,000 hrs
ILLUMINATION	
CCT:	2000-3000K
Lumens:	600 lm
Incandescent equiv.:	45W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	101



DIMMING	Dimmable 0-100% Recommended dimmer: Lutron Diva DVELV-300P (For a full list of recommended and compatible dimmers see website)		Tala Energy Ltd. 25b Vyner Street, London, E2 9DG, United Kingdom
			Tala North America Inc., 909 Rose Avenue, Suite 660 North Bethesda, MD 20852, United States
LOGISTICAL	Unit Packaging PC/Ctn: 1	Outer Carton PC/Ctn: 10	us.tala.co.uk   hello@tala.co.uk   +1 (240) 724-8111
	Gross weight: 125 g L 3 7/8 x W 3 7/8 x H 5 3/4 in	Gross weight: 1.22 kg L 20 4/8 x W 4 3/8 x H 12 2/8 iı	n Specification subject to change without notice. Refer to our website for the most
WARRANTY	2 years		recent product documentation. Tala designs in the EU/UK are protected by
EAN	5060915715456		registered and or unregistered design rights

95