

299752Q

Aluminium Handle, waterfed,
Q-coupling (Q), Ø31 mm,
1920 mm, Black



A professional water-fed handle with an insulated sleeve for a comfortable grip and a quick-release hose connector. Maximum water pressure, 6 bars.

Technical Data

Item Number	299752Q
Material	Anodised Aluminium Polypropylene Chromium-plated brass
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
SCIP number	e49c50b5-7653-429c- b8f3-803d37b5fefc
Use of phthalates and bisphenol A	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	620 Pcs.
Quantity Per Layer (Pallet)	0 Pcs.
Box Length	1955 mm
Box Width	175 mm
Box Height	75 mm
Product Diameter	31 mm
Length/Depth	1920 mm
Width	31 mm
Height	31 mm
Net Weight	0,66 kg
Weight cardboard	0,0425 kg
Tare total	0,0425 kg
Gross Weight	0,7 kg
Cubik metre	0,001845 M3
Max. bars pressure	6 Bar
Max usage temperature (non food contact)	50 °C
Min. pH-value in usage concentration	4 pH
Max. pH-value in Usage Concentration	11 pH
GTIN-13 Number	5705022997028
GTIN-14 Number (Box quantity)	15705022997025
Customs Tariff No.	76082020
Country of origin	Denmark

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.