

297152Q



Aluminium telescopic
waterfed handle w/Q
coupling, 1060 - 1600 mm,
Ø32 mm, Black



Professional telescopic water-fed handle with insulating sleeve for a comfortable grip with quick release hose connector. This handle can be used up to a pressure of 6 bar.

Technical Data

Item Number	297152Q
Material	Anodised Aluminium Polypropylene Chromium-plated brass
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
SCIP number	e49c50b5-7653-429c- b8f3-803d37b5fefc
Use of phthalates and bisphenol A	No
Box Quantity	5 Pcs.
Quantity per Pallet (80 x 120 x 200 cm)	580 Pcs.
Quantity Per Layer (Pallet)	25 Pcs.
Box Length	1110 mm
Box Width	140 mm
Box Height	85 mm
Product Diameter	32 mm
Length/Depth	1060 mm
Width	32 mm
Height	32 mm
Max. Length	1600 mm
Net Weight	0,63 kg
Weight cardboard	0,06 kg
Tare total	0,06 kg
Gross Weight	0,69 kg
Cubik metre	0,001085 M3
Max. bars pressure	6 Bar
Max usage temperature (non food contact)	50 °C
Min. pH-value in usage concentration	4 pH
Max. pH-value in Usage Concentration	11 pH
GTIN-13 Number	5705022971028
GTIN-14 Number (Box quantity)	15705022971025
Customs Tariff No.	76082020
Country of origin	Denmark

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.