

S P E C I F I C A T I O N S

TA-6500 | ConferenceHub™

4-Port Conference Room Networking Switch



The ConferenceHub™ is a multi-connection HSIA point/networking hub, perfect for meeting or conference rooms. The unit acts as a hub and switch, allowing up to 4 computers to access 1 local network (LAN)/Internet connection. Designed for easy installation and high performance where users need to access the network, without cable clutter.

- Plug-and-play connection multi-port networking switch for LAN conference
- Allows for multiple, concurrent use of the network from one point
- Enhance the look of conference or meeting rooms & increase productivity
- Retractable cable function eliminates cable clutter

 **teleadapt**
Keeping Your World Connected™

ConferenceHub™

TA-6500 | ConferenceHub™

4-Port Conference Room Networking Switch



Features & Benefits

- 4 x 2m (6ft) CAT5e LAN (10/100Mbps) retractable cords with Ethernet connectors
- Auto-learning of networking configurations
- Daisy-chain multiple units for more connection points
- Status lights informs users when the network is on-line and available for use
- Full-duplex 200Mbps bandwidth on each port
- IEEE 802.3x flow control for full-duplex communication
- Plug-and-play connections in all environments

Technical Specifications

- Standards: IEEE 802.3 10BASE-T, IEEE 802.3u, 100BASE-TX
- 4 CAT5e (10/100Mbps) cords at extended length of 2M (6ft)
- Network Transmission Media: 10Base-T Cat. 3,4,5 UTP/STP
100BASE-TX Cat.5 UTP/STP
- Power Adapter: DC 7.5V
- Network Status Monitoring LEDs perport: LINK/ACT, 10/100M
- FDX System: POWER
- BUFFER MEMORY: 768KByte per device
- MAC Address: Up to 2K per device
- Power Consumption: 4 port : 2 watts (Maximum)
- Operating Temperature: 0 - 55 Celsius
- Humidity: 10% - 90% RH



TA-6500-A01-UK - With UK power lead

TA-6500-A01-EU - With EU power lead

 **teleadapt**
Keeping Your World Connected™

web: www.teleadapt.com

email: info@teleadapt.com

ConferenceHub™