

Only
39 lbs!



ROLAIR[®] STANDARD FEATURES

- PUMP:** ROLAIR[®] Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.
- MOTOR:** 1.5 HP, 3400 RPM, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial-Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
FC1500HS3	1.5	1	7.8	4.0	2.5	20 X 9 X 18	43

STANDARD EQUIPMENT

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Compact/Lightweight Tank Design
- Tank Pressure Gauge
- Safety Relief Valve
- Replaceable Filter Cartridge
- Initial 6 oz. Oil Fill Included
- 13.5 Amp Motor

