

VORONOI III

5W | 250 lm | 2200K

VORN-III-5W-2200K-E26-T-120V-02

Voronoi III 5W 2200K E26 Tinted US LED Bulb, V.2


tala®

The Voronoi III bulb by Tala is noted for its oversized form and dramatic light output. The exposed internal filament mirrors the Fibonacci sequence, wrapping around a central glass column, and the unique glass shape catches the eye and the imagination. Fitted with E26 base cap.



PHYSICAL

Bulb diameter:	7 5/8in
Bulb length:	13 3/8in
Glass shape:	A52*
Base:	E26
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	355g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54




ELECTRICAL

Power:	5W
Current:	0.04A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	50 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	250 lm
Incandescent equiv.:	25W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 2
Gross weight: 580	Gross weight: TBC
L 9 7/8 x W 9 7/8 x H 15 6/8in	L TBC x W TBC x H TBCin

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060400159673