

Zeolite

Pre / Post Treatment Systems

Standard Features



- Fleck® Timer Control Valve
 - Easy to Program SXT Electronics
 - Pre-Treat Lockout Contacts
 - 48 Hour Power Backup
 - Day-of-the-Week Controls
 - Regeneration Can Be Triggered Immediately
- Zeolite Media NSF 61 Certified
- Structural® Heavy Duty Fiberglass Tank
- Heavy Duty Riser Pipe with Upper and Lower Screens

Specifications

PART NUMBER	VALVE	VOLTAGE	DLFC	CONNECTION (IN)	TANK SIZE (IN)	CUBIC (FT)	TANK (QTY)	BACKWASH RATE (GPM)	RECOMMENDED SERVICE FLOW (GPM)	SHIPPING WEIGHT (LBS)	SYSTEM ASSEMBLED
200159	5600SXT	110	7	3/4 MNPT	9 x 48	1	1	7.0	1.3 – 3.0	90	Assembled
203205	5600SXT	220	7	3/4 MNPT	9 x 48	1	1	7.0	1.3 – 3.0	90	Assembled
200160	5600SXT	110	7	3/4 MNPT	10 x 54	1.5	1	7.0	1.6 – 4.5	105	Assembled
203206	5600SXT	220	7	3/4 MNPT	10 x 54	1.5	1	7.0	1.6 – 4.5	105	Assembled
210060	5810SXT	110	15	1 MNPT	12 x 52	2	1	15.0	2.3 – 6.0	145	Assembled
210059	5810SXT	220	15	1 MNPT	12 x 52	2	1	15.0	2.3 – 6.0	145	Assembled
210061	5810SXT	110	20	1 MNPT	13 x 54	2.5	1	20.0	2.8 – 7.5	160	Assembled
210062	5810SXT	220	20	1 MNPT	13 x 54	2.5	1	20.0	2.8 – 7.5	160	Assembled
210063	5810 SXT	110	20	1 MNPT	14 x 65	3	1	20.0	3.2 – 9.0	200	Non-Assembled
210064	5810SXT	220	20	1 MNPT	14 x 65	3	1	20.0	3.2 – 9.0	200	Non-Assembled
210065	5810SXT	110	20	1 MNPT	16 x 65	4	1	20.0	4.2 – 12.0	265	Non-Assembled
210066	5810SXT	220	20	1 MNPT	16 x 65	4	1	20.0	4.2 – 12.0	265	Non-Assembled
203348	2850SSXT	110	25	1 1/2 MNPT	21 x 62	6	1	25.0	7.0 – 40.0	375	Non-Assembled
203352	2850SSXT	220	25	1 1/2 MNPT	21 x 62	6	1	25.0	7.0 – 40.0	375	Non-Assembled
203349	2850SSXT	110	45	1 1/2 MNPT	24 x 60	10	1	45.0	10.0 – 47.0	635	Non-Assembled
203353	2850SSXT	220	45	1 1/2 MNPT	24 x 60	10	1	45.0	10.0 – 47.0	635	Non-Assembled
203350	2850SSXT	110	45	1 1/2 MNPT	24 x 72	10	1	45.0	10.0 – 47.0	635	Non-Assembled
203354	2850SSXT	220	45	1 1/2 MNPT	24 x 72	10	1	45.0	10.0 – 47.0	635	Non-Assembled