



ThermoWorks

Smoke X2™

2-Channel Wireless BBQ Alarm Thermometer 6,562 Feet (1.24 Miles) Transmission Range

Large Dashboard Display

The dashboard-like display shows the current temperature, high and low alarm settings, max/min readings, and alarm state for both channels—plus volume level and battery state, for the whole unit.

Smoke X2 Receiver

Updates every 30 seconds with readings from both channels. Also shows current temperatures, high/low alarm settings, and if the alarm is on or off.



Two Probes & Probe Identifiers

Includes a Pro-Series® High-Temp Cooking Probe and a Pro-Series High-Temp Air Probe. Works with all other Pro-Series probes. Probe identifiers allow you to quickly and easily identify which probe is plugged into each channel.

Backlight

Turns on backlight for 20 seconds.

Audible Alarm

Audible alarm adjustable in four steps up to 90dB for Smoke X2 and 75dB for Smoke X2 Receiver.



Optional Billows™ Compatibility

Smoke X2 will allow you to control your smoker temperatures over an entire cook with Billows.



Everyone Else



ThermoWorks Smoke X

Transmission Range

Range is an incredible 6,562 feet line-of-sight which gives you the freedom to keep track of your cook at a greater distance and signal strength to penetrate walls and obstacles.



User Calibration

New from the factory, your Smoke X2 will read within $\pm 1.8^\circ\text{F}$ even after changing probes so you should never really need to use the CAL function. However, you can fine-tune the calibration for accuracy better than $\pm 1^\circ\text{F}$ on each channel.

Wireless Pairing

From the factory, Smoke X2 and Smoke X2 Receiver are paired and ready to use. Access the sync mode to sync multiple Smoke X2 Receivers.