

supamag[®] : PLAIN ISOTROPIC MAGNETIC SHEET



Base material, to which vinyl, adhesive or print can be applied

- Manufacturing process: calendered
- Material composition: 90% high grade ferrite powder, 10% synthetic binder, free of PVC and phthalates
- Adhesive: N/A
- Magnetisation: one face only, UV coated
- Pole pitch: 1.5mm to 2.5mm (travelling down the length of the roll)
- Density: 3.6g/cm³
- Colour: dark brown
- Hardness: (Shore-D) 33±5
- Working Face: the UV coated face
- Magnetic stability: immune to magnetic damage in normal use
- Working Temperature: -10°C to 60°C above which performance will reduce
- Storage Temperature: between 10°C & 40°C
- Compliance: **supamag**[®] sheet conforms to European toy safety standard EN71, part 3, REACH & RoHS approved
- Packaging: rolls supplied in cartons (wound on a 3" core). Cut sheets will be in cartons or on pallets



MORE INFORMATION

www.anchormagnets.com/pages/supamag-superior-magnetic-sheet

Disclaimer:

Published technical information concerning our products is based upon research, which, to the best of our company's knowledge & belief, is accurate & reliable.

Whilst the guidelines above will assist the purchaser in considering the suitability & performance of the product for each intended use, it remains the user's responsibility to satisfy themselves as to the suitability of such information for each particular use.

Therefore, Anchor Magnets Ltd & Anchor Magnets Europe, accepts no liability in the event of improper use or processing beyond our guidelines.