

G95 - SHORE LED BULB

tala®

6W | 550 lm | 2000-3000K

G95-6W-2000-3000K-E26-MW-120V


Shore WoD 2000K to 3000K E26 Matte Porcelain US LED Bulb

Tala's G95 for Shore offers highly impressive technical qualities alongside a refined visual aesthetic. A design feature to be celebrated, the bulb is characterised by its Dim to Warm and flicker free behaviour, offering warm and ambient light when dimmed down from 100-0%. Fitted with a standard E26 base cap.




PHYSICAL

Bulb diameter:	3 3/4in
Bulb length:	5 1/2in
Glass shape:	G95
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	70g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— CIE180
— CIE129

IES/LDT photometry files and product photography available on request



ELECTRICAL

Power:	6W
Current:	0.06A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	92 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2000-3000K
Lumens:	550 lm
Incandescent equiv.:	45W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	72
TM30 - Rg	100
TM30 - Rf	91



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 125 g	Gross weight: 1.22 kg
L 3 7/8 x W 3 7/8 x H 5 3/4 in	L 20 4/8 x W 4 3/8 x H 12 2/8 in

Tala North America Inc. C/O LH Frishkoff & Company
546 5th Avenue, FL 9, New York NY 10036, USA

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060915715456