

Activated Carbon

Pre / Post Treatment Systems

Standard Features



- Fleck® Timer Control Valve
 - Easy to Program SXT Electronics
 - Pre-Treat Lockout Contacts
 - 48 Hour Power Backup
 - Day-of-the-Week Controls
 - Regeneration Can Be Triggered Immediately
- Structural® Heavy Duty Fiberglass Tank
- Heavy Duty Riser Pipe with Upper and Lower Screens
- Carbon Media NSF 61 Certified

Specifications

PART NUMBER	VALVE	VOLTAGE	DLFC	CONNECTION (IN)	TANK SIZE (IN)	CUBIC (FT)	TANK (QTY)	BACKWASH RATE (GPM)	RECOMMENDED SERVICE FLOW (GPM)	SHIPPING WEIGHT (LBS)	SYSTEM ASSEMBLED
200117	5600SXT	110	4	3/4 MNPT	9 x 48	1	1	4.0	1.3 – 3.0	90	Assembled
203194	5600SXT	220	4	3/4 MNPT	9 x 48	1	1	4.0	1.3 – 3.0	90	Assembled
200118	5600SXT	110	6	3/4 MNPT	10 x 54	1.5	1	6.0	1.6 – 4.5	105	Assembled
203195	5600SXT	220	6	3/4 MNPT	10 x 54	1.5	1	6.0	1.6 – 4.5	105	Assembled
210035	5810SXT	110	8	1 MNPT	12 x 52	2	1	8.0	2.3 – 6.0	145	Assembled
210036	5810SXT	220	8	1 MNPT	12 x 52	2	1	8.0	2.3 – 6.0	145	Assembled
210037	5810SXT	110	9	1 MNPT	13 x 54	2.5	1	9.0	2.8 – 7.5	160	Assembled
210038	5810SXT	220	9	1 MNPT	13 x 54	2.5	1	9.0	2.8 – 7.5	160	Assembled
210039	5810SXT	110	12	1 MNPT	14 x 65	3	1	12.0	3.2 – 9.0	200	Non-Assembled
210040	5810SXT	220	12	1 MNPT	14 x 65	3	1	12.0	3.2 – 9.0	200	Non-Assembled
210041	5810SXT	110	15	1 MNPT	16 x 65	4	1	15.0	4.2 – 12.0	265	Non-Assembled
210042	5810SXT	220	15	1 MNPT	16 x 65	4	1	15.0	4.2 – 12.0	265	Non-Assembled
200129	2850SNXT	110	25	1 1/2 MNPT	21 x 62	6	1	25.0	7.0 – 18.0	375	Non-Assembled
203167	2850SNXT	220	25	1 1/2 MNPT	21 x 62	6	1	25.0	7.0 – 18.0	375	Non-Assembled
200130	2850SNXT	110	30	1 1/2 MNPT	24 x 60	8	1	30.0	10.0 – 24.0	550	Non-Assembled
203168	2850SNXT	220	30	1 1/2 MNPT	24 x 60	8	1	30.0	10.0 – 24.0	550	Non-Assembled
200131	2850SNXT	110	35	1 1/2 MNPT	24 x 72	10	1	35.0	10.0 – 30.0	635	Non-Assembled
203169	2850SNXT	220	35	1 1/2 MNPT	24 x 72	10	1	35.0	10.0 – 30.0	635	Non-Assembled