

Installation Instructions & Warranty Information SK105 ~ 1975-1981 Chevrolet Camaro/Firebird LS Engine Swap Motor Mount Brackets



PerTronix[®] thanks you for choosing **DOUG'S HEADERS**, the best fitting, highest quality Header and Engine Swap products on the market. To realize the full potential of our good fit, please read and understand these instructions completely prior to starting work.

Check to make sure you received the proper parts for your application against the parts list in these instructions. If you are unsure you have received the proper parts, please call PerTronix before you start work.

Be sure to work safe! Whenever you work under the vehicle be sure that it is located on level, solid ground and is supported by adequate safety stands! Remember: Hot asphalt will not support most jack stands!

WARNING:

This product can expose you to chemicals including Lead, Nickel, Cadmium and Chromium which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Rev. 2 9-22-21 DSL

NOTE: Read Before Starting Installation

- 1. Doug's motor mount kit SK105 is designed to be used exclusively with Doug's transmission crossmember SKC104. Use of any other brand of crossmember will not necessarily fit and driveline angles will be incorrect causing vibrations.
- 2. Doug's Oil Pan #SKOP100 or a 98-02 Camaro oil pan is required to clear the frame crossmember.
- 3. You will need New Clam Shell style motor mounts such as Anchor 2292 or Energy Suspension inserts #3.1116 or equivalent. Firebirds will require drilling two holes in the crossmember t use the Chevrolet mounts.
- 4. Use of these mounts will allow LS engines with 4L60/4L65/4L70/4L75 and F-Body style T56 trans to be installed without cutting the floor or firewall (other than for shifter location). T56 Magnum transmissions may require floor modifications.
- 5. Doug's offers both long and mid length headers (D3352 and D3353) as well as complete exhaust systems (DES104). Alternatively, Patriot Cast Iron manifolds will also work with this swap (H8097).

Additional Tips for this swap

- Use of F-Body, Corvette, and GTO accessory drives will work with the following exceptions:
- The plastic cover on the rear of the F-Body alternator will need to be removed. GTO Alternators will not work.
- Corvette Power Steering pumps and pulley are generally too large to clear the upper control arm and should be swapped for F-Body or other smaller pump/pulley combination.
- 1970-74 models will need to change the pitman arm to the 79 Trans Am offset pitman arm, center link, and tie rod ends if using the low mount F-Body alternator.
- Low mount A/C Compressors will not work with this installation. Aftermarket upper right-side mounted compressor mount such as the Sanden 20-134 will be necessary.

INSTALLATION

- 1. Make sure that all the parts are in the kit before starting. If you have any questions contact Doug's Tech Department at 909 599-5955.
- 2. Camaro applications: Remove the original clam shell motor mounts from the crossmember and clean the mounting area. We recommend painting if the area is rusty. Bolt the new motor mounts in place
- **3. Firebird** applications: remove the Pontiac motor mounts from the crossmember and clean the mounting area. We recommend painting if the area is rusty. Bolt the new motor mounts in place using the replacement clam shell mounts. Bolt the mounts to the crossmember using the TOP two holes through the matching holes in the crossmember from the stock engine mounts that you removed from the crossmember. Mark the location of the lower Rearward hole on the crossmember and drill to 25/64".
- 4. NOTE: The clamshell mounts have a wider pattern on one end, this is the Top.
- **5. ALL Applications**; Bolt the New Clam Shell mounts to the crossmember using the original 3/8" bolts and flange nuts.
- 6. Bolt the Doug's Motor Mount Brackets to the engine using the supplied 10mm bolts and flat washers - Red Loctite is Recommended. The "ears" on the mounts goes towards the front and the shorter ears are the Passenger side.
- 7. Lower the engine into the engine bay, support the rear of the transmission if attached, and secure the Doug's motor mount brackets to the clam shell mounts using the supplied 12mm bolts, flat washers, lock washers, and nuts.
- 8. Proceed with the installation of the appropriate Doug's Transmission Crossmember to complete the installation.

1

8

2

2

Parts	List	
1	Left Side	e mo

- Left Side motor mount bracket M10-1.5 x 30mm Hex Bolt
- 2 M12-1.75 x 140MM Bolt
- 2 M12-1.75 X 140MM B 4 M12 Flat Washer
 - M12 Flat Washer

- Right Side motor mount bracket
- M10 Flat Washer
- M12-1.75 Hex Nut
- M12 Lock Washer



This product is designed for swapping a non-original engine into a vehicle that did not offer it. Laws vary by state regarding emissions regulations for engine swaps. This product is Illegal for Street or Off Highway use on any 1975 or newer vehicle originally equipped with a catalytic converter and may further be illegal depending on state or federal engine swap emissions laws regardless of vehicle year and would therefore only be legal for Closed Course Competition use. *PerTronix Performance Brands* 2021

DOUG'S HEADERS LIMITED WARRANTY

All Doug's Headers and Exhaust products are guaranteed, to the original purchaser, to be free of defects in material and workmanship for one year from date of purchase. This warranty covers the replacement or repair of the product and does not cover the cost of removal and installation, customer applied coatings, or Any discoloration or corrosion of finished surfaces.

Damage or product failure resulting from collision, improper installation, off road use, road hazards, the use of exhaust insulating wrap, or rust occurring after installation is not covered by the warranty. This warranty extends only to the original purchaser.

Should a part be deemed defective, it should be returned to the original selling retailer and must be accompanied by the sales receipt. If there is no retailer in your area, contact PerTronix direct for a return authorization and return the part prepaid to the factory for inspection. PerTronix reserves the right to replace or repair the alleged defective part and return the part freight collect.



A PerTronix Performance Brand ~ <u>www.pertronixbrands.com</u> ~ 909 599-5955