

GU10

7W | 550 lm | 2700K

GU10-7W-2700K-36DEG-120V

GU10 7W 2700K CRI 95 LED Downlight with 36 degree beam angle 120V

tala®



PHYSICAL

Bulb diameter:	1 7/8 in
Bulb length:	2 1/8 in
Glass shape:	GU10
Base:	GU10
Materials:	ceramic and polycarbonate
Glass finish:	Clear
Weight:	0.14 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP20




ELECTRICAL

Power:	7W
Current:	0.06 A
Voltage:	110-120V~ V
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	80 lm/W
Lifetime:	30000 hrs

ILLUMINATION

CCT:	2700K
Lumens:	550 lm
Incandescent equiv.:	45W
Flicker:	<5%
Beam angle:	36°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	100
TM30 - Rf	90

IES/LDT photometry files
and product photography
available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

WARRANTY

2 years

talaighting.com | hello@tala.co.uk | +1 (240) 724-8111

EAN

5061046292069

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights