

Vikan - Cleaning System



Vikan Wet 61,
Wet mopping

Article	Article no.	Size	Recommended frame or holder
40 cm	545440 White Loop 545443 Blue Loop 545444 Red Loop 545446 Yellow Loop	140x480 mm	Vikan composite frame 374218 with exchangeable hooks 376312
60 cm	545460	140x680 mm	Vikan composite frame 374318 with exchangeable hooks 376412
Pocket mop	545400	140x480 mm	Vikan plastic frame 374018 with trigger mechanism
Traceability	First 4 numbers describes the construction and the last numbers indicates the model of the product. Batch number indicates when the product is manufactured, refering to this Vikan can trace the production and take action if necessary.		
Packed	5 pcs. in a plastic bag - 50 pcs. in a carton.		

CLEANING

Where to use:	For all types of heavily soiled surfaces, especially structured floors, entrances and stairways. Perfect for collecting spill and excess moisture. A mop that can be customized for most applications and environments. Avoid any contact with solvents, strong acid or alkaline products.		
How to use:	Preferably used in Vikan® system. A ready-made mop is picked up with the frame - used for 15-30 sqm depending on dirt and hygiene requirements - thereafter released in the laundry bag. Mop can also be used in conjunction with normal cleaning agents if needed. Training is organized by Vikan. Contact our sales organization for further information or set up a meeting.		
Optimum moisture:	250% to achieve best cleaning efficiency and scope		
Preparation:	Use only water, directly in the washing machine with controlled spin-drying process or by using Vikan® preparation lid and box. In case of using cleaning agents we definitely recommend impregnation in lid and box for lowest chemical use.		
Article	Dry weight ± 5 g	ml water	Damp weight ± 15 g
40 cm	115	288	403
60 cm	150	375	525
Pocket mop	125	313	438
Drying speed	Use a dry wet mopp for quick removal of the remaining moisture on the surface, to minimise the risk of slips and falls.		

CARE

Care label			
Care label describes the maximum temperature that should be used. Due to cost, time and environmental impact a reduced temperature should always be evaluated depending on the application.			
Recommended washing	60°C	Use detergents developed for mops and with a pH less than 10. Softner or biocides should not be used as they can cause fiber damage and specific in combination with high temperature.	
Washing in specific hygiene use	72-95°C, depending on time		
Drying instruction	Max 55°C	The recommendation is made to avoid the textile to be damaged if humidity is not controlled.	
Autoclaveable	steam at 121° C - 20 min	Possible to autoclave in steam if required. Other methods must be tested and approved by the originator.	



Vikan - Cleaning System

COMPOSITION

Cleaning surface	45% PES, 40% Co, 15% CV.	The combination of viscose and high denier polyester give an optimized durability and capacity of absorption. Closed inner loop collecting dust and dirt efficiently at the same time this construction protect the spun fibers during use and wash. Open fringe give access in corners and nooks without getting trapped and damaged.
Backing	100 % PA woven loop + 100 % PES conveyor	Long lasting fabric developed for use in damp and demanding conditions.

CHARACTERISTICS

Shrinkage	Less than 5% at recommended washing conditions.
Adsorbency	4-5 times its own weight can be picked up if something has been spilled out.
Staining	No staining in dry or damp condition if recommendation is followed. Some staining can be noticed on other textiles when the higher temperature range is used but separate washing of mops and cloths that are of different construction or used for different applications are recommended.

Developed and manufactured by the Vikan group for professionals.

