

Mojave Hose Reel Adapter Kit # 9.808-276.0

KÄRCHER



Table 1 – Contents of the kit

ITEM	PART NO.	DESCRIPTION	QTY
1	8.929-649.0	Tube retainer Hose reel Black	1 PC
2	8.918-259.0	HOSE 3/8"X 5' APEX 4000 SO/SW (EA)	1 PC
3	4.111-041.0	Adapter complete EASY!Lock TR22IG-3/8NPT	1 PC
4	4.111-042.0	Adapter complete EASY!Lock TR22AG-3/8-NPT	1 PC
5	8.758-159.0	Screw M6-1 X 16 Torx PHSTZNPLT	1 PC

Note: Hose reel not included

Compatible with: **8.750-685.0** **100' pivot hose reel**

TOOLS REQUIRED

- 10" adjustable wrench (2 ea.) or 11/16", 3/4", 24 mm & 27mm open end wrenches
- Torx T30 key

INSTALLATION INSTRUCTIONS

⚠ WARNING: Read all instructions thoroughly. Place machine on level surface. Turn off and unplug machine. Release trapped pressure on the system, prior any service.

Be sure you have all necessary components to install the kit, refer to **Table 1**.

1. Install the hose reel adapter bracket (**item 1**) on the hose reel support at the HDS Mojave frame.
2. Install the pivot hose reel on the adapter bracket. Secure with the M6x16 screw (**item 5**), using torx T30 key. Position the hose reel to the front of the device, in order to keep it away from the burner exhaust.
3. Install the adapter EASY!Lock to male 3/8" NPT (**item 4**) at the hose reel manifold outlet, in order to connect the EASY!Lock hose.
4. Install the adapter EASY!Lock to female 3/8" NPT (**item 3**) at the coil manifold outlet of the HDS Mojave.
5. Connect the 5'x3/8" jumper hose (**item 2**) between the adapter at the coil outlet and the hose reel inlet manifold.

