

LYNX PROFESSIONAL BUILT-IN GRILL SERIES

30" PROFESSIONAL FREESTANDING GRILL

TRIDENT™ AND CERAMIC WITH ROTISSERIE (L30TRF)







L30TRF PRODUCT OVERVIEW

- Cooking system: Ceramic Briquettes over Ceramic Burner and Trident[™] Burner, 48000 BTUs
- Impressive Heat Distribution—resulting in even cooking
- Independent cooking zones—2 burners
- Ample capacity—840 square inches of cooking surface (600 primary, 240 secondary)
- Slow-cooking excellence—with a dual-position rotisserie internally powered by a heavy-duty three-speed motor, and a rear infrared burner delivering up to 14,000 BTU
- Indulgent extra—premium smoker box included
- Beautiful illumination—luminous blue-lit control knobs
- Steady performance—heat-stabilizing design
- Reliable speed—Hot Surface Ignition system lights burners quickly and safely
- Perfect clarity—halogen grill surface light
- Quick visibility—temperature gauge
- Easy opening—Lynx Hood Assist
- Smooth movement—fluid rotation handle
- Premier platform—stainless steel grilling grates
- Steadfast durability—heavy-duty welded construction eliminates gaps where grease can collect
- Open options—available in Natural Gas and LP

PRODUCT TECHNICAL SPECIFICATIONS

L30TRF PRODUCT FEATURES

Our unrelenting attention to detail and our passion for innovation have fostered the stunning features that define the Lynx Professional Series.

These features begin with meticulous hand-crafted excellence, and they culminate in powerful capabilities that give you precision control.



TRIDENT™ INFRARED BURNER




CERAMIC RADIANT BRIQUETTES



SEAMLESS WELDED CONSTRUCTION



HEAT STABILIZING DESIGN



HOT SURFACE IGNITION



EXPANSIVE GRILLING SURFACE



ROTISSERIE SYSTEM



SMOKER BOX



INTEGRATED ILLUMINATION



CERAMIC BURNER



LYNX HOOD ASSIST

FOR MORE
INFORMATION ON
LYNX PROFESSIONAL
PRODUCT FEATURES,
PLEASE VISIT
LYNXGRILLS.COM



PRODUCT DIMENSIONS: WIDTH: 55.75" / HEIGHT: 50" / DEPTH: 27.75"



SHIPPING DIMENSIONS: WIDTH 38.5" / HEIGHT 58.5" / DEPTH 34.25" SHIPPING WEIGHT: 352 POUNDS



GAS REQUIREMENTS: SHIPS IN LIQUID PROPANE OR NATURAL GAS FROM FACTORY



ELECTRICAL REQUIREMENTS: INSTALLATION REQUIRES AN OUTDOOR 120V/15GFI ELECTRICAL OUTLET ADJACENT TO PRODUCT



COOKING CONFIGURATION: FREESTANDING GRILL WITH 1 TRIDENT™ INFRA-RED BURNER AND 1 CERAMIC BURNER AND ROTISSERIE