

# CANDLE

4W | 250 lm | 2000-3000K

CAND-4W-2000-3000K-E12-MP-120V


Candle 4W 2000K to 3000K E12 Matte Porcelain US LED Bulb

tala®



## PHYSICAL

Bulb diameter:	1 3/8 in
Bulb length:	3 7/8 in
Glass shape:	C11
Base:	E12
Materials:	glass and nickel
Glass finish:	Matte White
Weight:	0.03 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP54




## ELECTRICAL

Power:	4W
Current:	0.04 A
Voltage:	110-120V~ V
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	65 lm/W
Lifetime:	15000 hrs

## ILLUMINATION

CCT:	2000-3000K
Lumens:	250 lm
Incandescent equiv.:	25W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	85
TM30 - Rg	100
TM30 - Rf	90

IES/LDT photometry files and product photography available on request



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## WARRANTY

2 years

[talaighting.com](http://talaighting.com) | [hello@tala.co.uk](mailto:hello@tala.co.uk) | +1 (240) 724-8111

## EAN

5061046292144

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights