

TTP095R

Cut Resistant reversed chemical gauntlet

TTP095R is part of a family of gauntlet gloves delivering cut and chemical resistance. With ANSI level A8 cut resistance, level 4 puncture resistance and chemical and liquid protection in one powerful solution, there is a style to suit most handling applications.

The neoprene inner is certified to EN374: 2004 and provides protection against a broad range of chemicals. The reversed style gauntlet is designed for use where cuts and lacerations are the primary risk. The external cut resistant knit protects the chemical barrier from damage caused by mechanical hazards. Alternatively where chemicals are the greater risk the black neoprene gauntlet 095 would be more suitable.



Product Specifications

Product Name	CUT-CHEM™
Product Code	095R
Sizes	7/S – 11/2XL
Glove Base	Tilsatec – RhinoYarn®
Construction	Bonded
Glove Coating	Neoprene inner shell
Cuff/Wrist	Gauntlet
Origin	Malaysia

Packaging

Case Quantity	72 pairs per case
Internal Packaging	6 pairs per poly bag

Performance

ANSI 105: 2016



CUT

EN388: 2003




4543



PUNCTURE:

4

Available Sizes & Cuff Colors

Size	7 S	8 M	9 L	10 XL	11 2X
Cuff					



Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

United States Office
1.877.466.8499
info@tilsatec-na.com
tilsatec.com

Canadian Office
1.866.960.9454
info@tilsatec.net

TTP095R



Performance

ANSI 105: 2016



CUT

EN388: 2003



4 5 4 3

EN407: 2004



X 1 X X X X

EN421: 2010



EN374: 2004



EN374: 2004



A, K, L



AKL

This pictogram is used for liquid proof gloves that have a breakthrough time > 30min. for at least 3 chemical from this list: (AKL represent the code letters for 3 of the these chemicals for which the glove obtained > 30min. breakthrough time)

- A - Methanol
- B - Acetone
- C - Acetonitrile
- D - Dichloromethane
- E - Carbon Disulphide
- F - Toluene

- G - Diethylamine
- H - Tetrahydrofurane
- I - Ethyl acetate
- J - n-Heptane
- K - Sodium hydroxide 40%
- L - Sulphuric acid 96%



Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

United States Office
 1.877.466.8499
 info@tilsatec-na.com
 tilsatec.com

Canadian Office
 1.866.960.9454
 info@tilsatec.net