

Hi-Viz arc and cut resistant leather drivers glove

The TTP230CRFR represents Tilsatec's next generation of high specification leather gloves.

Made with Dupont™ Kevlar® the seamless knitted shell delivers ANSI A6 cut resistance for extreme protection. With its full aramid seams and supple goatskin leather outer the glove also provides electric arc resistance with an ATPV rating of 37cal./cm².



Product Specifications

Product Code	TTP230CRFR
Sizes	7/S – 14/5XL
Glove Base	Tilsatec – RhinoYarn®
Construction	Seamless knit
Glove Shell	Goatskin Leather
Cuff/Wrist	Shirred elastic
Origin	Pakistan

Performance

ANSI 105: 2016



PUNCTURE:
4



NFPA70E Compliant
ASTM F2675 / F2675M - 13



Arc Rating: ATPV = 37 Cal/cm²
Heat Attenuation Factor: HAF = 94%

Packaging

Case Quantity	72 pairs per case
Internal Packaging	12 pairs per poly bag

Available Sizes & Cuff Colors

Size	7 S	8 M	9 L	10 XL	11 2X	12 3X	13 4X	14 5X
Cuff								



Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

United States Office
1.877.466.8499
info@tilsatec-na.com
tilsatec.com

Canadian Office
1.866.960.9454
info@tilsatec.net

USA Modifications & Arc Testing

Split Cowhide Gauntlet + Cut-resistant liner cuff for additional protection of the lower arm area.

4" Leather + Cut Resistance Gauntlet Cuff



4" Cuff - 230CR+FR-GC4 Shown

8" Leather + Cut Resistance Gauntlet Cuff



8" Cuff - 230CR+FR-GC8 Shown

Cut, Flame, and Arc Resistant



TTP230CRFR

ANSI Cut Level A6

ANSI Puncture Level 4

Full FR Construction

NFPA70E Compliant

ASTM F2675 / F2675M - 13

Arc Rating: **ATPV = 37 Cal/cm²**

Heat Attenuation Factor: **HAF = 94%**

Report # K-418922-1602G05-R00

Samples Received:
Feb-16-16

Samples Tested:
Feb-25-16

Test Report

Kinectrics Inc., 800 Kipling Avenue, Unit 2
Toronto, Ontario, Canada
Tel: 416-207-6000, www.kinectrics.com



Tested for

ArcWear
3018 Eastpoint Parkway
Louisville, KY 40223
502-333-0510

Contact information for item tested:

Tilsatec North America
2985 E Roane Ave
Eupora, MS 39744
1-877-466-8499

Test item description

Tilsatec North America, Gloves, Model TTP230CR+FR,
Premium Goatskin, Natural over TTP058F Liner, Knit,

Reference Standard

ASTM F2675 / F2675M - 13
Standard Test Method for Determining Arc Ratings of Hand Protective Products Developed and Used for Electrical Arc
Flash Protection

Test Parameters:

Test current: 8 kA

Arc Gap: 30 cm

Distance to Fabric: 30 cm

Number of samples analysed: 20

Incident Energy Range: 27 to 45 cal/cm²

Arc Rating, ATPV = 37 Cal/cm²

Heat Attenuation Factor, HAF = 94%

No variations to standard method noted.

Samples tested as received, pre-test laundering as required by standard was arranged by client.



Made with Tilsatec Rhino Yarn technology.
Produced in the UK and developed by Tilsatec's
specialist team of yarn technologists to deliver
the optimum in performance and comfort.

United States Office

1.877.466.8499

info@tilsatec-na.com

tilsatec.com

Canadian Office

1.866.960.9454

info@tilsatec.net