

T-Grip

Operating Instructions

- Accuracy to $\pm 0.9^{\circ}\text{F}$ ($\pm 0.5^{\circ}\text{C}$)
- Calibration trim
- Backlight
- Various probes lengths
- IP67 rating
- Extra large digits
- -58 to 572°F range
- 180° auto-rotating display
- $^{\circ}\text{C}/^{\circ}\text{F}$ switchable

Instrument Operation

Press the power button to activate the thermometer. Temperatures will be displayed and the display will auto-rotate depending on orientation. The thermometer will turn off automatically after 10 minutes. This can be disabled. Press and hold the power button for 3 seconds to turn off. To activate the backlight, press the power button once while the instrument is turned on. Press again to turn off.




Insert the stainless steel probe to the desired depth. The measured temperature will be shown on the LCD display within 8 seconds.

To Switch from $^{\circ}\text{F}$ to $^{\circ}\text{C}$

Press and hold the power button for 5 seconds upon start up.

Auto-Off

To disable: Press  button 6 times. Display will flash OFF twice

To enable: Press  button 6 times. Display will flash ON twice.

Auto-off setting is saved even if instrument is turned off.

Battery Installation

Replace the battery when 'LoBat' flashes. Replace with a 3-volt, type CR2032, button-cell battery or equivalent. Use a screwdriver of suitable size to open the battery cover on the back. Install the battery observing the correct polarity, (+) positive side up, sliding the battery into the compartment. Replace the battery cover.



Calibration Trim

From the factory T-Grip should read within $\pm 0.9^{\circ}\text{F}$ and a calibration adjustment should never be needed. For instructions on how and when to perform a one-point calibration trim go to www.thermoworks.com/T-Grip.

Specifications

Measuring Range	-58 to 572°F (-50 to 300°C)
Accuracy	$\pm 0.9^{\circ}\text{F}$ ($\pm 0.5^{\circ}\text{C}$) between 14 to 212°F (-10 to 100°C), $\pm 4.5^{\circ}\text{F}$ ($\pm 2.5^{\circ}\text{C}$) between 392 to 572°F (200 to 300°C); otherwise $\pm 2.7^{\circ}\text{F}$ ($\pm 1.5^{\circ}\text{C}$)
Display Resolution	0.1° over full range
Response	About 8 seconds
IP Rating	IP67
Operating Range	32 to 122°F (0 to 50°C)
Probe - TX-3005	5 L x 0.2 inch dia. reduces to 0.14 inches dia. (127 L x 5.0 mm dia. reduces to 3.5 mm dia.)
Probe - TX-3010	12 L x 0.2 inch dia. reduces to 0.14 inches dia. (305 L x 5.0 mm dia. reduces to 3.5 mm dia.)
Probe - TX-3015	24 L x 0.2 inch dia. reduces to 0.14 inches dia. (610 L x 6.0 mm dia. reduces to 3.5 mm dia.)
Probe - TX-3020	36 L x 0.2 inch dia. reduces to 0.14 inches dia. (914 L x 6.0 mm dia. reduces to 3.5 mm dia.)
Auto-Off	After 10 minutes, can be disabled
Backlight	10 seconds
Battery	CR2032 (3V) lithium coin cell (included) x 1, 4,000 hours
Display	0.70 H x 1.8 W inches (18 H x 47 W mm); Digits: 0.62 H inches (16 H mm)
Product Size	Main Body: 1.14 H x 3.6 W x 1.6 D inches (29 H x 91 W x 42 D mm)

Care and Cleaning

Clean the probe immediately after each measurement to avoid cross contamination. Do not expose the thermometer body to temperatures over 122°F (50°C). Do not leave inside ovens. Avoid submersing the entire thermometer.

Technical Support

For warranty, service, and technical assistance, please contact ThermoWorks' Technical Support at (801) 756-7705 or email at techsupport@thermoworks.com.

For additional cooking tips and doneness temperatures, and to see the full line of ThermoWorks tools, visit our website at www.thermoworks.com.

Chef-Recommended Temps**

For additional temperature recommendations, go to blog.thermoworks.com

Beef, Veal & Lamb Roasts, Steaks & Chops	Rare 120-130°F* 49-54°C	Med. Rare 130-135°F* 54-57°C	Medium 135-145°F* 57-63°C	Med. Well 145-155°F* 63-68°C	Well Done 155°F-up* 68°C-up
Pork Roasts, Steaks & Chops				USDA-Done 145°F* 63°C	Well Done 150°F-up* 66°C-up
BBQ Brisket, Ribs, & Pork Butt					Done 190-205°F 88-96°C

* These temperatures are ideal peak temperatures. Meals should be removed from heat several degrees lower and allowed to rise during resting.

** Chef-recommended temperatures are consistent with many expert sources for taste and safety. USDA-recommended temperatures are 5 to 10°F (2 to 5°C) higher.

Minimum Done Temps for Food Safety

Ground Meat: Beef, Veal, & Sausage*	160°F 71°C	Chicken, Turkey & Duck (whole or pieces)*	165°F 74°C
Ham (raw)	160°F 71°C	Poultry Dark Meat**	175°F 79°C
Ham (pre-cooked)	140°F 60°C	Stuffing (in the bird)	165°F 74°C
Egg dishes	160°F 71°C	Tuna, Swordfish & Marlin**	125°F 52°C
Casseroles & Leftovers	165°F 74°C	Other Fish**	140°F 60°C

Water Temps (at sea level)

Poach	160-180°F 71-82°C	Simmer	185°F 85°C
Low Simmer	180°F 82°C	Slow Boil	205°F 96°C
		Rolling Boil	212°F 100°C

Other Food Temps

Bread: Rich Dough	190-200°F 88-93°C	Butter: Chilled	35°F 2°C
Bread: Lean Dough	200-210°F 93-99°C	Butter: Softened	60-67°F 16-19°C
Water temp to add active dry yeast	105-115°F 41-46°C	Butter: Melted & Cooled	85-90°F 29-32°C

Candy or Sugar Syrup Temps (at sea level)

Thread	230-234°F (110-112°C)	Syrup	
Soft Ball	234-240°F (112-116°C)	Fondant, Fudge & Pralines	
Firm Ball	244-248°F (118-120°C)	Caramels	
Hard Ball	250-266°F (121-130°C)	Divinity & Nougat	
Soft Crack	270-290°F (132-143°C)	Taffy	
Hard Crack	300-310°F (149-154°C)	Brittles, Lollipops & Hardtack	
Caramel	320-350°F (160-177°C)	Flan & Caramel Cages	



www.thermoworks.com
741 E. Utah Valley Dr.
American Fork, UT 84003

ThermoWorks

For service or warranty:
1-800-393-6434
1-801-756-7705
techsupport@thermoworks.com

P-21-005-02-b