

CK3010

KIOTI COMPACT TRACTOR



run ahead of the pack

Specifications



ISO 9001
NO:954596



ISO 14001
NO:771475



OHSAS 18001
NO:K033008

MODEL		CK3010	
		MANUAL	HST
ENGINE			
Model		3A139LWB	
Engine Max HP @ 2900rpm	hp	30	
Engine Gross	hp	28	
Rated revolution	cc	2600	
Total displace	rpm	1393	
Fuel tank capacity	ℓ	25	
DRIVE TRAIN			
Clutch		Dry single	
Transmission		Manual	Hydrostatic
Speeds		3 x 2 (6F2R)	INF. 2
Differential lock (rear)		Standard	
Brake		Wet disc type	
PTO		Transmission	Live
	Rear	rpm	540
	Mid(Optional)	rpm	2,000
HYDRAULIC SYSTEM			
Pump		Gear(Tandem)	
Total Pump capacity at maximum flow	ℓ /min	42.9	
3-point hitch		Cat. 1	
Maximum lifting capacity(24 behind lift point)	kg	739(546)	
Hydraulic lift control system		Position control	
Steering		Hydrostatic Power Steering	
No. of standard remote valve (Rear)		1 (Opt)	1 (Std)
TIRE SIZE			
AG Tire	Front	7-12	
	Rear	11.2-16	
TRAVELING SPEEDS			
Forward	km/h	1.20-17.34	0-17.15
Reverse	km/h	1.48-6.73	0-12.01
DIMENSIONS			
Overall length(including 3-pt hitch)		mm	2,790
Overall width(minimum tread)		mm	1,250
Overall height(from top of ROPS)		mm	2108
Wheelbase		mm	1,520
Min. ground clearance		mm	330
Tread	Front	mm	989
	Rear	mm	950
Weight with ROPS		kg	1,025

Standard Equipment

- Joystick lever with mid mount valve for front loader
- Cruise Control (HST model)
- Hydraulic Power Steering

Optional Equipment

- Front Weight
- Working lamp
- 7-Pin Connector
- Rear Remote Hydraulic Valve (Manual Model Only)



PFG AUSTRALIA
 199 Australis Drive, Derrimut, VIC 3030 Australia
 · tel 03 8353 3600 · fax 03 8353 3699
 web www.kiotitractors.com.au

Dealer Imprint Area