



Class 2 Electrical Insulating Gloves

Applications

- Power Utilities and Public Works
- Substation Installation
- Electric Driven Public Transport Maintenance
- Switchgear and Transformer Maintenance
- EV Battery Manufacturing and Assembly
- EV Aftermarket Service and Maintenance
- Overhead Power Line Maintenance and Repairs
- Excavation and Cable Laying



Code	Length	Color	Cuff	Cat	Proof	Max	Size**	EN Arc	ATPV Arc Rating
24-2024*	14" / 36cm	Dual Black/Red	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2025	14" / 36cm	Dual Black/Yellow	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2026	14" / 36cm	Dual Black/Red	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2027	14" / 36cm	Dual Black/Yellow	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2034	16" / 41cm	Dual Black/Red	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2035	16" / 41cm	Dual Black/Yellow	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2036	16" / 41cm	Dual Black/Red	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2037	16" / 41cm	Dual Black/Yellow	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2044	18" / 46cm	Dual Black/Red	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2045	18" / 46cm	Dual Black/Yellow	Straight / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2046	18" / 46cm	Dual Black/Red	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²
24-2047	18" / 46cm	Dual Black/Yellow	Bell / Beaded	R/C	20.000/50.000	17.000/25.500	8-12	APC 2	21.0 cal/cm ²

AC = Alternative Current (Flows both ways)

DC = Direct Current (Flows one way)

*Stocked

**Including half sizes

Features & Benefits

- Made from 100% natural high grade rubber latex
- Smooth chlorinated surface finish and rolled cuff edge aid donning and doffing
- Environmentally friendly dipping process free from the use of solvents
- Ergonomic design and finger shape minimises hand fatigue
- Increased flexibility in cold environments
- Silicone-free
- Double certification EN 60903 and ASTM D120

Packaging

1 pair p/polybag and individual box.
10 pairs p/carton



EN Category description

R - Acid, Ozone, Oil resistant

C - Extreme low temperature

Certification



Manufactured and tested in accordance with IEC 60903, EN 60903 and ASTM D120.



United States Office

1-877-466-8499 | infona@tilsatec.com
www.tilsatec-na.com

Canadian Office

1.866.960.9454 | info@tilsatec.net

