24-2024

TILSATEC®

Class 2 14" / 36cm Black/Red

Category	A/C/H			
Class	2			
Cuff	Straight with beaded edge			
Max Use	17000V			
Туре	1			
Color	Black/Red			
Length	14" / 36cm			
Sizes	8-11			
Packaging	1 pair p/polybag and individual box. 10 pairs p/carton			

Applications

- Power Utilities and Public Works
- Substation Installation
- Electric Driven Public Transport Maintenance
- Switchgear and Transformer Maintenance
- EV Battery Manufacturing and Assembly
- EV Aftermarket Service and Maintenance
- Overhead Power Line Maintenance and Repairs
- Excavation and Cable Laying



CLASS	LENGTH CM/INCH		CATEGORIES	PROOF TEST VOLTAGE AC/DC	MAXIMUM USE VOLTAGE AC/DC	SIZES
Class 00 Beige	28/11	36/14	A/C	2.500/10.000	500/750	8, 9, 10, 11
Class O Red	28/11	36/14	A/C	5.000/20.000	1.000/1.500	8, 9, 10, 11
Class 1 White	36/14		A/C	10.000/40.000	7.500/11.250	8, 9, 10, 11
Class 2 Yellow	36/14		A/C/H	20.000/50.000	17.000/25.500	8, 9, 10, 11
Class 3 Green	36/14		A/C/H	30.000/60.000	26.500/39.750	8, 9, 10, 11
Class 4 Orange	41/16		A/C/H	40.000/70.000	36.000/54.000	9, 10, 11, 12

Certification



Manufactured and tested in accordance with IEC 60903, EN 60903 and ASTM D120.







Made with Tilsatec Rhino Yarn technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

United States Office 1.877.466.8499 info@tilsatec-na.com

Canadian Office 1.866.960.9454 info@tilsatec.net