

US G4 2700K


2.5W | 220 lm | 2700K
G4-2.5W-2700K-CC-12V

tala®



PHYSICAL

Bulb dimension:	6/8 in
Bulb length:	1 4/8 in
Glass shape:	T6
Base:	G9
Materials:	Ceramic & Polycarbonate
Glass finish:	Lightly frosted
Weight:	0.04 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP20




ELECTRICAL

Power:	2.5W
Current:	0.2 A
Voltage:	12VDC/AC
Frequency:	50/60Hz
Power factor	0.9
Efficiency:	88 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2700K
Lumens:	220 lm
Incandescent equiv.:	22 W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	90

IES/LDT photometry files
and product photography
available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Tala Rotary Wall Dimmer
(For a full list of recommended and compatible
dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America Inc.
C/O LH Frishkoff & Company
546 5th Avenue, FL 9
New York NY 10036
United States

talalighting.com | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

EAN

5056859702287

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights