WOOD REPLICA Porcelain

ARCHITECTURAL CERAMICS



www.architecturalceramics.com

COLORS





9x36 White Smoke

9x36 Beige Digue



6x36 White Smoke*



6x36 Beige Digue*



9x36 Grey Pepper



9x36 Brown Flax



6x36 Grey Pepper*




6x36 Brown Flax*

ARCHITECTURAL CERAMICS

MOSAICS



12"X12" WHITE/GREY TALK MOSAIC



12"X12" BEIGE / BROWN TALK MOSAIC



DYAGO MOSAIC



12"X12" BEIGE / BROWN DYAGO MOSAIC



























AVAILABLE SIZES			PLANK				MOSAIC		TRIM
	12x48	16x48 20 mm	Modular Mixed Sizes	8x71	9x36	6x36	12x12 Dyago	12x12 Talk	3x36 Bullnose
White Smoke	N	N	N	N	N	N*	N	N	Ν
Beige Digue	N	Ν	N	Ν	Ν	N*			Ν
Brown Flax	N	Ν	N	N	N	N*	N	N	Ν
Grey Pepper	N	Ν	N	N	Ν	N*			Ν

N=Natural finish, *Stocked Sizes

Italicized items are special order from Italy with extended lead times. Please consult an ACI sales rep for sample & product availability.

Lead times for specialty & non-stocked items will vary depending on product ordered, quantity, and destination. Please contact ACI to determine the lead time to order samples and material.

DESCRIPTION

Wood Replica is inspired by real wood oak, sessile oak, frakè, olive, walnut, American walnut, chestnut and spruce trunks and under-bark spruce, all very different but united by the color shades decreed by time.

INSTALLATION & MAINTENANCE

Wood Replica may be installed using standard ceramic tile installation methods and materials, as recommended by the Tile Council of North America (TCNA). An Architectural Ceramics sales representative will advise you on general installation questions. Please note that ACI does not recommend grout joints smaller than 1/16" for ACI Stock material.

TECHNICAL INFORMATION

ORIGIN: ITALY AVAILABLE FINISHES: NATURAL TYPE: PORCELAIN EDGE: RECTIFIED LOOK: WOOD APPLICATION: FLOOR & WALL USE: COMMERCIAL & RESIDENTIAL PACKAGING: PLEASE CONSULT YOUR ACI SALES REP FOR PACKAGING INFORMATION COLOR VARIATION: V3 - MODERATE VARIATION THICKNESS: 10.5MM PORCELAIN ENAMEL INSTITUTE SCALE: CLASS 5 - EXTRA HEAVY TRAFFIC, ABRASIVE DIRT, CHEMICALLY MORE RESISTANT. DYNAMIC COEFFICIENT OF FRICTION: 0.42 BREAKING STRENGTH: COMPLIANT TO ASTM C-648 > 250 LBS WATER ABSORPTION: < 0.5% STAIN RESISTANCE: YES FROST RESISTANCE: YES ENVIRONMENT: 7.5% PRE-CONSUMER RECYCLED CONTENT

WEBSITE LINKS

WWW.architecturalceramics.com/catalogs PLEASE NOTE THIS LINK IS CASE SENSITIVE

CONTACT INFORMATION: www.architecturalceramics.com 1.800.287.1742 For general sales inquiries: sales@architecturalceramics.com For commercial & hospitality sample requests: samples@architecturalceramics.com Headquarters: 800 E Gude Dr Suite F Rockville, MD 20850