

# SLIM SLAB LITE

Porcelain

ARCHITECTURAL  
CERAMICS



AVENUE XXL



IVORY



SILVER



PLUMB



AMBER

LIMESTONE



MOON



ASH



DEEP

## PIETRE

---



LAVICA PEARL FACE A\*



LAVICA BEIGE FACE A\*



LAVICA GREY FACE A\*



LAVICA DARK FACE A\*



LAVICA BLACK FACE A\*

ROADS



WHITE PURITY



SAND HEARTH



GREY CALM



COFFEE TRUTH



DARK DEPTH





























































AVAILABLE SIZES		SLAB		
		40x120	40x60	40x40
AVENUE XXL	Ivory	N	N	N
	Silver	N	N	N
	Plumb	N	N	N
	Amber	N	N	N
LIMESTONE	Moon	N		N
	Ash	N		N
	Deep	N		N
PIETRE	Lavica Pearl	N		N
	Lavica Beige	N		N
	Lavica Grey	N		N
	Lavica Dark	N		N
	Lavica Black	N		N
ROADS	White Purity	N		N
	Sand Hearth	N		N
	Grey Calm	N		N
	Coffee Truth	N		N
	Dark Depth	N		N

N=Natural finish  
*Italicized items are special order from Italy with extended lead times & are sold by the pallet.*  
*Please consult an ACI sales rep for sample & product availability.*

Lead times for specialty & non-stocked items varies depending on product ordered, quantity, and destination. Please contact ACI to determine the lead time to order samples and material.

## DESCRIPTION

Slim Slab Lite opens new dimensions for contemporary architecture because it combines low thicknesses with large formats, guaranteeing high technical performance, a lower load on the floors, and an aesthetic quality never seen before. Enhance your room with the unique effects of Slim Slabs visual continuity. Available in 1/4" thickness, Slim Slab is ideal for floors and walls and can be installed indoor or outdoor in any climate.

## INSTALLATION & MAINTENANCE

Please consult the Slim Slab Installation instructions and video links provided below. For additional questions please consult your Architectural Ceramics sales representative.

**INSTALLATION BROCHURE:**

**VIDEO ON MITERING:**

**VIDEO ON HANDLING:**

**VIDEO ON CUTTING:**

**VIDEO ON EXTERIOR INSTALLATION:**

[www.architecturalceramics.com/Datasheets/SLIMSLABINSTALLATION.pdf](http://www.architecturalceramics.com/Datasheets/SLIMSLABINSTALLATION.pdf)

[www.architecturalceramics.com/Datasheets/SLIMSLAB-MITERS.mp4](http://www.architecturalceramics.com/Datasheets/SLIMSLAB-MITERS.mp4)

[www.architecturalceramics.com/Datasheets/SLIMSLAB-HANDLING.mp4](http://www.architecturalceramics.com/Datasheets/SLIMSLAB-HANDLING.mp4)

[www.architecturalceramics.com/Datasheets/SLIMSLAB-CUTS.mp4](http://www.architecturalceramics.com/Datasheets/SLIMSLAB-CUTS.mp4)

[www.architecturalceramics.com/Datasheets/SLIMSLAB-EXTERIOR.mp4](http://www.architecturalceramics.com/Datasheets/SLIMSLAB-EXTERIOR.mp4)

## TECHNICAL INFORMATION

ORIGIN: ITALY

AVAILABLE FINISH: NATURAL

TYPE: PORCELAIN

EDGE: RECTIFIED

LOOK: SLAB

APPLICATION: FLOOR & WALL

USE: COMMERCIAL & RESIDENTIAL

PACKAGING: ALL SLABS & PLANKS DELIVERED ON AN A-FRAME

PLEASE CONSULT YOUR SALES REP FOR PACKAGING INFORMATION

COLOR VARIATION: N/A

THICKNESS: 6 MM

PORCELAIN ENAMEL INSTITUTE SCALE: N/A

DYNAMIC COEFFICIENT OF FRICTION: 0.61 (HONED FINISH),  
0.24 (POLISHED FINISH)

BREAKING STRENGTH: COMPLIANT TO ASTM C-648 > 250 LBS

WATER ABSORPTION: < 0.5%

STAIN RESISTANCE: YES

FROST RESISTANCE: YES

ENVIRONMENT: N/A

## WEBSITE LINKS

[www.architecturalceramics.com/Datasheets/SLIMSLABLITE.pdf](http://www.architecturalceramics.com/Datasheets/SLIMSLABLITE.pdf)

PLEASE NOTE THIS LINK IS CASE SENSITIVE

## CONTACT INFORMATION:

[www.architecturalceramics.com](http://www.architecturalceramics.com)

1.800.287.1742

For general sales inquiries: [sales@architecturalceramics.com](mailto:sales@architecturalceramics.com)

For commercial & hospitality sample requests: [samples@architecturalceramics.com](mailto:samples@architecturalceramics.com)

Headquarters: 800 E Gude Dr Suite F Rockville, MD 20850