

DIESEL LIQUID STONE

Porcelain



ARCHITESSA

an Architectural Ceramics brand





Diesel Liquid Stone Moss 12x24; 24x24

DIESEL LIQUID STONE



Diesel Liquid Stone Moss 1x30

DIESEL LIQUID STONE



Diesel Liquid Stone Mud 24x48

DIESEL LIQUID STONE



Diesel Liquid Stone Sand 24x24

COLORS



Black



Bronze



Inox



Moss



Mud



Sand

AVAILABLE SIZES	FIELD			MOSAIC			TRIM		
	24x48	24x24	12x24	1x1 NOMINAL	2x2 NOMINAL	1x12 NOMINAL	3x24 Base Board	6x12 Step Edge Cover	12x24 Step/Stair Tread
Black	N, R11	N, R11	N, R11	N	N	N	N	N	N
Bronze	N, R11	N, R11	N, R11	N	N	N	N	N	N
Inox	N, R11	N, R11	N, R11	N	N	N	N	N	N
Moss	N, R11	N, R11	N, R11	N	N	N	N	N	N
Mud	N, R11	N, R11	N, R11	N	N	N	N	N	N
Sand	N, R11	N, R11	N, R11	N	N	N	N	N	N

N= Natural, R11= Anti-slip R11

Lead times for specialty & non-stocked items varies depending on product ordered, quantity, and destination. Please contact Architessa to determine the lead time to order samples and material.

DESCRIPTION

With an unpredictable soul, it recombines at each new moment, dancing in a hypnotic texture. Everything is liquid, constantly changing to remind us to stop and think, every now and then, about that moment that becomes stone, and it is forever.

INSTALLATION & MAINTENANCE

Diesel Liquid Stone may be installed using standard porcelain installation methods and materials, as recommended by the Tile Council of North America (TCNA). An Architessa sales representative will advise you on general installation questions.

TECHNICAL INFORMATION

ORIGIN: ITALY
 AVAILABLE FINISHES: NATURAL (R10) AND ANTISLIP (R11)
 TYPE: PORCELAIN
 EDGE: RECTIFIED
 LOOK: STONE
 APPLICATION: FLOOR AND WALL
 USE: INTERIOR AND EXTERIOR RESIDENTIAL/
 COMMERCIAL
 PACKAGING: PLEASE CONSULT YOUR SALES REP
 COLOR VARIATION: V3

THICKNESS: 9 MM
 PORCELAIN ENAMEL INSTITUTE SCALE: MUD, BRONZE,
 INOX, BLACK - 3 SAND, MOSS - 4
 DYNAMIC COEFFICIENT OF FRICTION: SLIP RESISTANCE
 CLASSIFICATION DIN51130 -R10 AND R11
 BREAKING STRENGTH: > 1700 N
 WATER ABSORPTION: ≤0.1%
 STAIN RESISTANCE: YES, CLASS 3 MINIMUM
 FROST RESISTANCE: YES
 ENVIRONMENT: >40% RECYCLED CONTENT

WEBSITE

www.architessa.com/products

CONTACT INFORMATION:

www.architessa.com

1.800.287.1742

For general sales inquiries: sales@architessa.com

For commercial & hospitality sample requests: samples@architessa.com

Headquarters: 1803 Research Blvd. Suite 402 Rockville, MD 20850