DIESEL LIQUID STONE 🛞 ARCHITESSA





an Architectural Ceramics brand











www.architessa.com









www.architessa.com



COLORS



Black



Bronze



Inox



Moss



Mud



Sand



AVAILABLE SIZES	FIELD			MOSAIC			TRIM		
	24x48	24x24	12x24	1x1 nominal	2x2 NOMINAL	1x12 nominal	3x24 Base Board	6x12 Step Edge Cover	12x24 Step/Stair Tread
Black	N, R11	N, R11	N, R11	Ν	N	Ν	N	Ν	Ν
Bronze	N, R11	N, R11	N, R11	Ν	Ν	Ν	Ν	Ν	Ν
Inox	N, R11	N, R11	N, R11	Ν	Ν	Ν	Ν	Ν	Ν
Moss	N, R11	N, R11	N, R11	Ν	Ν	Ν	Ν	Ν	Ν
Mud	N, R11	N, R11	N, R11	Ν	Ν	Ν	Ν	Ν	Ν
Sand	N, R11	N, R11	N, R11	Ν	Ν	Ν	Ν	Ν	Ν

N= Natural, R11= Anti-slip R11

Lead times for specialty & non-stocked items varies depending on product ordered, quantity, and destination. Please contact Architessa to determine the lead time to order samples and material.

DESCRIPTION

With an unpredictable soul, it recombines at each new moment, dancing in a hypnotic texture. Everything is liquid, constantly changing to remind us to stop and think, every now and then, about that moment that becomes stone, and it is forever.

INSTALLATION & MAINTENANCE

DIESEL LIQUID STONE may be installed using standard ceramic tile installation methods and materials, as recommended by the Tile Council of North America (TCNA). An Architessa sales representative will advise you on general installation questions.

TECHNICAL INFORMATION

TYPE: PORCELAIN ORIGIN: ITALY EDGE: RECTIFIED THICKNESS: 9 MM LOOK: STONE SHADE VARIATION: 3 - MODERATE SURFACE ABRASION: MUD, BRONZE, INOX, BLACK - 3 SAND, MOSS - 4 TRAFFIC RATING: COMMERCIAL DCOF: SLIP RESISTANCE CLASSIFICATION DIN51130 -R10 AND R11 BREAKING STRENGTH: >1700 N WATER ABSORPTION: ≤0.1% STAIN RESISTANCE: YES, CLASS 3 MINIMUM FROST RESISTANCE: YES ENVIRONMENT: >40% RECYCLED CONTENT

CONTACT INFORMATION:

www.architessa.com 1.800.287.1742 For general sales inquiries: sales@architessa.com For commercial & hospitality sample requests: samples@architessa.com Headquarters: 1803 Research Blvd. Suite 402 Rockville, MD 20850