

## Nozzles and Accessories

Image for illustrative purposes only.  
Spray tank not included.

4.8 metres

4.8 metres

9.6 metres full spray reach

### TPL BOOMLESS NOZZLE

Specifically designed for a 3 point linkage unit running between 30 and 60 psi spraying pressure. It can spray up to 9.6 metres wide and is available with an optional mounting bracket that fits between the upright bars on Silvan linkage equipment.

- Sprays 4.8 metres one side or 9.6 metres both sides together
- Can spray one or both sides with blanking cap included
- Fitted with 2.5 metres of Ag hose
- Nozzle reorder code: For blue FC-XT020 Hypro boomless nozzle



M99-76

Application Rate Chart M99-76 Litres/Hectare

Application Rate Chart M99-76 Litres/Hectare											
Application Rate L/ha at km/hr											
Description	Swath (M)	Bar	L/min	4 kmh	5 km/hr	6 km/hr	8 km/hr	10km/hr	12km/hr	14km/hr	16km/hr
Single Side 1 Nozzle		2	6.4	200	160	133	100	80	67	57	50
	4.8	3	7.9	247	198	165	123	99	82	71	62
		4	9.1	284	228	190	142	114	95	81	71
	Swath (M)	Bar	L/min	4 kmh	5 km/hr	6 km/hr	8 km/hr	10km/hr	12km/hr	14km/hr	16km/hr
Double Side 2 Nozzle		2	12.8	200	160	133	100	80	67	57	50
	9.6	3	15.8	247	198	165	123	99	82	71	62
		4	18.2	284	228	190	142	114	95	81	71

CODE	DESCRIPTION	PRESSURE	L/MIN (UP TO)	SWATH WIDTH	NOZZLE COLOUR	CAT
M99-76	Boomless Nozzle Kit 2 Jet	2 Bar/30 psi	18.2	10.4		B
K99-10	Mounting Bracket (Suit Super Series TPL)					B