
## **Garden Valves**

125 lb. CWP to 100°F Maximum Temperature 180°F

| GARDEN VALVE MATERIALS LIST |                                      |  |  |
|-----------------------------|--------------------------------------|--|--|
| PART                        | SPECIFICATION                        |  |  |
| Body                        | Cast Copper - Based Alloy C84400     |  |  |
| Bonnet                      | Cast Copper - Based Alloy C84400     |  |  |
| Stem                        | Cold-formed Copper Alloy             |  |  |
| Seat Disc                   | Buna-N                               |  |  |
| Seat Disc Screw             | Stainless Steel, Type 410            |  |  |
| Packing Nut                 | Free Cutting Brass - ASTM B 16       |  |  |
| Packing                     | Graphite Impregnated, Asbestos-Free  |  |  |
| Handwheel                   | Epoxy Coated Zinc Alloy              |  |  |
| Handwheel Screw             | Carbon Steel - Clear Chromate Finish |  |  |





61

| DESCRIPTION                        | Nom.<br>Size | DIMENSIONS<br>B | APPROX.<br>NET WT. |
|------------------------------------|--------------|-----------------|--------------------|
| Bent Nose Hose Bibb<br>FIP to Hose | 1/2"         | 35/8"           | .60 lb             |
|                                    | 3/4"         | 33/4"           | .70 lb             |

 $\Lambda$ 

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.