

# PIXAPRO® Studio Strobe Comparison

					
<b>Model</b>	<b>LUMI200 II</b>	<b>LUMI400 II</b>	<b>STORM II 400</b>	<b>STORM II 600</b>	<b>KINO II 600+</b>
<b>Power Output</b>	200Ws	400Ws	400Ws	600Ws	600Ws
<b>Guide Number (ISO 100)</b>	49m	65m	65m	76m	76m
<b>Recycle Times</b>	0.3 -1 sec	0.3 - 1.5 sec	0.05~0.7 sec	0.05-0.9 sec	0.3-1.5 sec
<b>Flash Duration</b>	1/2000-1/800 sec	1/2000-1/800 sec	1/35086 - 1/416 sec	1/316s - 1/28984s	1/2000-1/800 sec
<b>Power Range</b>	1/1 - 1/32 (6 Stops)	1/1 - 1/32 (6 Stops)	1/1 - 1/64 (7 Stops)	1/1 - 1/128 (8 Stops)	1/1 - 1/32 (6 Stops)
<b>Modelling Light</b>	150w	150w	150w	150w	150w
<b>Colour Temperature</b>	5600K ± 200K	5600 ± 200K	5600 ± 100K	5400 ± 200K In Stable Colour Mode - Figures may Vary in Different Modes	5600 ± 200K
<b>Trigger Method</b>	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port
<b>Optical Slave Modes</b>	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)
<b>High-Speed Sync</b>	No	No	No	Yes (Requires ST-III)	No
<b>Built-In Receiver Flash</b>	No	No	No	Yes	No
<b>IGBT Technology</b>	No	No	Yes	Yes	No
<b>Dimensions</b>	Diameter Ø11.4CM 21.9cm Height	Diameter Ø12.5CM 25cm Height	Diameter Ø12.5CM 25cm Height	Ø 14cm x 23cm x 41cm	Ø 14cm x 23cm x 41cm
<b>Weight</b>	Approx 2.0kg	2.0kg	2.0kg	2.96kg	3.0kg