


PIXAPRO® Studio Strobe Comparison

					
Model	0200	0	620400	S20II 600	12II 600
Power Output	200Ws	400Ws	400Ws	600Ws	600Ws
Guide Number (ISO 100)	49m	65m	65m	76m	76m
Recycle Times	0.3 -1 sec	0.3 - 1.5 sec	0.05~1/3sec	0.05-0.9 sec	0.3-1.5 sec
Flash Duration	1/2000-1/800 sec	1/2000-1/800 sec	1/□ - 1/13sec	1/316s - 1/28984s	1/2000-1/800 sec
Power Range	1/1 - 1/32 (6 Stops)	1/1 - 1/32 (6 Stops)	1/1 - 1/64 (7 Stops)	1/1 - 1/128 (8 Stops)	1/1 - 1/32 (6 Stops)
Modelling Light	150w	150w	150w	150w	150w
Colour Temperature	5600K ± 200K	5600 ± 200K	5600 ± 100K	50± 200K In Stable Colour Mode - Figures may Vary i Different Modes	5600 ± 200K
Trigger Method	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port	Built-In ST-III Receiver, Sync cord, Test button, Slave triggering, wireless control port
Optical Slave Modes	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)	Yes (S1 & S2)
High-Speed Sync	No	No	No	Yes (Requires ST-III)	No
Built-In Receiver Flash	No	No	No	Yes	No
IGBT Technology	No	No	Yes	Yes	No
Dimensions	Diameter Ø10CM□ 26m Height	Diameter Ø12.5CM 25cm Height	Diameter Ø12.5CM 25cm Height	Ø 14cm x 23cm x 41cm	Ø 14cm x 23cm x 41cm
Weight	SSR kg	2.0kg	2.0kg	2.96kg	3.0kg