


BOWER PENDANT LIGHT C220 GREEN WITH SPHERE G100

tala®

SKU: BWR-C220-GRN-SPHR-III-01-EU/ BWR-C220-GRN-SPHR-III-01-US

FINISH: DARK GREEN



FIXTURE - PHYSICAL

Pendant dimension:	L220mm x W220mm x H230mm L8 5/8in x W8 5/8in x H9in
Ceiling rose dimension:	L110mm x W110mm x H28mm L4in x W4in x H1in
Cable length:	3m 10in
Materials:	Steel and Aluminium
Finish:	Yellow
Weight:	820g 1.8lbs
IP rating:	IP20 - Suitable for dry locations
Base:	E27 E26

BULB - PHYSICAL

Bulb dimension:	L100mm x W137mm L3 7/8in x W5 3/8 in
Glass shape:	G100
Materials:	Glass and nickel
Glass finish	Matte White
Weight	122g 0.27lbs
Max. working temp.:	-5 to 40 °C
IP rating:	IP54
Power:	7W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Base:	E27 E26

ILLUMINATION

CCT:	2000-2800K
Lumens:	600lm
Incand equiv:	48W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	90
TM30-Rg:	95
TM30-Rf:	101

The light source can all be easily replaced.
For replacement parts, please visit our
website or contact us at customerservice@tala.co.uk.

ELECTRICAL

Wattage:	Max 60W
Voltage:	220-240V 110-120V
Frequency:	50/60Hz



DIMMING

Dimmable 0-100%
Recommended dimmer Lutron Diva DVELV-300P

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

WARRANTY

2 years

Tala Europe B.V. Bertus Aafjeshove 40
Nieumwegein 3437 JN

EAN

5061046292427
5061046292458

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights