

www.stephill-generators.co.uk +44 (0) 1933 677911

GE3300

3.3kVA Petrol Generator

GENERATOR SPECIFICATION		ENGINE SPECIFICATION	
Voltage	230/115	Engine	Honda GP200
Phase	1	Emissions certified	N/A
Frequency	50Hz	Cylinders	Single
Prime Power (PRP)	3.3 kVA / 2.6 kW	Distribution	0.H.V.
Alternator	NSM K80C	Aspiration	Normally aspirated
Alternator Type	Brushless - Smooth Waveform	Cooling	Air
Fuel tank capacity	3.1 Litres	Displacement	196 cm ³
Autonomy 75% load	2.5 Hours	Rpm	3000
LWA	96	Starting system	Recoil
dBA @ 7M	71	Fuel	Unleaded 86 octane or higher



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	36
610	420	415	



24 Months Non-Commercial Engine Warranty (Limited)3 Months Commercial Engine Warranty (Limited)

CONTROL BOX (Plastic)

- 1 x 16A 230V & 1 x 16A 115V BS4343 sockets.
- Reset circuit breaker overload protection.
- Voltage selector switch.

STANDARD FEATURES

POWER DEFINITION

- Oil alert/low oil shutdown.
- Full wrap-around frame.
- Brushless smooth waveform alternator.

OPTIONS

- Single voltage.
- Trolley kit.

Prime Power (PRP) : Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.



