

www.stephill-generators.co.uk +44 (0) 1933 677911

SE34003SLR

3.4kVA Long Run Tank Petrol Generator

GENERATOR SPECIFICATION		ENGINE SPECIFICATION	
Voltage	230/115	Engine	Honda GX200
Phase	1	Emissions certified	EU Stage V
Frequency	50Hz	Cylinders	Single
Prime Power (PRP)	3.4 kVA / 2.7 kW	Distribution	O.H.V.
Alternator	NSM K80C	Aspiration	Naturally aspirated
Alternator Type	Brushless - Smooth Waveform	Cooling	Air
Fuel tank capacity	11.0 Litres	Displacement	196 cm³
Autonomy 75% load	9.1 Hours	Rpm	3000
LWA	96	Starting system	Recoil
dBA @ 7M	71	Fuel	Unleaded 86 octane or highe



DIMENSIONS (mm)			WEIGHT (KG)
Length	Width	Height	40
610	420	540	





CONTROL BOX (Plastic)

- 115V: 2 x 16A BS4343 sockets.
- 230V: 1 x 16A BS4343 sockets.
- Reset circuit breaker overload protection.
- Voltage selector switch.

OPTIONS

- Single voltage.
- Trolley kit.

STANDARD FEATURES

- Oil alert/low oil shutdown.
- 3 Year engine warranty (Limited).
- Full wrap-around frame.
- Brushless smooth waveform alternator.

POWER DEFINITION

Prime Power (PRP): Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.