

**GENERATOR SPECIFICATION**

|                           |                             |
|---------------------------|-----------------------------|
| <b>Voltage</b>            | 230/115                     |
| <b>Phase</b>              | 1                           |
| <b>Frequency</b>          | 50Hz                        |
| <b>Prime Power (PRP)</b>  | 4.0kVA / 3.2kW              |
| <b>Alternator</b>         | NSM K100F                   |
| <b>Alternator Type</b>    | Brushless - Smooth Waveform |
| <b>Fuel tank capacity</b> | 13.0 Litres                 |
| <b>Autonomy 75% load</b>  | 13.0 Hours                  |
| <b>LWA</b>                | 97                          |
| <b>dBA @ 7M</b>           | 71                          |

**ENGINE SPECIFICATION**

|                            |                     |
|----------------------------|---------------------|
| <b>Engine</b>              | Kohler KD-350GE530  |
| <b>Emissions certified</b> | EU Stage V          |
| <b>Cylinders</b>           | Single              |
| <b>Distribution</b>        | O.H.V.              |
| <b>Aspiration</b>          | Normally aspirated  |
| <b>Cooling</b>             | Air                 |
| <b>Displacement</b>        | 349 cm <sup>3</sup> |
| <b>Rpm</b>                 | 3000                |
| <b>Starting system</b>     | Recoil              |
| <b>Fuel</b>                | Diesel              |



**KOHLER**  
IN POWER. SINCE 1920.

**DIMENSIONS (mm)**

| Length | Width | Height | WEIGHT (KG) |
|--------|-------|--------|-------------|
| 775    | 475   | 560    |             |

**WEIGHT (KG)**

84


**CONTROL BOX**

- 1 x 16A & 1 x 32A 115V BS4343 sockets.
- 1 x 16A 230V BS4343 socket.
- Reset circuit breaker overload protection.

**STANDARD FEATURES**

- Long run fuel tank.
- Easy carry fold-away handles.
- Brushless smooth waveform alternator.

**OPTIONS**

- Single voltage.
- Electric start (SE4000DLES)
- Trolley kit.

**POWER DEFINITION**

**Prime Power (PRP) :** Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1 under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.