



Module B and C2 approval:
CCOS Certification Services Ltd.
Block 1, Blanchardstown Corporate
Park, Ballycoolin Road,
Blanchardstown, Dublin,
D15 AKK1, Ireland

Notified Body Number 2834



GB

INSTRUCTIONS FOR USE



55-4173 - Nitrile cut level D/A4 chemical gauntlet with microfoam palm coating

Sizes	Cuff Colour	Sizes	Cuff Colour
Size 7 - S	Blue	Size 10 - XL	Black
Size 8 - M	Green	Size 11 - 2XL	Brown
Size 9 - L	Red	Size 12 - 3XL	White

EN ISO 374-1/Type A



J K L M N O

EN ISO 374-5:2016




ANSI/ISEA
105-2024



Mechanical Protection
EN 388: 2016+A1:2018



4 X 4 2 D




Abrasion (0-4) Cut (0-5) Tear (0-4) Puncture (0-4) ISO13997 (A-F)

Heat Protection
EN 407: 2020



X 1 X X X X



Limited flame spread (0-4) Contact heat (0-4) Convective heat (0-4) Radiant heat (0-4) Small drops molten metal (0-4) Large quantity molten metal (0-4)

x = not tested

NORTH AMERICA

5770 N. Hix Road,
Westland, MI 48185, USA

Tel: +001 877-466-8499
infona@tilsatec.com
customerservice@tilsatec.com

UK & EUROPE

United Kingdom
Tilsatec Limited, Flanshaw Lane,
Wakefield, West Yorkshire,
WF2 9ND, England

Tel: +44 (0)1924 375742
info@tilsatec.com
customerservice@tilsatec.com

Canada

Tel: +001-866-960-9454
info@tilsatec.net
customerservice@tilsatec.net

Mexico

info-mex@tilsatec-na.com

CE Marking conforms with EU PPE Regulation [EU] 2016/425. Do not use where there are electrical, flame or entanglement risks. Place dry hand into the glove to don and do not reverse the gloves – always wear in the form supplied and only wear gloves of a suitable size ensuring a good fit at the finger crotch and length. Remove by inverting cuff with opposite hand, turning inside out. Gloves will not lose their protective properties for up to 5 years after manufacturing provided that they are stored in accordance with these recommendations but you are always advised to carefully inspect the gloves before use. The gloves are intended to provide chemical and mechanical protection in industrial applications. They contain high stretch material which causes shrinkage in the relaxed state and therefore may not conform to the BS EN ISO 21420:2020 length requirements. Never use damaged PPE and replace immediately if signs of wear are evident. Repair of PPE is not permitted. Store in a well ventilated area away from extremes of temperature. The gloves have been tested according to BS EN ISO 374-1:2016+A1:2018 Permeation and BS EN ISO 374-4:2019 Degradation against the following chemicals

Code	Chemical	EN374-1:2016+A1:2018/Type A Permeation Performance Level	Breakthrough Time (min)	EN374-4:2019 Degradation %
J	n-Heptane	6	>480	23.87
K	Sodium Hydroxide 40%	6	>480	35.59
L	Sulphuric Acid 96%	3	72	30.97
M	Nitric Acid 65%	2	56	81.68
N	Acetic Acid 99%	3	74	53.88
O	Ammonium Hydroxide 25%	6	>480	18.80

This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is tested also) and relates only to the chemical tested. It can be different if the chemical is used in a mixture. Degradation results indicate the change in puncture resistance of the gloves after exposure to the challenge chemical. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen. The gloves have been tested for protection against bacteria and fungi according to BS EN ISO 374-5:2016

WARNING: Not tested against viruses

Suitable for EN407: 2020 level 1 contact heat involving handling materials at 100°C for up to 15 seconds. Gloves do not offer flame protection. The gloves are not suitable for washing. The properties have been tested as new and not after laundering. It is the responsibility of the user to determine if the PPE is fit for use following any cleaning procedure. Gloves are made from a blend of engineered textile fibres – a list of the raw materials used is available upon request. In case of decontamination, cleanse outer surface of glove according to relevant MSDS instructions. Dispose of in accordance with Local Authority Regulations.

Issue 1: July 2023

EU declaration of conformity can be viewed at <http://tilsatec.com/resources>

EU Authorised Representative: Advena Limited, Tower Business Centre,
2nd Floor, Tower Street, Swatar, BKR 4013, Malta