SIDE BURNERS
SPECIFICATIONS
& INSTALLATION

## **PRODUCT**

Sunstone Single & Double Side Burners

Item No. 1SSB Item No. 2CSB

### DESCRIPTION

Sunstone Single and Double Side Burners

#### **SPECIFICATIONS**

304 Stainless Steel, 18 Gauge for Burner Structure, 18 Gauge for Single Burner Cover. Handles are made of Zinc Alloy, Chrome Plated.

### WARRANTY

- EXTERIOR FINISH ------3 YEARS
   STRUCTURE ------3 YEARS
- HANDLE, VALVES, KNOB-----1 YEAR
- BURNER -----LIFETIME WARRANTY

## **INSTALLATION REQUIRMENTS**

- **COMBUSTABLE MATERIALS:** For Wood Framed Island Construction is Extremely important Not to use any wood within 24" Inches of Side Burner. Wood frame is fine for Bar/Sink areas and or Storage compartments. If your island is mostly wood, just substitute for Metal Studs while within the 24" Inches of Side Burner. If the island is against any Combustible Materials be sure to provide protection and keep a minimum distance of 8-1/2" Inches away.
- 2 ISLAND VENTILATION: For every Gas-Related appliance Grill or Side Burner you are required to have at least Two Air-Vents in the Island, within 24" Inches of Appliance. Place Two Vents in Low position 2" to 4" from base on exterior wall when using Liquid Propane and place Two Vents in High position 2" to 4" Inches below the counters bottom edge for Natural Gas. Do not Build Enclosure under Side Burners, Side burners are meant to Free-Hang from counter top surface.
- GAS SAFETY & ACCESS: For either Natural Gas or Liquid Propane type, it is required you have clear access to all interior island Gas-Plumbing, we recommend placing one of Sunstone's Single Access Vented Doors, like item no. A-DV1420, or A-DV1724. Also have at least One Safety-Shut Off Valve Present and within easy access, if this appliance is being installed in a High-Traffic location like for Residential Community, it is important to have installed a Shut-Off Timer set for Auto-Shut off in 20 Minutes.

## **PRODUCT SPECIFICATIONS**

	<u> </u>	<u> </u>
ITEM NO.	PRODUCT SIZE	CUT-OUT
Double Sli	de-In Side Burner	
2CSB	13"W x 22-1/2"D x 12-1/2	12"W x 20-1/4"D x 8"H
Single Dro	p-In Side Burner	
1SSB	11"W x 17"D x 4"H	10"W x 16-1/8"D

# **PLACING:** Allow 3" to 4" of space on either side for better access Place Vents in High and larger frying pans Position for All Natural Gas Installations Place Vents in Low Position for All Liquid Propane **Installations** Helpful to add Propane Storage Solution Below

## **MOUNTING**

Locate the side burner only in a well-ventilated area. Never locate the side burner in a building, garage, breezeway, shed or other such enclosed areas without an approved ventilation system. During heavy use, the side burner will produce a lot of smoke. Ensure there is adequate area for it to dissipate.

The two illustrations demonstrate how the slide-in type unit is designed to fit into openfront enclosures on the Left and on the Right the Drop-In Style is supported at the Countertop.



