

## Specifications

Product Line	Woodland Collection
Product Type	Stone Polymer Composite
Core Material	Rigid Polymeric Core
Wear Layer	12mil
Overall Thickness	5.0mm
Nominal Plank Size	7" x 48"
Actual Plank Size	180 mm x 1220 mm
Edge Profile	Matte Bevel
Embossing	Ceramic
Finish	UltraShield Coating
Installation Type	Floating   2G Valinge
Attached Pad	1.0mm IXPE Sound Reducing

## Shipping

### CARTON

Planks	12
Square Feet	28.05
Weight (lbs)	48
Square Meters	2.606
Weight (kg)	21.77

### PALLET

Cartons	45
Square Feet	1,262.25
Weight (lbs)	2,234
Square Meters	117.267
Weight (kg)	1,013.33

### CONTAINER

Cartons	1,170
Square Feet	32,818.50
Weight (lbs)	58,084
Square Meters	3,048.942
Weight (kg)	26,346.45

## Warranty



**20 YEAR  
RESIDENTIAL**



**10 YEAR  
COMMERCIAL**



WATERPROOF  
MATERIAL



UNIQUE PLANK  
PATTERN VARIATION



SCRATCH &  
STAIN RESISTANT

## Performance Testing

Slip Resistance	ASTM D2047	R9   Class DS
Castor Chair	EN 426	PASS (15,000 Cycles)
Dimensional Stability	ISO 23999	PASS
Light Resistance	ASTM F1515	PASS
Heat Resistance	ASTM F1514	PASS
Fire Resistance and Smoke Emission	EN ISO 9239-1	Class Bfl s1
Chemical Resistance	ASTM F925	PASS
Phthalate Content	CPSC-CH-C1001-09.3	Not Detected
Heavy Metals	ASTM F963	PASS
VOC Emission	BS ISO 16000 / ASTM D5116	Certified FloorScore & GreenGuard Gold
Vinyl Chloride Monomer (VCM) Content	ASTM D4443-95(2002)	Not Detected

## Sound Testing

Sound testing was conducted over a 150mm thick concrete floor and the 5.0mm SPC Flooring (including 1mm IXPE underlayment) were placed on the concrete floor.

Delta Impact Sound Insulation Class	ASTM E2179-09	$\Delta IIC = 18$
Impact Sound Insulation Class (IIC)	ASTM E492-09	IIC = 59
Sound Transmission Class (STC)	ASTM E413-22	STC = 52